



Specialty Inks for Hard to Mark Surfaces

## Product Specification

### AERO 613

IIMAK Product Category	Non Standard
General Description	Extremely heavy marking ink which contains extra pigment, ideal for applications which require a very deep, intense color. Commonly used in a wide variety of non-porous applications, including rubbers, plastics, foils, metals, and woods.
System	Solvent
Colors	White*, Yellow* Custom Colors (MOQ may apply): n/a, Color matching available
Sizes Available	Quart, Gallon (call for additional sizes)
Colorant	Pigment
Surface Type	Non-porous
Typical Substrates	Non-porous rubber, plastic, foil, metal, wood
Suggested Printing Method	Flexo coders, hand stamp
Regulatory / Certifications	REACH, RoHS, HAPS Free
Dry Time	45 seconds
Recommended Reactivator Thinner / Cleaner / Solvent	141 Solvent/Reactivator Contact IIMAK Inks for mixing ratios to alter dry times if needed.
Shelf Life (Unopened Container)	Dye - 12 months / Pigment - 6-9 months

\*Pigment

September 2013

Data provided is for reference only, testing of ink in your application is recommended. For more information, please contact IIMAK Inks or refer to Safety Data Sheet.

IIMAK Inks – A Division of International Imaging Materials, Inc  
310 Commerce Drive • Amherst, NY 14228

Phone: 866-535-3439 • Fax: 866-497-3657 • Email: [orders@iimakinks.com](mailto:orders@iimakinks.com)  
Website: [www.iimakinks.com](http://www.iimakinks.com)