

Product Information

Silicone Sealant



DOW CORNING

Dow Corning® 7094 Flowable Sealant

FEATURES & BENEFITS

- One component adhesive/sealant
- Cures at room temperature when exposed to moisture in the air
- Alkoxy cure system
- Flowable and self-leveling
- Easy to apply
- Excellent unprimed adhesion to many substrates
- Stable and flexible from -50°C to +180°C
- Non corrosive to metals
- Low odor
- Unprimed adhesion to mixed substrates

COMPOSITION

- Silicone Adhesive/Sealant

One component, flowable neutral cure silicone adhesive/sealant

APPLICATIONS

- Sealing and bonding applications where low viscosity and self-leveling properties in combination with non-corrosive cure is required
- Designed for applications which demand a strong but flexible bond such as when bonding materials with differing thermal expansion rates e.g., glass to metal or glass to plastic
- Low modulus formulation for high movement capability
- Sealing in gaps where an elastic grouting is required

TYPICAL PROPERTIES

Specification Writers: These values are not intended for use in preparing specifications. Please contact your local Dow Corning sales office or your Global Dow Corning Connection before writing specifications on this product.

Test*	Property	Unit	Result
As Supplied			
	Appearance		Black or white, viscous liquid
CTM 0097B	Density	g/cm ³	1.30
CTM 0050	Viscosity	mPa·s	28,000
CTM 0098	Skin-over-time (23°C, 50% R.H.)	Min	25
CTM 0095A	Tack-free-time (23°C, 50% R.H.)	Min	50
Mechanical Properties, cured 7 days in air at 23°C and 50% R.H.			
CTM 0137A	Tensile Strength	MPa	1.2
CTM 0137A	Elongation at Break	%	400
CTM 0137A	Modulus at 100%	MPa	0.36
CTM 0099	Hardness, Shore A		19

*CTM: Corporate Test Method, copies of CTM's are available on request.

DESCRIPTION

Dow Corning® 7094 Flowable Sealant is a black or white, low modulus silicone adhesive/sealant designed for applications where a flowable product and noncorrosive cure with durable adhesion to a variety of substrates is required. The flowable properties allow spray applications by airless pumps.

HOW TO USE

Substrate Preparation

All surfaces must be clean and dry. Degrease and wash off any contaminants that could impair adhesion. Suitable solvents include isopropyl alcohol, acetone or methyl-ethyl ketone.

Unprimed adhesion may be obtained by on many substrates such as glass, metals (e.g. steel, aluminum) and most common engineering plastics (e.g. polyamide, polycarbonate). Adhesion may be less successful on some low energy plastics such as polyethylene, polypropylene and PTFE.

How to Apply

Dow Corning 7094 Flowable Sealant is ready to use. Apply a suitable amount of *Dow Corning 7094 Flowable Sealant* to one of the prepared surfaces, and then quickly cover with the other substrate to be bonded.

On exposure to moisture, the freshly applied material will “skin over” in about 25 minutes at room temperature and 50% rel. humidity. Any tooling should be completed before this skin forms. The surface is easily tooled with a spatula. The adhesive/sealant will be tack-free in about 50 minutes.

Cure Time

After skin formation, cure continues inward from the surface. In 24 hours at room temperature and 50% relative humidity, *Dow Corning 7094 Flowable Sealant* will cure to a depth of about 2 mm. Very deep sections, especially when access to atmospheric moisture is restricted, will take longer to cure completely. Cure time is very much depending on the humidity level. It is extended at lower humidity levels and accelerated at higher levels, respectively (see table below).

Condition	Rel. Cure Speed
23°C, 50% R.H.	100%
15°C, 40% R.H.	70%
30°C, 60% R.H.	135%
35°C, 70% R.H.	168%

Before handling and packaging bonded components, users are advised to wait a sufficiently long time to ensure that the integrity of the

seal is not affected. This will depend on many factors and should be determined by the user for each specific application.

HANDLING PRECAUTIONS
PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW CORNING WEBSITE AT DOWCORNING.COM, OR FROM YOUR DOW CORNING SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CORNING CUSTOMER SERVICE.

USABLE LIFE AND STORAGE

When stored below 32°C in the original unopened containers, this product has a usable life of 12 months from the date of production.

PACKAGING INFORMATION

Dow Corning 7094 Flowable Sealant is available in various standard industrial containers. Please contact your local Dow Corning representative for further details.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

HEALTH AND ENVIRONMENTAL INFORMATION

To support customers in their product safety needs, Dow Corning has an extensive Product Stewardship organization and a team of Product Safety and Regulatory Compliance

(PS&RC) specialists available in each area.

For further information, please see our website, dowcorning.com or consult your local Dow Corning representative.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer’s tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning’s sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

We help you invent the future.™

dowcorning.com

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow. Dow Corning is a registered trademark of Dow Corning Corporation. The Corning portion of the Dow Corning trademark is a trademark of Corning, Incorporated, used under license.

We help you invent the future is a trademark of Dow Corning Corporation.

XIAMETER is a registered trademark of Dow Corning Corporation.

© 2011–2017 Dow Corning Corporation, a wholly owned subsidiary of The Dow Chemical Company. All rights reserved.