Aeroglaze® 9958 Thinner

Description

Aeroglaze® 9958 thinner is used to reduce viscosities of Aeroglaze wash primers and Aeroglaze polyurethane coatings for spray applications.

Features and Benefits

Improves Application – when used in Aeroglaze primers or coatings, improves flow properties for spray application and provides better control of application film thickness.

MIL-T-81772 Type I Compliant – meets requirements of Military Specification MIL-T-81772 Type I thinner.

Application

Mixing – Premix Aeroglaze primer or coating before adding thinner. Refer to appropriate data sheet for primer or coating mixing instructions.

Slowly add Aeroglaze 9958 thinner, 15-20% by volume, while stirring the mixed primer/coating.

Shelf Life/Storage

Shelf life is one year from date of shipment when stored in a dry, well ventilated area at 16°C (60°F) in original, unopened containers. Do not store or use near heat, sparks or open flame.

Cautionary Information

Before using this or any SOCOMORE product, refer to the Mate-rial Safety Data Sheet (MSDS) and label for safe use and handling instructions.

For industrial/commercial use only. Must be applied by trained personnel only. Not to be used in household applications. Not for consumer use.

Typical Properties*

Appearance Clear or Straw Yellow Liquid

Density

ASTM D 1475-85

kg/L 0.88-0.89 (lb/gal) (7.35-7.45) Flash Point (Seta), °C (°F) 5 (41)

ASTM D 3278-82, Closed Cup

Volatile Organic Content (VOC)

ASTM D 3960-87

g/L 887 (lb/gal) (7.4)

*Data is typical and not to be used for specification purposes.



SOCOMORE TECHNICAL DATA

Values stated in this technical data sheet represent typical values as not all tests are run on each lot of material produced. For formalized product specifications for specific product end uses, contact SOCOMORE.

Information provided herein is based upon tests believed to be reliable. In as much as SOCOMORE has no control over the manner in which others may use this information, it does not guarantee the results to be obtained. In addition, SOCOMORE does not guarantee the performance of the product or the results obtained from the use of the product or this information where the product has been repackaged by any third party, including but not limited to any product end-user. Nor does the company make any express or implied warranty of merchantability or fitness for a particular purpose concerning the effects or results of such use. Terms and Conditions of Sale are available at www.socomore.com.

Since 1972, SOCOMORE has been creating, manufacturing and commercializing expert solutions for the preparation, protection, treatment and control of metallic and composite materials. Our commitment goes beyond the technical performance of our products. Our technical and commercial teams have an in-depth knowledge of the technology used by our clients, their work methods, the complexity of their processes and their constraints. Our experienced teams work with our clients to provide solutions to their problems, contribute to their technical specifications, and jointly develop new products. Located worldwide, we offer our customers a complete personalized service, with advice both before and after sales.

Manufactured for SOCOMORE by: LORD Corporation, Saegertown, PA

For more information contact: SOCOMORE 791 Westport Pkwy Fort Worth, TX 76177 Phone: 1-817-335-1826 csr-na@socomore.com www.socomore.com

