

# SAFETY DATA SHEET HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

#### 1. Identification

Product identifier

Product name HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Product number MCC-SPRL, MCC-SPRG, MCC-SPRD, MCC-SPRGL, MCC-SPRGG

Synonyms; trade names "SPR - SUPRCLEAN Nonflammable Flux Remover"

Recommended use of the chemical and restrictions on use

**Application** Cleaning agent.

Details of the supplier of the safety data sheet

Supplier MICROCARE CORPORATION

Manufacturer MICROCARE CORPORATION

595 John Downey Drive New Britain, CT 06051 United States of America

CAGE: OATV9

Tel: + 1 800 638 0125, +1 860-827-0626

Fax: +1 860-827-8105 techsupport@microcare.com

**Emergency telephone number** 

Emergency telephone CHEMTREC 1-800-424-9300 (within the U.S.)

+1 703-741-5970 (from anywhere in the world)

### 2. Hazard(s) identification

## Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302

**Environmental hazards** Aquatic Chronic 3 - H412

Human health Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Mild

dermatitis, allergic skin rash.

Environmental The product contains a substance which is harmful to aquatic organisms and which may

cause long-term adverse effects in the aquatic environment.

Physicochemical Vapors are heavier than air and may travel along the floor and accumulate in the bottom of

containers. Gas or vapor displaces oxygen available for breathing (asphyxiant).

Label elements

#### **Pictogram**



Signal word Warning

Hazard statements H302 Harmful if swallowed.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** P273 Avoid release to the environment.

P301+P312 If swallowed: Call a poison center/ doctor if you feel unwell. P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water. P314 Get medical advice/ attention if you feel unwell.

P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label

information

Safety data sheet available on request. For use in industrial installations only.

Contains trans-DICHLOROETHYLENE

## 3. Composition/information on ingredients

#### **Mixtures**

#### trans-DICHLOROETHYLENE

60-100%

CAS number: 156-60-5

Classification

Flam. Liq. 2 - H225 Acute Tox. 4 - H332 Aquatic Chronic 3 - H412

## 1,1,1,2,2,3,4,5,5,5-decafluoropentane

10-30%

CAS number: 138495-42-8

Classification

Aquatic Chronic 3 - H412

ETHANOL 5-10%

CAS number: 64-17-5

Classification

Flam. Liq. 2 - H225

The full text for all hazard statements is displayed in Section 16.

Composition comments The exact percentage (concentration) of composition has been withheld as a trade secret in

accordance with paragraph (i) of CFR 1900.1200 TSCA: The ingredients of this product are

on the TSCA Inventory.

## Composition

## 4. First-aid measures

#### Description of first aid measures

## HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

**General information** Never give anything by mouth to an unconscious person. Do not induce vomiting. Place

unconscious person on the side in the recovery position and ensure breathing can take place.

If breathing stops, provide artificial respiration.

**Inhalation** Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. When breathing is difficult, properly trained personnel may assist affected person

by administering oxygen.

**Ingestion** Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink.

Consult a physician for specific advice.

**Skin Contact** Remove contaminated clothing and rinse skin thoroughly with water.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Consult a physician for specific advice.

### Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Vapors may cause headache, fatigue, dizziness and nausea. Difficulty in breathing. Upper

respiratory irritation. Severe irritation of nose and throat.

**Ingestion** May cause stomach pain or vomiting. Drowsiness, dizziness, disorientation, vertigo.

Skin contact Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.

Eye contact Irritation of eyes and mucous membranes. Irritating to eyes. Symptoms following

overexposure may include the following: Redness. Pain.

## Indication of immediate medical attention and special treatment needed

Notes for the doctor 
No specific recommendations. If in doubt, get medical attention promptly.

#### 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

#### Special hazards arising from the substance or mixture

Flammability Class The product is not flammable.

Specific hazards Neutral

Hazardous combustion

products

Heating may generate the following products: Toxic and corrosive gases or vapors. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

Oxides of carbon. Oxides of nitrogen.

#### Advice for firefighters

Protective actions during

firefighting

Move containers from fire area if it can be done without risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Bursting

aerosol containers may be propelled from a fire at high speed.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures

## HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Personal precautions Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation.

Avoid inhalation of vapors. Use approved respirator if air contamination is above an

acceptable level.

**Environmental precautions** 

**Environmental precautions**Contain spillage with sand, earth or other suitable non-combustible material. Avoid release to

the environment.

#### Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames

or other sources of ignition near spillage. Provide adequate ventilation.

**Reference to other sections** See Section 11 for additional information on health hazards.

#### 7. Handling and storage

#### Precautions for safe handling

**Usage precautions** Provide adequate ventilation. Avoid inhalation of vapors/spray and contact with skin and eyes.

Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapors.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product.

#### Conditions for safe storage, including any incompatibilities

Storage precautions Keep container tightly closed. Store in tightly-closed, original container in a dry, cool and well-

ventilated place.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

Reference to other sections. Store away from incompatible materials (see Section 10).

#### 8. Exposure Controls/personal protection

## Control parameters

#### Occupational exposure limits

## trans-DICHLOROETHYLENE

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 793 mg/m³

## 1,1,1,2,2,3,4,5,5,5-decafluoropentane

No information available that would effect occupational exposure limit values.

## **ETHANOL**

Short-term exposure limit (15-minute): ACGIH 1000 ppm 1880 mg/m³

A3

Long-term exposure limit (8-hour TWA): OSHA 1000 ppm 1900 mg/m³ ACGIH = American Conference of Governmental Industrial Hygienists. A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

OSHA = Occupational Safety and Health Administration.

#### **Additional Occupational**

**Exposure Limits** 

Ingredient comments ACGIH = US Standard. WEL = Workplace Exposure Limits

ETHANOL (CAS: 64-17-5)

Ingredient comments WEL = Workplace Exposure Limits

## **Exposure controls**

#### Protective equipment





Appropriate engineering

controls

No specific ventilation requirements. This product must not be handled in a confined space

without adequate ventilation.

**Eye/face protection** Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. Unless the assessment indicates a higher degree of protection is

required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible.

Other skin and body

protection

Wear suitable protective clothing as protection against splashing or contamination. Wear

apron or protective clothing in case of contact.

Hygiene measures No specific hygiene procedures recommended but good personal hygiene practices should

always be observed when working with chemical products. When using do not eat, drink or

smoke.

Respiratory protection Vapors are heavier than air and may travel along the floor and accumulate in the bottom of

containers. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn.

Wear self-contained breathing apparatus with full facepiece.

## 9. Physical and Chemical Properties

## Information on basic physical and chemical properties

Appearance Clear liquid.

Color Colorless.

Odor Slight. Ether.

Odor threshold No information available.

**pH** No information available.

Melting point No information available.

Initial boiling point and range 41°C/106°F @ 101.3 kPa

**Flash point** The product is not flammable.

Evaporation rate

No information available.

Evaporation factor

No information available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or

explosive limits

Upper flammable/explosive limit: 14.4 %(V) Lower flammable/explosive limit: 5.0 %(V)

Other flammability The product is not flammable. Aerosol ignition distance: none at 0.0 cm

Vapor pressure 37.9 kPa @ 20°C

Vapor density 3.4

Relative density 1.26 g/cc

Bulk density No information available.

Solubility(ies) 0.3 % water @ 20°C

Partition coefficient No information available.

Auto-ignition temperature No information available.

Decomposition Temperature No information available.

**Viscosity** 0.48 cP @ 20°C

**Explosive properties** No information available.

Oxidizing properties Not known.

Comments Aerosol.

**Refractive index** No information available.

Particle size No information available.

Molecular weight Not applicable.

Volatility 100%

Saturation concentration No information available.

Critical temperature No information available.

Volatile organic compound This product contains a maximum VOC content of 1080 g/l.

**Flammability** The product is not flammable.

## 10. Stability and reactivity

**Reactivity** The following materials may react with the product: Strong alkalis.

Stability Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous

reactions

Will not polymerize.

Conditions to avoid Keep away from heat, sparks and open flame. Thermal decomposition or combustion

products may include the following substances: Toxic and corrosive gases or vapors.

Materials to avoid Alkali metals. Alkaline earth metals. Powdered metal.

Hazardous decomposition

products

Heating may generate the following products: Toxic and corrosive gases or vapors.

Halogenated hydrocarbons. Hydrogen fluoride (HF). Carbon dioxide (CO2). Carbon monoxide

(CO).

#### 11. Toxicological information

## Information on toxicological effects

Acute toxicity - oral

**ATE oral (mg/kg)** 1,810.85

## HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Inhalation Vapors may irritate throat/respiratory system. A single exposure may cause the following

adverse effects: Coughing. Difficulty in breathing.

**Ingestion** May cause stomach pain or vomiting. May cause nausea, headache, dizziness and

intoxication.

Skin Contact Product has a defatting effect on skin. May cause allergic contact eczema.

**Eye contact** May cause temporary eye irritation.

Medical Symptoms Gas or vapor in high concentrations may irritate the respiratory system. Symptoms following

overexposure may include the following: Headache. Fatigue. Nausea, vomiting.

### Toxicological information on ingredients.

#### trans-DICHLOROETHYLENE

Other health effects There is no evidence that the product can cause cancer.

## 1,1,1,2,2,3,4,5,5,5-decafluoropentane

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

5,000.0

**Species** Rat

ATE oral (mg/kg) 5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅ 5,000.0

mg/kg)

Species Rat

**ATE dermal (mg/kg)** 5,000.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC<sub>50</sub> vapours mg/l)

**Species** Rat

ATE inhalation (vapours

mg/l)

Skin corrosion/irritation

Animal data Not irritating. Rabbit

Human skin model test Data lacking.

**Extreme pH** Not applicable. Not corrosive to skin.

114.0

114.0

Serious eye damage/irritation

Serious eye Not irritating. Rabbit

damage/irritation

Respiratory sensitization

Respiratory sensitization Data lacking.

Skin sensitization

## HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

**Skin sensitization** Not sensitizing. - Guinea pig: Not sensitizing.

Germ cell mutagenicity

**Genotoxicity - in vitro**This substance has no evidence of mutagenic properties.

**Genotoxicity - in vivo** This substance has no evidence of mutagenic properties.

Carcinogenicity

**Carcinogenicity** Does not contain any substances known to be carcinogenic.

IARC carcinogenicity Not listed.

NTP carcinogenicity Not listed.

OSHA Carcinogenicity Not listed.

Reproductive toxicity

Reproductive toxicity -

fertility

No evidence of reproductive toxicity in animal studies.

Skin Contact Skin irritation should not occur when used as recommended. May cause defatting

of the skin but is not an irritant.

**Eye contact** May cause eye irritation.

Acute and chronic health

hazards

There is no evidence that the product can cause cancer.

**ETHANOL** 

Acute toxicity - inhalation

Acute toxicity inhalation

(LC<sub>50</sub> vapours mg/l)

ATE inhalation (vapours

mg/l)

20,000.0

20,000.0

Carcinogenicity

IARC carcinogenicity IARC Group 1 Carcinogenic to humans.

12. Ecological Information

Ecological information on ingredients.

trans-DICHLOROETHYLENE

**Ecotoxicity** Low acute toxicity to aquatic organisms.

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Ecotoxicity It is unlikely that the substance will dissolve in water in amounts big enough to have

a toxic effect on fish and daphnies.

**Toxicity** Very toxic to aquatic organisms.

Ecological information on ingredients.

trans-DICHLOROETHYLENE

## HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 1350 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 220 mg/l, Daphnia magna

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Acute toxicity - fish LC₅₀, 96 hours: 13.9 mg/l, Onchorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

LC<sub>50</sub>, 48 hours: 11.7 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC<sub>50</sub>, 72 hours: >120 mg/l, Algae

ETHANOL

Acute toxicity - fish LC<sub>50</sub>, 96 hours: >10,000 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 7,800 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

, 96 hours: 1000 mg/l, Freshwater algae

Persistence and degradability

Ecological information on ingredients.

**ETHANOL** 

Persistence and

degradability

The product is expected to be biodegradable.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients.

trans-DICHLOROETHYLENE

Bio-Accumulative Potential Bioaccumulation is unlikely to be significant because of the low water-solubility of

this product.

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Bio-Accumulative Potential Bioaccumulation is unlikely to be significant because of the low water-solubility of

this product.

Partition coefficient Pow: 2.7

**ETHANOL** 

Bio-Accumulative Potential Bioaccumulation is unlikely.

Partition coefficient No information available.

Mobility in soil

**Mobility** The product contains volatile substances which may spread in the atmosphere.

## HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

## Ecological information on ingredients.

### trans-DICHLOROETHYLENE

**Mobility** The product has poor water-solubility.

**ETHANOL** 

Mobility The product is soluble in water.

Other adverse effects

Other adverse effects The product contains a substance or substances that will contribute to global warming

(greenhouse effect).

#### 13. Disposal considerations

## Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods**Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

## 14. Transport information

General Not regulated. The product is not covered by international regulations on the transport of

dangerous goods (IMDG, IATA, DOT).

## **UN Number**

## UN proper shipping name

Proper shipping name (TDG) Not Hazardous Not Regulated

Proper shipping name (IMDG) Not Hazardous Not Regulated

Proper shipping name (ICAO) Not Hazardous Not Regulated

Proper shipping name (DOT) Not Hazardous Not Regulated

### Transport hazard class(es)

Not applicable. No information required.

#### Packing group

No information required.

## Special precautions for user

Not applicable. No information required.

**Transport in bulk according to** Not applicable. No information required. **Annex II of MARPOL 73/78** and the IBC Code

## 15. Regulatory information

#### **US Federal Regulations**

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities Not listed.

## CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

trans-DICHLOROETHYLENE

Final CERCLA RQ: 1000(454) pounds (Kilograms)

## SARA Extremely Hazardous Substances EPCRA Reportable Quantities

Not listed.

#### SARA 313 Emission Reporting

Not listed.

#### **CAA Accidental Release Prevention**

Not listed.

## **OSHA Highly Hazardous Chemicals**

Not listed.

## **US State Regulations**

#### California Proposition 65 Carcinogens and Reproductive Toxins

Not listed.

## California Air Toxics "Hot Spots" (A-I)

Not listed.

### California Air Toxics "Hot Spots" (A-II)

Not listed.

#### California Directors List of Hazardous Substances

**ETHANOL** 

Present.

trans-DICHLOROETHYLENE

Present.

## Massachusetts "Right To Know" List

**ETHANOL** 

Present.

trans-DICHLOROETHYLENE

Present.

## Rhode Island "Right To Know" List

**ETHANOL** 

Present.

## Minnesota "Right To Know" List

ETHANOL

Present.

## New Jersey "Right To Know" List

**ETHANOL** 

Present.

## Pennsylvania "Right To Know" List

**ETHANOL** 

Present.

trans-DICHLOROETHYLENE

Present.

#### Inventories

Canada - DSL/NDSL

DSL

1,1,1,2,2,3,4,5,5,5-decafluoropentane

DSL

**ETHANOL** 

DSL

trans-DICHLOROETHYLENE

DSL

#### **US-TSCA**

All the ingredients are listed.

1,1,1,2,2,3,4,5,5,5-DECAFLUOROPENTANE (CAS# 138495-42-8) is controlled by TSCA Section 5, Significant New Use

(SNUR; 40 CFR 721.5645) The approved uses are: precision and general cleaning, carrier fluid, displacement drying,

printed circuit board cleaning, particulate removal and film

cleaning, process medium, heat transfer fluid (dielectric

and non-dielectric), and test fluid. Processors and users

of this substance must also comply with the applicable general SNUR requirements set forth in 40 CFR 721 subpart A,

including export notification requirements if applicable (40

CFR 721.20), and the applicable record keeping requirements

set forth at 40 CFR 721.125.

1,1,1,2,2,3,4,5,5,5-Decafluoropentane 138495-42-8
The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product. This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D:

#### 16. Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

8/7/2017 Revision date

Revision 37

Supersedes date 8/3/2017

SDS No. **BULK - SPR** 

SDS status Approved.

Hazard statements in full H225 Highly flammable liquid and vapor.

> H302 Harmful if swallowed. H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.