

## MicroCare®



### Heavy Duty Flux Remover SuprClean™

- Best option for rosin fluxes
- Removes acrylic conformal coatings
- Instant drying, low odor
- No residues / no rinsing
- Nonflammable, ESD-safe
- Best option for rosin fluxes
- Test on plastics
- *MicroCare TriggerGrip™* cleaning system compatible

### Product Information

The Heavy Duty Flux Remover - *SuprClean* is the industry's most versatile precision cleaner. The powerful flux remover dries instantly with no residue making it ideal for heavy duty printed circuit board cleaning, especially in tight-fitting areas. It is optimized for use on R, RA, RMA, and SA fluxes.

Heavy Duty Flux Remover - *SuprClean* is the preferred choice for tough SMT defluxing, thru-hole work, BGA boards, hybrids and connectors. Use to remove tough lead-free solders and pastes, as well as most acrylic and conformal coatings.

Safe on most components, epoxies, nylon, polyethylene, polypropylene and PVC. Test on other plastics before use.

Dispense directly from the can or use with the *MicroCare TriggerGrip* cleaning system for faster, safer and more economical process of cleaning printed circuit boards at the work bench.

Not suitable for use in heated cleaning systems.

**AVAILABILITY:** Stocked by MicroCare distributors world-wide. Contact MicroCare for a distributor near you. For more information contact MicroCare directly or visit [www.MicroCare.com](http://www.MicroCare.com).

Not all products and packages available in all regions and territories.

### Discover Perfectly Clean

[www.MicroCare.com](http://www.MicroCare.com)

#### MicroCare Corporation

595 John Downey Drive  
New Britain, CT 06051 USA  
Tel: 860.827.0626  
Fax: 860.827.8105  
Toll-Free: 800.638.0125  
Email: [TechSupport@MicroCare.com](mailto:TechSupport@MicroCare.com)

#### MicroCare Europe Bvba

Havendoklaan 13d  
B-1804 Cargovil-Vilvoorde  
Belgium  
Tel: +32 2 251 95 05  
Fax: +32 2 400 96 39  
Email: [EuroSales@MicroCare.com](mailto:EuroSales@MicroCare.com)

#### MicroCare Asia Pte Ltd

102E Pasir Panjang Road  
# 03-01 Citilink Warehouse Complex  
Singapore 118529  
Tel: (65) 6271 0182  
Email: [techsupport@microcare.sg](mailto:techsupport@microcare.sg)

### Technical Details and Cleaning Data

Boiling Point . . . . .	41°C / 106°F
Chemical Family . . . . .	HFC Blend
Cleaning Strength (KB value) . . . . .	110
Evaporation Rate . . . . .	Fast
Odor . . . . .	Slight, Ether
Percent Volatile . . . . .	100%
Specific Gravity . . . . .	1.26

### Health, Safety and Environmental Data

Flammable . . . . .	No
Flashpoint . . . . .	None- Not Flammable
NFPA . . . . .	Health: 1 Fire: 1 Instability: 1
Organic Content (g/L) . . . . .	939
RoHS and WEEE Complaint . . . . .	Yes
REACH . . . . .	Yes*
US EPA SNAP-Approved . . . . .	Yes

GHS / HCS Pictogram . . . . .



### Packaging

Aerosol <sup>1</sup> - 12 oz / 340 g . . . . .	MCC-SPR
Minipail <sup>1</sup> - 10 lb / 4.53 kg . . . . .	MCC-SPRG
Pail <sup>1</sup> - 50 lb / 22.7 kg . . . . .	MCC-SPRP
Drum <sup>1</sup> - 500 lb / 226.8 kg . . . . .	MCC-SPRD

<i>TriggerGrip</i> Compatible . . . . .	Yes (aerosol)
Aerosol Packaging . . . . .	12 cans/box
Shelf Life . . . . .	Unlimited

\*Contact MicroCare for specific details

