



SAFETY DATA SHEET

Revision Date 28-Oct-2016

Revision Number 0

This document complies with the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Hi Temperature 44 All colors

Other means of identification

Part Number 44219 (White), 44424 (Yellow), 44250 (Black), 44266 (Green), 44094 (Blue)

Formula Code Z219 (White), Z424 (Yellow), ER250 (Black), ER266 (Green), A094M (Blue)

UN-Number UN1263

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Solvent based marker

Uses advised against No information available

Supplier's details

Initial Supplier
ITW Permatex Canada
1-35 Brownridge Road
Halton Hills, ON, L7G 0C6
Canada

Supplier Address
ITW PRO BRANDS
805 E. Old 56 Highway
Olathe, KS 66061
TEL: 1-800-443-9536

Emergency telephone number

Emergency Telephone Number 800-535-5053 Infotrac

2. HAZARDS IDENTIFICATION

Classification

This product is considered hazardous according to the criteria set within the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

Acute Oral Toxicity	Category 4
Acute Inhalation Toxicity - Vapors	Category 4

Acute Inhalation Toxicity - Dusts and Mists	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Skin Sensitization	Category 1
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive Toxicity	Category 1A
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Specific Target Organ Toxicity (Repeated Exposure)	Category 1
Aspiration Toxicity	Category 1
Flammable liquids	Category 3

Label Elements

Danger



Hazard Statements

Harmful if swallowed
 Harmful if inhaled
 Causes skin irritation
 Causes serious eye irritation
 May cause an allergic skin reaction
 May cause genetic defects
 May cause cancer
 May damage fertility or the unborn child
 May cause respiratory irritation
 Causes damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 Flammable liquid and vapor.

Physical and Health Hazards Not Otherwise Classified

Not applicable.

Precautionary Statements

Prevention

- Use only outdoors or in a well-ventilated area.
- Wash face, hands and any exposed skin thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Contaminated work clothing should not be allowed out of the workplace.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Keep cool.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- If exposed or concerned: Get medical attention/advice
- Specific treatment (see supplemental first aid instructions on this label)

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Skin

- If skin irritation or rash occurs: Get medical advice/attention.
- Wash contaminated clothing before reuse.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Ingestion

- Rinse mouth.
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Do NOT induce vomiting.

Fire

- In case of fire: Use CO₂, dry chemical, or foam for extinction.

Storage

- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Other information

Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

32.76865% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Petroleum naphtha, light aromatic	64742-95-6	35.51	-	-
1,2,4 Trimethylbenzene	95-63-6	29.51	-	-
Chromium (III) oxide	1308-38-9	25.82	-	-
Chemical Frits (Lead free)	65997-18-4	21.04	-	-
Chrome yellow (Lead chromate pigment)	1344-37-2	17.44	-	-
Xylene, mixed isomers	1330-20-7	17	-	-
Titanium dioxide	13463-67-7	16.03	-	-
Ethylbenzene	100-41-4	7.01	-	-
1,3,5-Trimethylbenzene	108-67-8	5.9	-	-
Carbon black	1333-86-4	4.56	-	-
Quartz	14808-60-7	3.85	-	-
Cumene	98-82-8	2.95	-	-
Silicon dioxide	7631-86-9	1.76	-	-
Stoddard solvent	8052-41-3	1.68	-	-
2-Ethylhexanoic acid	149-57-5	0.56	-	-
Toluene	108-88-3	0.23	-	-

4. FIRST AID MEASURES

Description of necessary first-aid measures

Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Aspiration hazard if swallowed - can enter lungs and cause damage. Consult a physician if necessary.
Protection of First-aiders	Use personal protective equipment. Remove all sources of ignition.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects Eye irritation/reactions. Skin irritation. Respiratory irritation. May cause allergic skin reaction. Itching. Rashes. Aspiration may cause pulmonary edema and pneumonitis.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Carbon dioxide (CO₂). Foam. Dry chemical.

Unsuitable Extinguishing Media No information available.

Specific Hazards Arising from the Chemical May cause sensitization by skin contact. Thermal decomposition can lead to release of irritating gases and vapors. Risk of ignition. Vapors may travel to source of ignition and flash back.

Explosion Data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	Yes.

Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Do not touch or walk through spilled material. Stop leak if you can do it without risk. Take precautionary measures against static discharges.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Avoid release to the environment. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Small spillage: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Large spillage: Pump or vacuum

transfer spilled product to clean containers for recovery. Absorb unrecoverable product.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Conditions for safe storage, including any incompatibilities

Storage

Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from incompatible materials.

Incompatible Products

Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
1,2,4 Trimethylbenzene 95-63-6	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³	TWA: 25 ppm TWA: 125 mg/m ³
Chromium (III) oxide 1308-38-9	TWA: 0.5 mg/m ³ Cr	TWA: 0.5 mg/m ³ Cr (vacated) TWA: 0.5 mg/m ³ Cr	IDLH: 25 mg/m ³ Cr(III) TWA: 0.5 mg/m ³ Cr
Chemical Frits (Lead free) 65997-18-4	STEL: 10 mg/m ³ Zr TWA: 5 mg/m ³ Zr TWA: 0.2 mg/m ³ Mn	TWA: 5 mg/m ³ Zr (vacated) TWA: 5 mg/m ³ Zr (vacated) STEL: 10 mg/m ³ Zr (vacated) Ceiling: 5 mg/m ³ Ceiling: 5 mg/m ³ Mn	IDLH: 5 mg/m ³ As IDLH: 9 mg/m ³ Cd dust and fume IDLH: 50 mg/m ³ Sb IDLH: 100 mg/m ³ Cu dust and mist IDLH: 500 mg/m ³ Mn IDLH: 25 mg/m ³ Zr IDLH: 100 mg/m ³ Pb IDLH: 10 mg/m ³ Ni Ceiling: 0.002 mg/m ³ As 15 min Ceiling: 0.05 mg/m ³ V dust and fume 15 min TWA: 0.5 mg/m ³ Sb TWA: 1 mg/m ³ Cu dust and mist TWA: 1 mg/m ³ Mn TWA: 5 mg/m ³ except Zirconium tetrachloride Zr TWA: 0.050 mg/m ³ Pb TWA: 0.015 mg/m ³ except Nickel carbonyl Ni STEL: 3 mg/m ³ Mn STEL: 10 mg/m ³ Zr
Chrome yellow (Lead chromate pigment) 1344-37-2	TWA: 0.05 mg/m ³ Pb	TWA: 5 µg/m ³ TWA: 50 µg/m ³ Pb Action Level: 2.5 µg/m ³ Cr Action Level: 30 µg/m ³ Pb Poison; See 29 CFR 1910.1025	IDLH: 100 mg/m ³ Pb TWA: 0.0002 mg/m ³ Cr TWA: 0.050 mg/m ³ Pb
Xylene, mixed isomers 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

1,3,5-Trimethylbenzene 108-67-8	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³	TWA: 25 ppm TWA: 125 mg/m ³
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	30/(%SiO ₂ +2) mg/m ³ TWA, Total Dust;250/(%SiO ₂ +5) mppcf TWA, respirable fraction; 10/(%SiO ₂ +2) mg/m ³ TWA, respirable TWA: 0.1 mg/m ³ (vacated)	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³
Silicon dioxide 7631-86-9	10 mg/m ³	20 mppcf TWA; ((80)/(% SiO ₂)) mg/m ³)	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Aluminum hydroxide 21645-51-2	TWA: 1 mg/m ³ respirable particulate matter	-	-
2-Ethylhexanoic acid 149-57-5	TWA: 5 mg/m ³ inhalable fraction and vapor	-	-
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Skin and Body Protection Respiratory Protection

If splashes are likely to occur, wear: Chemical splash goggles.
Risk of contact: Chemical resistant gloves. Boots. Apron.
No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Hygiene Measures

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid.	Appearance	Opaque, Varies, Thin viscosity,
Odor	Aromatic.	Odor Threshold	No information available.
Property	Values	Remarks/ - Method	
pH	No data available	None known	
Melting Point/Range	No data available	None known	

Boiling Point/Boiling Range	158.89-170 °C / 318-338 °F	None known
Flash Point	42.22 °C / 108 °F	None known
Evaporation rate		None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	12.6	
lower flammability limit	1.9	
Vapor Pressure	No data available	None known
Vapor Density	> 1 (air = 1)	None known
Specific Gravity	No data available	None known
Water Solubility	Negligible	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

Flammable Properties Flammable; may be ignited by heat, sparks or flames.

Explosive Properties No data available

Oxidizing Properties No data available

Other information

VOC Content (%)	ER250 Black: 57.63% Z219 White: 52.35% A094 Blue: 67.72% Z424 Yellow: 58.69% ER266 Green: 60.99%
VOC (g/l)	ER250 Black: 642 g/L Z219 White: 666 g/L A094 Blue: 719 g/L Z424 Yellow: 700 g/L ER266 Green: 695 g/L

10. STABILITY AND REACTIVITY

Reactivity No data available.

Chemical stability Stable under recommended storage conditions.

Possibility of hazardous reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Incompatible products.

Incompatible materials Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

Hazardous decomposition products Carbon oxides. Smoke Soot.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Harmful if inhaled. May cause irritation of respiratory tract. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal

Eye Contact

Causes serious eye irritation.

Skin Contact

May be harmful in contact with skin. Causes skin irritation.

Ingestion

Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Numerical measures of toxicity - Product

Unknown acute toxicity 32.76865% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 757 mg/kg; Acute toxicity estimate
LD50 Dermal 4279 mg/kg; Acute toxicity estimate

Inhalation
dust/mist 2.34 mg/L; Acute toxicity estimate
Vapor 15.56 mg/L; Acute toxicity estimate

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Petroleum naphtha, light aromatic	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
1,2,4 Trimethylbenzene	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Chromium (III) oxide	> 5000 mg/kg (Rat)	-	-
Chemical Frits (Lead free)	> 2000 mg/kg (Rat)	>2500 mg/kg	-
Chrome yellow (Lead chromate pigment)	> 5000 mg/kg (Rat)	-	-
Xylene, mixed isomers	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
Ethylbenzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
1,3,5-Trimethylbenzene	= 5000 mg/kg (Rat)	-	= 24 g/m ³ (Rat) 4 h
Carbon black	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Quartz	500 mg/kg (Rat)	-	-
Cumene	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	= 39000 mg/m ³ (Rat) 4 h > 3577 ppm (Rat) 6 h
Silicon dioxide	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	>2.2 mg/L (Rat) 4 h
Aluminum hydroxide	> 5000 mg/kg (Rat)	-	-
2-Ethylhexanoic acid	= 1600 mg/kg (Rat)	= 1140 mg/kg (Rabbit)	-
Toluene	>5580 mg/kg (Rat)	8390 mg/kg (Rabbit)	12.5 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Respiratory or Skin Sensitization May cause sensitization of susceptible persons. May cause sensitization by skin contact.

Germ Cell Mutagenicity Contains a known or suspected mutagen. May cause genetic defects.

Carcinogenicity Contains a known or suspected carcinogen. May cause cancer. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Chromium (III) oxide		Group 3		
Chemical Frits (Lead free)	A1 A3 A2	Group 1 Group 2B Group 2A	Known Reasonably Anticipated	X
Chrome yellow (Lead chromate pigment)	A3	Group 1 Group 2A	Known Reasonably Anticipated	X
Xylene, mixed isomers		Group 3		
Titanium dioxide		Group 2B	-	-
Ethylbenzene	A3	Group 2B	-	-
Carbon black	A3	Group 2B	-	X
Quartz	A2	Group 1	Known	X
Cumene		Group 2B	Reasonably Anticipated	X
Silicon dioxide		Group 3		
Toluene	A4	Group 3	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen
A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans
 Group 2B - Possibly Carcinogenic to Humans
 Group 3 - Not Classifiable as to its Carcinogenicity to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Chronic Toxicity

Contains a known or suspected reproductive toxin. May damage fertility or the unborn child
 May cause respiratory irritation

Causes damage to organs through prolonged or repeated exposure.

Avoid repeated exposure. Contains a known or suspected reproductive toxin. Contains a known or suspected mutagen Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B).

Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. May cause adverse effects on the bone marrow and blood-forming system.

Target Organ Effects

Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS). Blood. Lungs. Lymphatic system.

Aspiration Hazard

May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum naphtha, light aromatic 64742-95-6		LC50 96 h: = 9.22 mg/L (Oncorhynchus mykiss)		EC50 48 h: = 6.14 mg/L (Daphnia magna)
1,2,4 Trimethylbenzene 95-63-6		LC50 96 h: 7.19 - 8.28 mg/L flow-through (Pimephales promelas)		EC50 48 h: = 6.14 mg/L (Daphnia magna)
Chrome yellow (Lead chromate pigment) 1344-37-2		LC50 96 h: > 10000 mg/L static (Leuciscus idus)	EC50 > 10000 mg/L 30 min	
Xylene, mixed isomers 1330-20-7	EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 13.4 mg/L flow-through (Pimephales promelas) LC50 96 h: 2.661 - 4.093 mg/L static (Oncorhynchus mykiss) LC50 96 h: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) LC50 96 h: 13.1 - 16.5 mg/L flow-through (Lepomis macrochirus) LC50 96 h: = 19 mg/L (Lepomis macrochirus) LC50 96 h: 7.711 - 9.591 mg/L static (Lepomis macrochirus) LC50 96 h: 23.53 - 29.97 mg/L static (Pimephales promelas) LC50 96 h: = 780 mg/L semi-static (Cyprinus carpio) LC50 96 h: > 780 mg/L (Cyprinus carpio) LC50 96 h: 30.26 - 40.75 mg/L static (Poecilia reticulata)		EC50 48 h: = 3.82 mg/L (water flea) LC50 48 h: = 0.6 mg/L (Gammarus lacustris)
Ethylbenzene 100-41-4	EC50 96 h: 1.7 - 7.6 mg/L static (Pseudokirchneriella subcapitata)	LC50 96 h: 4 mg/L static (Rainbow trout)		EC50 48 h: 1-4 mg/L (Daphnia magna)

1,3,5-Trimethylbenzene 108-67-8		LC50 96 h: = 3.48 mg/L (Pimephales promelas) LC50 96 h: = 7.72 mg/L flow-through (Pimephales promelas)		EC50 24 h: = 50 mg/L (Daphnia magna)
Carbon black 1333-86-4				EC50 24 h: > 5600 mg/L (Daphnia magna)
Cumene 98-82-8	EC50 72 h: = 2.6 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 6.04 - 6.61 mg/L flow-through (Pimephales promelas) LC50 96 h: = 2.7 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: = 4.8 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 5.1 mg/L semi-static (Poecilia reticulata)	EC50 = 0.89 mg/L 5 min EC50 = 1.10 mg/L 15 min EC50 = 1.48 mg/L 30 min EC50 = 172 mg/L 24 h	EC50 48 h: 7.9 - 14.1 mg/L Static (Daphnia magna) EC50 48 h: = 0.6 mg/L (Daphnia magna)
Silicon dioxide 7631-86-9	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)
2-Ethylhexanoic acid 149-57-5	EC50 96 h: = 41 mg/L (Desmodesmus subspicatus) EC50 72 h: = 61 mg/L (Desmodesmus subspicatus)	LC50 96 h: < 3000 mg/L semi-static (Brachydanio rerio) LC50 96 h: = 70 mg/L (Pimephales promelas)	EC50 = 110 mg/L 17 h EC50 = 670 mg/L 30 min	EC50 48 h: = 85.4 mg/L (Daphnia magna)
Toluene 108-88-3	EC50: 12.5 mg/L Pseudokirchneriella subcapitata 72 h static	LC50: 96 h static <=10 mg/L (Rainbow trout)		LC50 48 h: 7.6 mg/L (Daphnia magna)

Persistence and Degradability No information available.

Bioaccumulation

Chemical Name	Log Pow
1,2,4 Trimethylbenzene	3.63
Xylene, mixed isomers	2.77 - 3.15
Ethylbenzene	3.2
Cumene	3.7
2-Ethylhexanoic acid	2.7
Toluene	2.7

Mobility No information available.

Other Adverse Effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with local/regional/national regulations.

Contaminated Packaging Do not re-use empty containers.

US EPA Waste Number
D001
U055
U220
U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene, mixed isomers - 1330-20-7		Included in waste stream: F039		U239
Ethylbenzene - 100-41-4		Included in waste stream: F039		
Cumene - 98-82-8				U055
Toluene - 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
Component	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes

<p>Toluene 108-88-3 (0.23)</p>			<p>Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.</p>	
--------------------------------------	--	--	---	--

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Chromium (III) oxide	Toxic Corrosive Ignitable
Chrome yellow (Lead chromate pigment)	Toxic Corrosive Ignitable
Xylene, mixed isomers	Toxic Ignitable
Ethylbenzene	Toxic Ignitable
Cumene	Toxic Ignitable
Toluene	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-Number UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group III
 Description UN1263, Paint, 3, III, Marine Pollutant
 Emergency Response Guide Number 128

TDG

UN-Number UN1263
 Proper Shipping Name Paint
 Hazard Class 3
 Packing Group III
 Description UN1263, Paint, 3, III, Marine Pollutant

MEX

UN-Number UN1263
 Proper Shipping Name Paint
 Hazard Class 3
 Packing Group III
 Description UN1263, Paint, 3, III

IATA

UN-Number UN1263
 Proper Shipping Name Paint
 Hazard Class 3
 Packing Group III

ERG Code 3L
Description UN1263, Paint, 3, III

IMDG/IMO

UN-Number UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group III
EmS No. F-E, S-E
Marine Pollutant Product is a marine pollutant according to the criteria set by IMDG/IMO
Description UN1263, Paint, 3, III, (42.22°C c.c.), Marine Pollutant

15. REGULATORY INFORMATION

International Regulations

Ozone depleting substances Not applicable
Persistent Organic Pollutants Not applicable

Hazardous Waste

Chemical Name	Basel Convention (Hazardous Wastes)
Chemical Frits (Lead free)	Y26 Y23 Y27 Y22 Y24 Y31
Chrome yellow (Lead chromate pigment)	Y21 Y31
Xylene, mixed isomers	Y42
2-Ethylhexanoic acid	Y34
Toluene	Y42

The Rotterdam Convention (Prior Informed Consent) Not applicable

International Convention for the Prevention of Pollution from Ships (MARPOL) Not applicable

International Inventories

TSCA Complies
DSL Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
1,2,4 Trimethylbenzene	95-63-6	29.51	1.0
Chromium (III) oxide	1308-38-9	25.82	1.0
Chemical Frits (Lead free)	65997-18-4	21.04	0.1 1.0
Chrome yellow (Lead chromate pigment)	1344-37-2	17.44	0.1
Xylene, mixed isomers	1330-20-7	17	1.0
Spinels, chromium cobalt iron black	68186-97-0	10-30	0.1 1.0
C.I. Pigment Blue 28	1345-16-0	10-30	0.1
Ethylbenzene	100-41-4	7.01	0.1
Cumene	98-82-8	2.95	1.0
Toluene	108-88-3	0.23	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21

and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Chromium (III) oxide		X		
Chemical Frits (Lead free)		X		
Chrome yellow (Lead chromate pigment)		X		
Xylene, mixed isomers	100 lb			X
Ethylbenzene	1000 lb	X	X	X
Toluene	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Xylene, mixed isomers	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Cumene	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Toluene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Chemical Frits (Lead free)	65997-18-4	Carcinogen Developmental
Chrome yellow (Lead chromate pigment)	1344-37-2	Carcinogen Developmental Female Reproductive Male Reproductive
Titanium dioxide	13463-67-7	Carcinogen
Ethylbenzene	100-41-4	Carcinogen
Carbon black	1333-86-4	Carcinogen
Quartz	14808-60-7	Carcinogen
Cumene	98-82-8	Carcinogen
Toluene	108-88-3	Developmental
Chromium (VI)	18540-29-9	Carcinogen Developmental Female Reproductive Male Reproductive

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
1,2,4 Trimethylbenzene	X	X	X	X	X
Chromium (III) oxide	X	X	X	X	X
Chemical Frits (Lead free)	X		X	X	
Chrome yellow (Lead chromate pigment)	X		X	X	X
Xylene, mixed isomers	X	X	X	X	X
Titanium dioxide	X	X	X		X
Ethylbenzene	X	X	X	X	X
1,3,5-Trimethylbenzene	X	X	X	X	X
Carbon black	X	X	X	X	X
Quartz	X	X	X	-	X
Cumene	X	X	X	X	X

Stoddard solvent	X	X	X		X
Toluene	X	X	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA **Health Hazard 2** **Flammability 2** **Instability 0** **Physical and Chemical Hazards -**

HMIS **Health Hazard 2*** **Flammability 2** **Physical Hazard 0** **Personal Protection X**

*Indicates a chronic health hazard.

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 28-Oct-2016
Revision Date 28-Oct-2016
Revision Note Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet