



# SAFETY DATA SHEET

## DOW SILICONES CORPORATION

**Product name:** DOWSIL™ PR-1200 RTV Prime Coat Red

**Issue Date:** 05/22/2025

**Print Date:** 05/29/2025

DOW SILICONES CORPORATION encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

---

## 1. IDENTIFICATION

---

**Product name:** DOWSIL™ PR-1200 RTV Prime Coat Red

**Recommended use of the chemical and restrictions on use**

**Identified uses:** Primer.

### COMPANY IDENTIFICATION

DOW SILICONES CORPORATION  
2211 H.H. DOW WAY  
MIDLAND MI 48674-0001  
UNITED STATES

**Customer Information Number:**

800-258-2436  
SDSQuestion@dow.com

### EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** 1 800 424 9300

**Local Emergency Contact:** 800-424-9300

---

## 2. HAZARDS IDENTIFICATION

---

### Hazard classification

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids - Category 2

Skin irritation - Category 2

Serious eye damage - Category 1

Specific target organ toxicity - single exposure - Category 3

Specific target organ toxicity - repeated exposure - Category 2 - Oral

Aspiration hazard - Category 1

**Label elements**

**Hazard pictograms**



Signal word: **DANGER!**

#### Hazards

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs (Blood) through prolonged or repeated exposure if swallowed.

#### Precautionary statements

##### Prevention

P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe mist or vapours.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ eye protection/ face protection.

##### Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P314	Get medical advice/ attention if you feel unwell.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

##### Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

##### Disposal

P501	Dispose of contents/ container to an approved waste disposal plant.
------	---

**Other hazards**

No data available

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

---

**Chemical nature:** Inorganic and organic compounds, Mixture

This product is a mixture.

Component	CASRN	Concentration
Distillates, petroleum, light distillate hydrotreating process, low-boiling	68410-97-9	>= 82.0 - <= 88.0 %
Tetrakis(2-butoxyethyl) orthosilicate	18765-38-3	>= 4.0 - <= 6.0 %
Tetrapropyl orthosilicate	682-01-9	>= 4.0 - <= 6.0 %
Tetra n-Butyl titanate	5593-70-4	>= 4.0 - <= 6.0 %
Octane	111-65-9	>= 0.1 - <= 1.4 %

---

**4. FIRST AID MEASURES**

---

**Description of first aid measures****General advice:**

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air and keep comfortable for breathing; consult a physician.

**Skin contact:** Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

**Eye contact:** Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

**Ingestion:** Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

**Most important symptoms and effects, both acute and delayed:**

May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure if swallowed.

**Indication of any immediate medical attention and special treatment needed**

**Notes to physician:** Maintain adequate ventilation and oxygenation of the patient. May cause asthma-like (reactive airways) symptoms. Bronchodilators, expectorants, antitussives and corticosteroids may be of help. Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably from an ophthalmologist. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. The decision of whether to induce vomiting or not should be made by a physician. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Repeated excessive exposure may aggravate preexisting lung disease.

---

**5. FIREFIGHTING MEASURES**

---

**Extinguishing media**

**Suitable extinguishing media:** Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Dry sand.

**Unsuitable extinguishing media:** High volume water jet. Do not use direct water stream..

**Special hazards arising from the substance or mixture**

**Hazardous combustion products:** Silicon oxides. Formaldehyde. Carbon oxides. Metal oxides.

**Unusual Fire and Explosion Hazards:** Flash back possible over considerable distance.. Exposure to combustion products may be a hazard to health.. Flammable concentrations of vapor can accumulate at temperatures above flash point; see Section 9.. Flammable mixtures may exist within the vapor space of containers at room temperature.. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat.. Vapours may form explosive mixtures with air..

**Advice for firefighters**

**Fire Fighting Procedures:** Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage.. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.. Do not use a solid water stream as it may scatter and spread fire.. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

**Special protective equipment for firefighters:** In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

---

**6. ACCIDENTAL RELEASE MEASURES**

---

**Personal precautions, protective equipment and emergency procedures:** Remove all sources of ignition. Ventilate the area. Use personal protective equipment. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Ground and bond all containers and

handling equipment. Vapor explosion hazard. Keep out of sewers. Follow safe handling advice and personal protective equipment recommendations.

**Environmental precautions:** Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

**Methods and materials for containment and cleaning up:** Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. See sections: 7, 8, 11, 12 and 13.

---

## 7. HANDLING AND STORAGE

---

**Precautions for safe handling:** Do not get on skin or clothing. Do not breathe vapours or spray mist. Do not swallow. Do not get in eyes. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Non-sparking tools should be used. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation. Ensure all equipment is electrically grounded before beginning transfer operations. This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations. Restrict flow velocity in order to reduce the accumulation of static electricity. Ground and bond container and receiving equipment.

**Conditions for safe storage:** Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Flammable solids. Pyrophoric liquids. Pyrophoric solids. Self-heating substances and mixtures. Substances and mixtures, which in contact with water, emit flammable gases. Explosives. Gases. Unsuitable materials for containers: None known.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
-----------	------------	-----------------	-------

Distillates, petroleum, light distillate hydrotreating process, low-boiling	OSHA Z-1	TWA	2,000 mg/m3 500 ppm
Octane	OSHA Z-1	TWA	2,350 mg/m3 500 ppm
	ACGIH	TWA	300 ppm
Propyl alcohol	ACGIH	TWA	100 ppm
Further information: A4: Not classifiable as a human carcinogen			
	OSHA Z-1	TWA	500 mg/m3 200 ppm
Butanol	ACGIH	TWA	20 ppm
	OSHA Z-1	TWA	300 mg/m3 100 ppm
Ethylene glycol monobutyl ether	ACGIH	TWA	20 ppm
Further information: A3: Confirmed animal carcinogen with unknown relevance to humans			
	OSHA Z-1	TWA	240 mg/m3 50 ppm
Further information: X: Skin designation			

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing: Ethylene glycol monobutyl ether, Propyl alcohol, butanol

#### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Ethylene glycol monobutyl ether	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g creatinine	ACGIH BEI

#### Exposure controls

**Engineering controls:** Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

#### Individual protection measures

**Eye/face protection:** Use chemical goggles.

##### Skin protection

**Hand protection:** Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Polyvinyl alcohol ("PVA"). Examples of acceptable glove barrier materials include: Butyl rubber. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. In misty atmospheres, use an approved particulate respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### Appearance

Physical state	liquid
Color	pink
Odor	solvent-like
Odor Threshold	No data available
pH	Not applicable, substance/mixture is non-soluble (in water)
Melting point/ range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	> 100 °C ( > 212 °F)
Flash point	<b>Tag closed cup</b> 13 °C ( 55 °F)
Evaporation Rate (Butyl Acetate = 1)	No data available
Flammability (solid, gas)	Not applicable to liquids
Flammability (liquids)	Static-accumulating flammable liquid.
Lower explosion limit	0.6 % vol Mineral oil
Upper explosion limit	7.6 % vol Mineral oil
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	0.76
Water solubility	insoluble
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	246 - 470 °C (475 - 878 °F) Mineral oil
Decomposition temperature	No data available
Kinematic Viscosity	1 mm <sup>2</sup> /s at 25 °C (77 °F)
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.
Molecular weight	No data available
Particle size	Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** Not classified as a reactivity hazard.

**Chemical stability:** Stable under normal conditions.

**Possibility of hazardous reactions:** Can react with strong oxidizing agents. Vapours may form explosive mixture with air. Highly flammable liquid and vapour.

**Conditions to avoid:** Avoid static discharge. Heat, flames and sparks.

**Incompatible materials:** Avoid contact with oxidizing materials.

**Hazardous decomposition products:**

Decomposition products can include and are not limited to: Ethylene glycol monobutyl ether. Propyl alcohol. Butanol.

---

## 11. TOXICOLOGICAL INFORMATION

---

*Toxicological information appears in this section when such data are available.*

**Information on likely routes of exposure**

Inhalation, Eye contact, Skin contact, Ingestion.

**Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)**

**Acute Toxicity Endpoints:**

Not classified based on available information.

**Acute oral toxicity**

**Information for the Product:**

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, Rat, > 5,000 mg/kg Estimated.

**Information for components:**

**Distillates, petroleum, light distillate hydrotreating process, low-boiling**

Single dose oral LD50 has not been determined.

For similar material(s): LD50, Rat, male and female, > 5,000 mg/kg OECD 401 or equivalent No deaths occurred at this concentration.

**Tetrakis(2-butoxyethyl) orthosilicate**

LD50, Rat, > 2,000 mg/kg No deaths occurred at this concentration.



**Tetrapropyl orthosilicate**

LD50, Rat, male and female, > 2,000 mg/kg OECD Test Guideline 423 No deaths occurred at this concentration.

**Tetra n-Butyl titanate**

LD50, Rat, male, 4,220 mg/kg

**Octane**

Single dose oral LD50 has not been determined.

For similar material(s): LD50, Rat, male and female, > 5,000 mg/kg OECD 401 or equivalent

**Acute dermal toxicity**

**Information for the Product:**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):  
LD50, > 2,000 mg/kg Estimated.

**Information for components:**

**Distillates, petroleum, light distillate hydrotreating process, low-boiling**

The dermal LD50 has not been determined.

For similar material(s): LD50, Rabbit, male and female, > 2,000 mg/kg OECD 402 or equivalent No deaths occurred at this concentration.

**Tetrakis(2-butoxyethyl) orthosilicate**

LD50, Rat, > 2,000 mg/kg No deaths occurred at this concentration.

**Tetrapropyl orthosilicate**

LD50, > 2,000 mg/kg Estimated.

**Tetra n-Butyl titanate**

LD50, Rabbit, 5,300 mg/kg

**Octane**

The dermal LD50 has not been determined.

For similar material(s): LD50, Rabbit, male and female, > 2,000 mg/kg OECD 402 or equivalent No deaths occurred at this concentration.

**Acute inhalation toxicity**

**Information for the Product:**

Brief exposure (minutes) is not likely to cause adverse effects. Excessive exposure may cause: lung effects Central nervous system depression Mist may cause irritation of upper respiratory tract (nose and throat) and lungs.

As product: The LC50 has not been determined.

**Information for components:****Distillates, petroleum, light distillate hydrotreating process, low-boiling**

Brief exposure (minutes) is not likely to cause adverse effects. Excessive exposure may cause: lung effects Central nervous system depression

The LC50 has not been determined.

For similar material(s): LC50, Rat, 4 Hour, vapour, > 5.61 mg/l

**Tetrakis(2-butoxyethyl) orthosilicate**

Brief exposure (minutes) is not likely to cause adverse effects.

The LC50 has not been determined.

**Tetrapropyl orthosilicate**

LC50, Rat, male and female, 4 Hour, dust/mist, > 1 - 5 mg/l OECD Test Guideline 403

**Tetra n-Butyl titanate**

LC50, Rat, 4 Hour, dust/mist, 11 mg/l

**Octane**

LC50, Rat, male and female, 4 Hour, vapour, > 24.88 mg/l OECD Test Guideline 403  
No deaths occurred at this concentration.

**Skin corrosion/irritation**

Causes skin irritation.

**Information for the Product:**

Based on information for component(s):

Brief contact may cause severe skin irritation with pain and local redness.

**Information for components:****Distillates, petroleum, light distillate hydrotreating process, low-boiling**

For similar material(s):

Brief contact may cause severe skin irritation with pain and local redness.

**Tetrakis(2-butoxyethyl) orthosilicate**

Brief contact may cause moderate skin irritation with local redness.

**Tetrapropyl orthosilicate**

Brief contact may cause slight skin irritation with local redness.

**Tetra n-Butyl titanate**

Prolonged contact may cause moderate skin irritation with local redness.

**Octane**

Prolonged contact may cause skin irritation with local redness.

Repeated contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

May cause drying and flaking of the skin.

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Information for the Product:**

Based on information for component(s):

May cause moderate eye irritation.

May cause severe corneal injury.

May cause permanent impairment of vision.

**Information for components:****Distillates, petroleum, light distillate hydrotreating process, low-boiling**

For similar material(s):

May cause slight temporary eye irritation.

Corneal injury is unlikely.

**Tetrakis(2-butoxyethyl) orthosilicate**

Essentially nonirritating to eyes.

**Tetrapropyl orthosilicate**

May cause slight temporary eye irritation.

May cause slight temporary corneal injury.

**Tetra n-Butyl titanate**

May cause moderate eye irritation.

May cause severe corneal injury.

May cause permanent impairment of vision.

**Octane**

May cause pain disproportionate to the level of irritation to eye tissues.

May cause slight temporary eye irritation.

May cause slight temporary corneal injury.

**Sensitization****For skin sensitization:**

Not classified based on available information.

**For respiratory sensitization:**

Not classified based on available information.

**Information for the Product:**

For skin sensitization:

Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Information for components:**

**Distillates, petroleum, light distillate hydrotreating process, low-boiling**

For similar material(s):  
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Tetrakis(2-butoxyethyl) orthosilicate**

For skin sensitization:  
Did not cause allergic skin reactions when tested in guinea pigs.

No relevant data found.

**Tetrapropyl orthosilicate**

For similar material(s):  
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Tetra n-Butyl titanate**

Did not demonstrate the potential for contact allergy in mice.

For respiratory sensitization:  
No relevant data found.

**Octane**

For similar material(s):  
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause drowsiness or dizziness.

**Information for the Product:**

Product test data not available.

**Information for components:**

**Distillates, petroleum, light distillate hydrotreating process, low-boiling**

May cause drowsiness or dizziness.  
Route of Exposure: Inhalation  
Target Organs: Central nervous system

**Tetrakis(2-butoxyethyl) orthosilicate**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Tetrapropyl orthosilicate**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Tetra n-Butyl titanate**

May cause respiratory irritation.

Route of Exposure: Inhalation

Target Organs: Respiratory Tract

May cause drowsiness or dizziness.

Route of Exposure: Inhalation

Target Organs: Nervous system

**Octane**

May cause drowsiness or dizziness.

Route of Exposure: Inhalation

Target Organs: Central nervous system

**Aspiration Hazard**

May be fatal if swallowed and enters airways.

**Information for the Product:**

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia.

**Information for components:**

**Distillates, petroleum, light distillate hydrotreating process, low-boiling**

May be fatal if swallowed and enters airways.

**Tetrakis(2-butoxyethyl) orthosilicate**

Based on physical properties, not likely to be an aspiration hazard.

**Tetrapropyl orthosilicate**

Based on physical properties, not likely to be an aspiration hazard.

**Tetra n-Butyl titanate**

Based on available information, aspiration hazard could not be determined.

**Octane**

May be fatal if swallowed and enters airways.

**Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)**

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

May cause damage to organs (Blood) through prolonged or repeated exposure if swallowed.

**Information for the Product:**

Product test data not available.

**Information for components:**

**Distillates, petroleum, light distillate hydrotreating process, low-boiling**

For similar material(s):

Kidney effects have been observed in male rats. These effects are believed to be species specific and unlikely to occur in humans.

**Tetrakis(2-butoxyethyl) orthosilicate**

In animals, effects have been reported on the following organs:

Blood.

**Tetrapropyl orthosilicate**

For similar material(s):

In animals, effects have been reported on the following organs:

Kidney

**Tetra n-Butyl titanate**

No relevant data found.

**Octane**

No relevant data found.

**Carcinogenicity**

Not classified based on available information.

**Information for the Product:**

Product test data not available.

**Information for components:**

**Distillates, petroleum, light distillate hydrotreating process, low-boiling**

Kidney effects and/or tumors have been observed in male rats. These effects are believed to be species specific and unlikely to occur in humans.

**Tetrakis(2-butoxyethyl) orthosilicate**

No relevant data found.

**Tetrapropyl orthosilicate**

No relevant data found.

**Tetra n-Butyl titanate**

No relevant data found.

**Octane**

No relevant data found.

**Carcinogenicity**

**Component**

**Distillates, petroleum, light**

**List**

**IARC**

**Classification**

**Group 2B: Possibly carcinogenic to**

distillate hydrotreating process,  
low-boiling

humans

### Teratogenicity

Not classified based on available information.

#### Information for the Product:

Product test data not available.

#### Information for components:

##### **Distillates, petroleum, light distillate hydrotreating process, low-boiling**

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

##### **Tetrakis(2-butoxyethyl) orthosilicate**

Did not cause birth defects in laboratory animals.

##### **Tetrapropyl orthosilicate**

For similar material(s): Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

##### **Tetra n-Butyl titanate**

No relevant data found.

##### **Octane**

For similar material(s): Did not cause birth defects in laboratory animals.

### Reproductive toxicity

Not classified based on available information.

#### Information for the Product:

Product test data not available.

#### Information for components:

##### **Distillates, petroleum, light distillate hydrotreating process, low-boiling**

For similar material(s): In animal studies, did not interfere with reproduction.

##### **Tetrakis(2-butoxyethyl) orthosilicate**

In laboratory animals, excessive doses toxic to the parent animals caused decreased weight and survival of offspring.

##### **Tetrapropyl orthosilicate**

For similar material(s): In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.

##### **Tetra n-Butyl titanate**

No relevant data found.

**Octane**

For similar material(s): In animal studies, did not interfere with reproduction.

**Mutagenicity**

Not classified based on available information.

**Information for the Product:**

Product test data not available.

**Information for components:****Distillates, petroleum, light distillate hydrotreating process, low-boiling**

For similar material(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Tetrakis(2-butoxyethyl) orthosilicate**

No relevant data found.

**Tetrapropyl orthosilicate**

In vitro genetic toxicity studies were negative.

**Tetra n-Butyl titanate**

No relevant data found.

**Octane**

For similar material(s): In vitro genetic toxicity studies were negative.

---

**12. ECOLOGICAL INFORMATION**

---

*Ecotoxicological information appears in this section when such data are available.*

**Toxicity****Distillates, petroleum, light distillate hydrotreating process, low-boiling****Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LL50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 10 mg/l, OECD Test Guideline 203 or Equivalent

**Acute toxicity to aquatic invertebrates**

EL50, Daphnia magna (Water flea), static test, 48 Hour, 4.5 mg/l, OECD Test Guideline 202 or Equivalent

**Acute toxicity to algae/aquatic plants**

For similar material(s):

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate, 3.1 mg/l, OECD Test Guideline 201

For similar material(s):



NOELR, *Pseudokirchneriella subcapitata* (green algae), 72 Hour, Growth rate, 0.5 mg/l, OECD Test Guideline 201

**Chronic toxicity to fish**

For similar material(s):

NOELR, *Pimephales promelas* (fathead minnow), semi-static test, 14 d, mortality, 2.6 mg/l

**Chronic toxicity to aquatic invertebrates**

Based on data from similar materials

NOELR, *Daphnia magna* (Water flea), semi-static test, 21 d, number of offspring, 2.6 mg/l

**Tetrakis(2-butoxyethyl) orthosilicate****Acute toxicity to fish**

Material is practically non-toxic to fish on an acute basis (LC50 > 100 mg/L).

LC50, *Danio rerio* (zebra fish), 96 Hour, > 201 mg/l, OECD Test Guideline 203

**Acute toxicity to aquatic invertebrates**

No toxicity at the limit of solubility

EC50, *Daphnia* sp. (water flea), 48 Hour, > 90 mg/l, EG 84/449

**Acute toxicity to algae/aquatic plants**

ErC50, *Scenedesmus subspicatus*, 72 Hour, > 161 mg/l, 88/302/EC

**Tetrapropyl orthosilicate****Acute toxicity to fish**

Material is practically non-toxic to fish on an acute basis (LC50 > 100 mg/L).

For similar material(s):

LC50, *Brachydanio rerio* (zebrafish), 96 Hour, > 201 mg/l

**Acute toxicity to aquatic invertebrates**

For similar material(s):

EC50, *Daphnia* sp. (water flea), 48 Hour, > 90 mg/l, OECD Test Guideline 202 or Equivalent

**Acute toxicity to algae/aquatic plants**

For similar material(s):

ErC50, *Desmodesmus subspicatus* (green algae), 72 Hour, Growth rate, > 161 mg/l

For similar material(s):

NOEC, *Desmodesmus subspicatus* (green algae), 72 Hour, Growth rate, 110 mg/l

**Toxicity to bacteria**

For similar material(s):

EC50, activated sludge, 3 Hour, Respiration rates., > 100 mg/l, OECD Test Guideline 209

**Tetra n-Butyl titanate****Acute toxicity to fish**

No relevant data found.

**Octane****Acute toxicity to fish**

Material is highly toxic to aquatic organisms on an acute basis (LC50/EC50 between 0.1 and 1 mg/L in the most sensitive species tested).

LC50, *Oryzias latipes* (Orange-red killifish), 96 Hour, 0.42 mg/l

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), 48 Hour, 0.3 mg/l, Method Not Specified.

**Acute toxicity to algae/aquatic plants**

Pseudokirchneriella subcapita, 72 Hour, Growth rate, >1.1 mg/l

**Chronic toxicity to aquatic invertebrates**

For similar material(s):

NOEC, Daphnia magna (Water flea), 21 d, 0.17 mg/l

**Persistence and degradability****Distillates, petroleum, light distillate hydrotreating process, low-boiling**

**Biodegradability:** No relevant data found.

**Tetrakis(2-butoxyethyl) orthosilicate**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

**Biodegradation:** 83 %

**Method:** OECD Test Guideline 301B

**Tetrapropyl orthosilicate**

**Biodegradability:** For similar material(s): Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

**Biodegradation:** 98 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301A or Equivalent

**Tetra n-Butyl titanate**

**Biodegradability:** No relevant data found.

**Octane**

**Biodegradability:** Material is expected to be readily biodegradable.

**Biodegradation:** > 60 %

**Exposure time:** 20 d

**Method:** Other guidelines

**Bioaccumulative potential****Distillates, petroleum, light distillate hydrotreating process, low-boiling**

**Bioaccumulation:** Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

**Tetrakis(2-butoxyethyl) orthosilicate**

**Bioaccumulation:** No relevant data found.

**Tetrapropyl orthosilicate**

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

**Partition coefficient: n-octanol/water(log Pow):** 3.4 Estimated by Structure-Activity Relationship (SAR).

**Tetra n-Butyl titanate**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 0.88 Estimated.

**Octane**

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

**Partition coefficient: n-octanol/water(log Pow):** 5.15 Literature

**Bioconcentration factor (BCF):** 198.7 Mytilus eduli (saltwater mussels) 105 min

**Mobility in soil****Distillates, petroleum, light distillate hydrotreating process, low-boiling**

No relevant data found.

**Tetrakis(2-butoxyethyl) orthosilicate**

No relevant data found.

**Tetrapropyl orthosilicate**

No relevant data found.

**Tetra n-Butyl titanate**

No relevant data found.

**Octane**

Potential for mobility in soil is medium (Koc between 150 and 500).

**Partition coefficient (Koc):** 436.8 Estimated.

---

## **13. DISPOSAL CONSIDERATIONS**

---

**Disposal methods:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN SDS SECTION 1: Identified Uses. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

**Treatment and disposal methods of used packaging:** Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility of the waste generator. Do not re-use containers for any purpose.

---

## 14. TRANSPORT INFORMATION

---

**DOT**

<b>Proper shipping name</b>	Flammable liquids, n.o.s.(Distillates, petroleum, light distillate hydrotreating process, low-boiling, Octane)
<b>UN number</b>	UN 1993
<b>Class</b>	3
<b>Packing group</b>	II

**Classification for SEA transport (IMO-IMDG):**

<b>Proper shipping name</b>	FLAMMABLE LIQUID, N.O.S.(Distillates, petroleum, light distillate hydrotreating process, low-boiling, Octane)
<b>UN number</b>	UN 1993
<b>Class</b>	3
<b>Packing group</b>	II
<b>Marine pollutant</b>	Distillates, petroleum, light distillate hydrotreating process, low-boiling
<b>Special precautions for user</b>	EmS: F-E, S-E
<b>Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code</b>	Consult IMO regulations before transporting ocean bulk

**Classification for AIR transport (IATA/ICAO):**

<b>Proper shipping name</b>	Flammable liquid, n.o.s.(Distillates, petroleum, light distillate hydrotreating process, low-boiling, Octane)
<b>UN number</b>	UN 1993
<b>Class</b>	3
<b>Packing group</b>	II

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

## 15. REGULATORY INFORMATION

---

**Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312**

Flammable (gases, aerosols, liquids, or solids)  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard  
Skin corrosion or irritation

Serious eye damage or eye irritation

**Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Pennsylvania Right To Know**

The following chemicals are listed because of the additional requirements of Pennsylvania law:

**Components**

Distillates, petroleum, light distillate hydrotreating process,  
low-boiling  
Tetra n-Butyl titanate  
Tetrapropyl orthosilicate  
Tetrakis(2-butoxyethyl) orthosilicate  
Octane

**CASRN**

68410-97-9  
5593-70-4  
682-01-9  
18765-38-3  
111-65-9

**California Prop. 65**

WARNING: This product can expose you to chemicals including Ethylbenzene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**United States TSCA Inventory (TSCA)**

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

---

## 16. OTHER INFORMATION

---

**Hazard Rating System**

**NFPA**

Health	Flammability	Instability
3	3	0

**HMIS**

Health	Flammability	Physical Hazard
3*	3	0

\* = Chronic Effects (See Hazards Identification)

**Revision**

Identification Number: 4094481 / A713 / Issue Date: 05/22/2025 / Version: 13.0

In case this version of the SDS contains significant changes from the previous version, they are listed below or noted by bold, double bars in the left-hand margin throughout this document.

Changes encompass identification, hazards, tox/eco-tox information and the addition/removal of the ingredients, and regulatory information, hazard information, uses, risk management measures and other key regulatory changes of the product. Detailed explanation of the changes can be obtained upon request.

**Legend**

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
TWA	8-hour, time-weighted average

**Full text of other abbreviations**

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

**Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW SILICONES CORPORATION urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the

safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US