



# SAFETY DATA SHEET

## DOW SILICONES CORPORATION

**Product name:** DOWSIL™ PR-2260 Prime Coat

**Issue Date:** 07/13/2020

**Print Date:** 07/14/2020

DOW SILICONES CORPORATION encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

---

## 1. IDENTIFICATION

---

**Product name:** DOWSIL™ PR-2260 Prime Coat

**Recommended use of the chemical and restrictions on use**

**Identified uses:** Adhesive, binding agents

**COMPANY IDENTIFICATION**

DOW SILICONES CORPORATION  
2200 WEST SALZBURG ROAD  
MIDLAND MI 48686-0994  
UNITED STATES

**Customer Information Number:**

800-258-2436  
SDSQuestion@dow.com

**EMERGENCY TELEPHONE NUMBER**

**24-Hour Emergency Contact:** 1 800 424 9300

**Local Emergency Contact:** 800-424-9300

---

## 2. HAZARDS IDENTIFICATION

---

**Hazard classification**

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids - Category 2

Skin irritation - Category 2

Serious eye damage - Category 1

Specific target organ toxicity - single exposure - Category 3

Aspiration hazard - Category 1

**Label elements**

**Hazard pictograms**



Signal word: **DANGER!**

**Hazards**

Highly flammable liquid and vapour.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye damage.  
May cause drowsiness or dizziness.

**Precautionary statements****Prevention**

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/ eye protection/ face protection.

**Response**

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
Do NOT induce vomiting.  
If skin irritation occurs: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage**

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

**Disposal**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

Static-accumulating flammable liquid.

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

---

**Chemical nature:** Silicone in solvent  
This product is a mixture.

**Component****CASRN****Concentration**

---

Heptane	142-82-5	>= 67.0 - <= 81.0 %
Trimethoxyvinylsilane	2768-02-7	>= 14.0 - <= 20.0 %
Tetra n-Butyl titanate	5593-70-4	>= 2.3 - <= 3.1 %

---

## 4. FIRST AID MEASURES

---

### Description of first aid measures

#### General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

**Skin contact:** Wash off with plenty of water.

**Eye contact:** Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

**Ingestion:** Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

#### Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

#### Indication of any immediate medical attention and special treatment needed

**Notes to physician:** Maintain adequate ventilation and oxygenation of the patient. Exposure may increase "myocardial irritability". Do not administer sympathomimetic drugs such as epinephrine unless absolutely necessary. Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably from an ophthalmologist. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. The decision of whether to induce vomiting or not should be made by a physician. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

---

## 5. FIREFIGHTING MEASURES

---

### Extinguishing media

**Suitable extinguishing media:** Alcohol-resistant foam. Dry sand. Dry chemical.

**Unsuitable extinguishing media:** High volume water jet. Do not use direct water stream..

### Special hazards arising from the substance or mixture

**Hazardous combustion products:** Carbon oxides. Silicon oxides. Metal oxides.

**Unusual Fire and Explosion Hazards:** Flash back possible over considerable distance.. Exposure to combustion products may be a hazard to health.. Flammable concentrations of vapor can accumulate at temperatures above flash point; see Section 9.. Flammable mixtures may exist within the vapor space of containers at room temperature.. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat.. Vapours may form explosive mixtures with air..

### Advice for firefighters

**Fire Fighting Procedures:** Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage.. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.. Do not use a solid water stream as it may scatter and spread fire.. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

**Special protective equipment for firefighters:** In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

---

## 6. ACCIDENTAL RELEASE MEASURES

---

**Personal precautions, protective equipment and emergency procedures:** Remove all sources of ignition. Ventilate the area. Use personal protective equipment. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Ground and bond all containers and handling equipment. Vapor explosion hazard. Keep out of sewers. Follow safe handling advice and personal protective equipment recommendations.

**Environmental precautions:** Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

**Methods and materials for containment and cleaning up:** Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. See sections: 7, 8, 11, 12 and 13.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:** Do not get on skin or clothing. Do not breathe vapours or spray mist. Do not swallow. Do not get in eyes. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Non-sparking tools should be used. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation. Ensure all equipment is electrically grounded before beginning transfer operations. This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations. Restrict flow velocity in order to reduce the accumulation of static electricity. Ground and bond container and receiving equipment.

**Conditions for safe storage:** Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Flammable solids. Pyrophoric liquids. Pyrophoric solids. Self-heating substances and mixtures. Substances and mixtures, which in contact with water, emit flammable gases. Explosives. Gases. Unsuitable materials for containers: None known.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Heptane	Dow IHG	TWA	100 ppm
	ACGIH	TWA	400 ppm
	ACGIH	STEL	500 ppm
	OSHA Z-1	TWA	2,000 mg/m3 500 ppm
	OSHA P0	TWA	1,600 mg/m3 400 ppm
	OSHA P0	STEL	2,000 mg/m3 500 ppm
Trimethoxyvinylsilane	Dow IHG	TWA	1 ppm
Methanol	ACGIH	TWA	200 ppm
	Further information: Skin: Danger of cutaneous absorption		
	ACGIH	STEL	250 ppm
	Further information: Skin: Danger of cutaneous absorption		
	OSHA Z-1	TWA	260 mg/m3 200 ppm
Propyl alcohol	ACGIH	TWA	100 ppm
	Further information: A4: Not classifiable as a human carcinogen		
	OSHA Z-1	TWA	500 mg/m3 200 ppm
	OSHA P0	STEL	625 mg/m3 250 ppm
	OSHA P0	TWA	500 mg/m3 200 ppm
Butanol	ACGIH	TWA	20 ppm
	OSHA Z-1	TWA	300 mg/m3 100 ppm

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing: Methanol, Propyl alcohol, butanol

#### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

#### Exposure controls

**Engineering controls:** Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only in enclosed systems or with local exhaust ventilation. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. Lethal concentrations may exist in areas with poor ventilation.

#### Individual protection measures

**Eye/face protection:** Use chemical goggles.

##### Skin protection

**Hand protection:** Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. When respiratory protection is required, use an approved positive-pressure self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### Appearance

Physical state	liquid
Color	colourless
Odor	solvent-like
Odor Threshold	No data available
pH	No data available
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	98 °C ( 208 °F)
Flash point	<b>Pensky-Martens closed cup</b> 8.8 °C ( 47.8 °F)
Evaporation Rate (Butyl Acetate = 1)	No data available
Flammability (solid, gas)	Not applicable
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	0.7
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Kinematic Viscosity	1 cSt at 25 °C (77 °F)
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.
Molecular weight	No data available
Particle size	Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** Not classified as a reactivity hazard.

**Chemical stability:** Stable under normal conditions.

**Possibility of hazardous reactions:** Can react with strong oxidizing agents. Vapours may form explosive mixture with air. Highly flammable liquid and vapour.

**Conditions to avoid:** Avoid static discharge. Heat, flames and sparks.

**Incompatible materials:** Oxidizing agents

**Hazardous decomposition products:**

Decomposition products can include and are not limited to: Methanol. Propyl alcohol. Butanol.

---

## 11. TOXICOLOGICAL INFORMATION

---

*Toxicological information appears in this section when such data is available.*

### Information on likely routes of exposure

Inhalation, Eye contact, Skin contact, Ingestion.

### Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

#### Acute oral toxicity

Very low toxicity if swallowed. Swallowing may result in gastrointestinal irritation. May cause nausea and vomiting. May cause central nervous system effects.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):  
LD50, > 5,000 mg/kg Estimated.

#### Information for components:

##### Heptane

For similar material(s): May cause nausea and vomiting. May cause central nervous system effects. LD50, Rat, male and female, > 5,000 mg/kg

##### Trimethoxyvinylsilane

LD50, Rat, male, 7,120 mg/kg

LD50, Rat, female, 7,236 mg/kg

##### Tetra n-Butyl titanate

LD50, Rat, male, 4,220 mg/kg

#### Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):  
LD50, > 2,000 mg/kg Estimated.

#### Information for components:

##### Heptane

For similar material(s): LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

##### Trimethoxyvinylsilane

LD50, Rabbit, female, 3,259 mg/kg

LD50, Rabbit, male, 3,880 mg/kg



**Tetra n-Butyl titanate**

LD50, Rabbit, 5,300 mg/kg

**Acute inhalation toxicity**

In confined or poorly ventilated areas, vapor can readily accumulate and can cause unconsciousness and death. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed. May cause respiratory irritation and central nervous system depression. Excessive exposure may increase sensitivity to epinephrine and increase myocardial irritability (irregular heartbeats). May cause nausea and vomiting. May cause abdominal discomfort or diarrhea.

As product: The LC50 has not been determined.

**Information for components:**

**Heptane**

LC50, Rat, male and female, 4 Hour, vapour, > 29.3 mg/l No deaths occurred at this concentration.

**Trimethoxyvinylsilane**

LC50, Rat, male and female, 4 Hour, vapour, 16.8 mg/l

**Tetra n-Butyl titanate**

LC50, Rat, 4 Hour, dust/mist, 11 mg/l

**Skin corrosion/irritation**

Based on information for component(s):

Prolonged contact may cause moderate skin irritation with local redness.

May cause burning sensation.

May cause itching.

May cause drying and flaking of the skin.

May stain skin.

**Information for components:**

**Heptane**

Brief contact may cause slight skin irritation with local redness.

May cause burning sensation.

May cause itching.

May cause drying and flaking of the skin.

May stain skin.

**Trimethoxyvinylsilane**

Brief contact is essentially nonirritating to skin.

**Tetra n-Butyl titanate**

Prolonged contact may cause moderate skin irritation with local redness.

**Serious eye damage/eye irritation**

Based on information for component(s):

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

**Information for components:**

**Heptane**

May cause slight temporary eye irritation.  
May cause slight temporary corneal injury.  
May cause pain disproportionate to the level of irritation to eye tissues.

**Trimethoxyvinylsilane**

May cause slight temporary eye irritation.  
Corneal injury is unlikely.  
Vapor may cause eye irritation experienced as mild discomfort and redness.

**Tetra n-Butyl titanate**

May cause moderate eye irritation.  
May cause severe corneal injury.  
May cause permanent impairment of vision.

**Sensitization**

For the major component(s):  
For similar material(s):  
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Information for components:**

**Heptane**

For similar material(s):  
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Trimethoxyvinylsilane**

For skin sensitization:  
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Tetra n-Butyl titanate**

Did not demonstrate the potential for contact allergy in mice.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

**Information for components:**

**Heptane**

May cause drowsiness or dizziness.  
Route of Exposure: Inhalation  
Target Organs: Central nervous system

**Trimethoxyvinylsilane**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Tetra n-Butyl titanate**

May cause respiratory irritation.  
Route of Exposure: Inhalation  
Target Organs: Respiratory Tract  
May cause drowsiness or dizziness.  
Route of Exposure: Inhalation  
Target Organs: Nervous system

**Aspiration Hazard**

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia.

**Information for components:**

**Heptane**

May be fatal if swallowed and enters airways.

**Trimethoxyvinylsilane**

Based on physical properties, not likely to be an aspiration hazard.

**Tetra n-Butyl titanate**

Based on available information, aspiration hazard could not be determined.

**Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)**

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Contains component(s) which have been reported to cause effects on the following organs in animals:  
Blood.  
Kidney.  
Bladder.

Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed.

Heptane is part of a mixture which caused polyneuropathy. However, there is no clear evidence that heptane causes peripheral nervous system effects.

**Information for components:**

**Heptane**

Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

Heptane is part of a mixture which caused polyneuropathy. However, there is no clear evidence that heptane causes peripheral nervous system effects.

**Trimethoxyvinylsilane**

In animals, effects have been reported on the following organs:  
Kidney.

Bladder.

Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed.

**Tetra n-Butyl titanate**

No relevant data found.

**Carcinogenicity**

No relevant data found.

**Information for components:**

**Heptane**

No relevant data found.

**Trimethoxyvinylsilane**

No relevant data found.

**Tetra n-Butyl titanate**

No relevant data found.

**Teratogenicity**

Contains component(s) which, in laboratory animals, have been toxic to the fetus only at doses toxic to the mother.

**Information for components:**

**Heptane**

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

**Trimethoxyvinylsilane**

Has been toxic to the fetus in laboratory animals at doses toxic to the mother.

**Tetra n-Butyl titanate**

No relevant data found.

**Reproductive toxicity**

For the major component(s): For similar material(s): In animal studies, did not interfere with reproduction.

**Information for components:**

**Heptane**

For similar material(s): In animal studies, did not interfere with reproduction.

**Trimethoxyvinylsilane**

In animal studies, did not interfere with reproduction.

**Tetra n-Butyl titanate**

No relevant data found.

**Mutagenicity**

In vitro genetic toxicity studies were negative for component(s) tested.

**Information for components:****Heptane**

In vitro genetic toxicity studies were negative.

**Trimethoxyvinylsilane**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Tetra n-Butyl titanate**

No relevant data found.

---

**12. ECOLOGICAL INFORMATION**

---

*Ecotoxicological information appears in this section when such data is available.*

**Toxicity****Heptane****Acute toxicity to fish**

Material is highly toxic to aquatic organisms on an acute basis (LC50/EC50 between 0.1 and 1 mg/L in the most sensitive species tested).

LL50, Oncorhynchus mykiss (rainbow trout), 96 Hour, 5.738 mg/l

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), static test, 48 Hour, 1.5 mg/l

EC50, crustacean Chaetogammarus marinus, 48 Hour, 0.2 mg/l

**Acute toxicity to algae/aquatic plants**

EL50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Biomass, 4.34 mg/l

NOELR, Pseudokirchneriella subcapitata (green algae), 72 Hour, Biomass, 0.97 mg/l,

Estimated.

**Trimethoxyvinylsilane****Acute toxicity to fish**

Material is practically non-toxic to aquatic invertebrates on an acute basis (LC50/EC50 > 100 mg/L).

For the hydrolysis product:

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, 191 mg/l

**Acute toxicity to aquatic invertebrates**

For the hydrolysis product(s)

EC50, Daphnia magna (Water flea), static test, 48 Hour, 168.7 mg/l

**Acute toxicity to algae/aquatic plants**

For the hydrolysis product(s)

EC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, Growth rate inhibition, > 89 mg/l

For the hydrolysis product(s)

NOEC, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, Growth rate inhibition, 89 mg/l

**Toxicity to bacteria**

EC50, activated sludge, 3 Hour, Respiration rates., > 100 mg/l, OECD Test Guideline 209

**Chronic toxicity to aquatic invertebrates**

For the hydrolysis product:

NOEC, Daphnia magna (Water flea), 21 d, number of offspring, 28.1 mg/l

**Tetra n-Butyl titanate****Acute toxicity to fish**

No relevant data found.

**Persistence and degradability****Heptane**

**Biodegradability:** Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability. Biodegradation rate may increase in soil and/or water with acclimation.

**Theoretical Oxygen Demand:** 3.52 mg/g

**Trimethoxyvinylsilane**

**Biodegradability:** Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

**Biodegradation:** 51 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301F or Equivalent

**Tetra n-Butyl titanate**

**Biodegradability:** No relevant data found.

**Bioaccumulative potential****Heptane**

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

**Partition coefficient: n-octanol/water(log Pow):** 4.397 Estimated.

**Bioconcentration factor (BCF):** 552 Fish Measured

**Trimethoxyvinylsilane**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** -0.82 Estimated.

**Tetra n-Butyl titanate**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 0.88 Estimated.

**Mobility in soil****Heptane**

Expected to be relatively immobile in soil (Koc > 5000).

**Partition coefficient (Koc):** 2040 - 16000 Estimated.

**Trimethoxyvinylsilane**

No relevant data found.

**Tetra n-Butyl titanate**

No relevant data found.

---

---

**13. DISPOSAL CONSIDERATIONS**

---

**Disposal methods:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

**Treatment and disposal methods of used packaging:** Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

---

---

**14. TRANSPORT INFORMATION**

---

**DOT**

<b>Proper shipping name</b>	Flammable liquids, n.o.s.(Heptane, Alkoxysilane)
<b>UN number</b>	UN 1993
<b>Class</b>	3
<b>Packing group</b>	II
<b>Marine pollutant</b>	Heptane

**Classification for SEA transport (IMO-IMDG):**

<b>Proper shipping name</b>	FLAMMABLE LIQUID, N.O.S.(Heptane, Alkoxysilane)
<b>UN number</b>	UN 1993
<b>Class</b>	3
<b>Packing group</b>	II
<b>Marine pollutant</b>	Heptane
<b>Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code</b>	Consult IMO regulations before transporting ocean bulk

**Classification for AIR transport (IATA/ICAO):**

<b>Proper shipping name</b>	Flammable liquid, n.o.s.(Heptane, Alkoxysilane)
<b>UN number</b>	UN 1993

<b>Class</b>	3
<b>Packing group</b>	II

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

## 15. REGULATORY INFORMATION

---

### **Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312**

Flammable (gases, aerosols, liquids, or solids)

Hazard not otherwise classified (physical hazards)

Aspiration hazard

Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

### **Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### **Pennsylvania Right To Know**

The following chemicals are listed because of the additional requirements of Pennsylvania law:

<b>Components</b>	<b>CASRN</b>
Heptane	142-82-5
Trimethoxyvinylsilane	2768-02-7
Tetrapropyl orthosilicate	682-01-9
Tetra n-Butyl titanate	5593-70-4

### **California Prop. 65**

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### **United States TSCA Inventory (TSCA)**

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.



---

## 16. OTHER INFORMATION

---

### Hazard Rating System

#### NFPA

Health	Flammability	Instability
2	3	0

#### HMIS

Health	Flammability	Physical Hazard
3/	3	0

### Revision

Identification Number: 4094470 / A713 / Issue Date: 07/13/2020 / Version: 6.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

### Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
Dow IHG	Dow Industrial Hygiene Guideline
OSHA P0	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
STEL	Short-term exposure limit
TWA	Time weighted average

### Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European

Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

**Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW SILICONES CORPORATION urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US