DOWSIL™ SE 4430 B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/18/2017

 6.0
 03/09/2018
 971641-00009
 Date of first issue: 12/19/2014

SECTION 1. IDENTIFICATION

Product name : DOWSIL™ SE 4430 B

Product code : 06020486

Manufacturer or supplier's details

Company Identification : THE DOW CHEMICAL COMPANY

2030 WILLARD H DOW CENTER

MIDLAND MI 48674-0000

UNITED STATES

Telephone : 800-258-2436

24-Hour Emergency Contact : Chemtrec +1 800-424-9300

Local Emergency Number : 800-424-9300

E-mail address : SDSQuestion@dow.com

Recommended use of the chemical and restrictions on use

Recommended use : Electrical industry and electronics

Polymer

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :

Signal Word : Warning

Hazard Statements : H361f Suspected of damaging fertility.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P234 Keep only in original container.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

Storage:

P403 Store in a well-ventilated place.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

May generate flammable hydrogen gas. Avoid contact with water, alcohols, acidic, basic, or oxidizing materials.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Silicone compound

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Aluminum oxide	1344-28-1	>= 68 - <= 83
Octamethylcyclotetrasiloxane	556-67-2	>= 0.16 - <= 0.22
Carbon black	1333-86-4	>= 0.16 - <= 0.22

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

Suspected of damaging fertility.

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

delayed

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Unsuitable extinguishing

media

Dry chemical

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health. Applying foam will release significant amounts of hydrogen

gas that can be trapped under the foam blanket.

Hazardous combustion prod-

ucts

Metal oxides Carbon oxides

Silicon oxides Formaldehyde

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Do not allow extinguishing medium to contact container contents. Most fire extinguishing media will cause hydrogen evolution, and once the fire is put out, may accumulate in poorly ventilated or confined areas and result in flash fire or explo-

sion if ignited.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Materials in contact with water, moisture, acids or bases have the potential to generate hydrogen gas. Recovered material

should be stored in a vented container.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

Recovered material should be stored in a vented container. The vent must prevent the ingress of water as further reaction with spilled materials can take place which could lead to

overpressurization of the container.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid inhalation of vapor or mist.

Do not swallow.

Avoid contact with eyes.

Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep away from water. Protect from moisture.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in original container.

Store in a closed container.

Store in accordance with the particular national regulations. Product may evolve minute quantities of flammable hydrogen gas which can accumulate. Adequately ventilate to maintain vapors well below flammability limits and exposure guidelines. Do not repackage. Clogged container vents may increase

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

pressure build up.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Packaging material : Unsuitable material: Do not store in or use containers except

the original product package.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum oxide	1344-28-1	TWA (total dust)	15 mg/m³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m³	OSHA Z-1
		TWA (Respirable fraction)	1 mg/m³ (Aluminum)	ACGIH
Octamethylcyclotetrasiloxane	556-67-2	TWA	10 ppm	US WEEL
Carbon black	1333-86-4	TWA	3.5 mg/m ³	NIOSH REL
		TWA	3.5 mg/m ³	OSHA Z-1
		TWA (Inhal- able fraction)	3 mg/m³	ACGIH

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carbon black

Engineering measures : Processing may form hazardous compounds (see section

10).

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are

unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

These precautions are for room temperature handling. Use at

elevated temperature or aerosol/spray applications may

require added precautions.

For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Chemical customer service group.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : gray

Odor : none

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

100 °C

Flash point : $> 100 \, ^{\circ}\text{C}$

Method: closed cup

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Not applicable

Self-ignition : The substance or mixture is not classified as pyrophoric. The

substance or mixture is not classified as self heating.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 2.21

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : 45 Poise

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Contact with water liberates highly flammable gases.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Can react with strong oxidizing agents.

When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapors. Safe handling conditions may be maintained by keeping vapor

concentrations within the occupational exposure limit for

formaldehyde.

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

See OSHA formaldehyde standard, 29 CFR 1910.1048 Formaldehyde may cause cancer. It is also toxic by inhalation, skin absorption and ingestion, corrosive to skin and eyes, and

may cause skin sensitization and respiratory irritation.

Product may evolve flammable hydrogen gas on contact with water, alcohols, acidic or basic materials, many metals or metallic compounds and can form explosive mixtures in air. Hazardous decomposition products will be formed at elevated

temperatures.

Conditions to avoid : Exposure to moisture.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Ingredients:

Aluminum oxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Octamethylcyclotetrasiloxane:

Acute oral toxicity : LD50 (Rat): > 4,800 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: On basis of test data.

Acute inhalation toxicity : LC50 (Rat): 2975 ppm

Exposure time: 4 h
Test atmosphere: vapor

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: On basis of test data.

Acute dermal toxicity : LD50 (Rabbit): > 2.5 ml/kg

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: On basis of test data.

Carbon black:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0.0046 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Ingredients:

Aluminum oxide:

Species: Rabbit

Result: No skin irritation

Octamethylcyclotetrasiloxane:

Species: Rabbit

Result: No skin irritation

Remarks: On basis of test data.

Carbon black:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Ingredients:

Aluminum oxide:

Species: Rabbit

Result: No eye irritation

Octamethylcyclotetrasiloxane:

Species: Rabbit

Result: No eye irritation

Remarks: On basis of test data.

Carbon black:

Species: Rabbit

Result: No eye irritation

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:

Aluminum oxide:

Test Type: Maximization Test Routes of exposure: Skin contact

Species: Guinea pig Result: negative

Octamethylcyclotetrasiloxane:

Assessment: Does not cause skin sensitization.

Test Type: Maximization Test

Species: Guinea pig Result: negative

Remarks: On basis of test data.

Carbon black:

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Aluminum oxide:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 475

Result: positive

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

Remarks: Based on data from similar materials

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Octamethylcyclotetrasiloxane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: On basis of test data.

Test Type: Mutagenicity (in vitro mammalian cytogenetic test)

Result: negative

Remarks: On basis of test data.

Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: On basis of test data.

Test Type: In vitro sister chromatid exchange assay in mam-

malian cells Result: negative

Remarks: On basis of test data.

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Remarks: On basis of test data.

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (vapor)

Result: negative

Remarks: On basis of test data.

Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: On basis of test data.

Germ cell mutagenicity -

Assessment

Animal testing did not show any mutagenic effects.

Carbon black:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Carcinogenicity

Not classified based on available information.

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

Ingredients:

Aluminum oxide:

Species: Rat

Application Route: inhalation (dust/mist/fume)

Exposure time: 86 weeks

Result: negative

IARC Group 2B: Possibly carcinogenic to humans

Carbon black 1333-86-4

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Suspected of damaging fertility.

Ingredients:

Aluminum oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Octamethylcyclotetrasiloxane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat, male and female Application Route: inhalation (vapor) Symptoms: Effects on fertility. Remarks: On basis of test data.

Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)

Species: Rabbit

Application Route: inhalation (vapor)

Symptoms: No effects on fetal development.

Remarks: On basis of test data.

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on sexual function and

fertility, based on animal experiments.

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Ingredients:

Octamethylcyclotetrasiloxane:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg

bw or less.

Routes of exposure: inhalation (vapor)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or

less.

Routes of exposure: Skin contact

Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg

bw or less.

Carbon black:

Routes of exposure: inhalation (dust/mist/fume)

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d

or less.

Repeated dose toxicity

Ingredients:

Aluminum oxide:

Species: Dog

Application Route: Ingestion Exposure time: 90 Days Symptoms: No adverse effects.

Species: Rat

Application Route: inhalation (dust/mist/fume)

Exposure time: 90 Days Symptoms: No adverse effects.

Octamethylcyclotetrasiloxane:

Species: Rat

Application Route: Ingestion Remarks: On basis of test data.

Species: Rat

Application Route: inhalation (vapor) Remarks: On basis of test data.

Species: Rabbit

Application Route: Skin contact Remarks: On basis of test data.

DOWSIL™ SE 4430 B



Version **Revision Date:** SDS Number: Date of last issue: 05/18/2017 03/09/2018 971641-00009 Date of first issue: 12/19/2014 6.0

Carbon black:

Species: Rat NOAEL: 1 mg/m³ LOAEL: 7 mg/m³

Application Route: Inhalation Test atmosphere: dust/mist Exposure time: 90 Days

Remarks: These substance(s) are inextricably bound in the product and therefore do not

contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

Further information

Ingredients:

Octamethylcyclotetrasiloxane:

Remarks: Results from a 2 year repeated vapor inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Aluminum oxide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 218.64 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

: EC50 (Selenastrum capricornutum (green algae)): > 100 mg/l Toxicity to algae

Exposure time: 72 h

Toxicity to fish (Chronic toxic: :

NOEC (Pimephales promelas (fathead minnow)): 7.1 mg/l

Exposure time: 7 d

aquatic invertebrates (Chronic toxicity)

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 1.89 mg/l

Exposure time: 28 d

Octamethylcyclotetrasiloxane:

Toxicity to fish LC50 (Cyprinodon variegatus (sheepshead minnow)): >

0.0063 mg/l

Exposure time: 336 h

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Mysidopsis bahia (opossum shrimp)): > 0.0091 mg/l

Exposure time: 96 h

Remarks: No toxicity at the limit of solubility.

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): >

0.022 mg/l

Exposure time: 72 h

Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic toxic-:

ity)

NOEC (Oncorhynchus mykiss (rainbow trout)): >= 0.0044 mg/l

Remarks: On basis of test data. No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

NOEC (Daphnia magna (Water flea)): >= 0.0079 mg/l

Exposure time: 21 d

Remarks: On basis of test data. No toxicity at the limit of solubility.

Ecotoxicology Assessment

Chronic aquatic toxicity

May cause long lasting harmful effects to aquatic life.

Carbon black:

Toxicity to fish : LC0 (Danio rerio (zebra fish)): 1,000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 5,600 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): 10,000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Persistence and degradability

Ingredients:

Octamethylcyclotetrasiloxane:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 3.7 % Exposure time: 28 d

Method: OECD Test Guideline 310

Stability in water : Degradation half life: 69.3 - 144 h (24.6 °C) pH: 7

Method: OECD Test Guideline 111

DOWSIL™ SE 4430 B



Version **Revision Date:** SDS Number: Date of last issue: 05/18/2017 03/09/2018 971641-00009 Date of first issue: 12/19/2014 6.0

Bioaccumulative potential

Ingredients:

Octamethylcyclotetrasiloxane:

Bioaccumulation Species: Pimephales promelas (fathead minnow)

Bioconcentration factor (BCF): 12,400

Partition coefficient: n-

octanol/water

log Pow: 6.48 (25.1 °C)

Mobility in soil

No data available

Other adverse effects

Ingredients:

Octamethylcyclotetrasiloxane:

Results of PBT and vPvB

assessment

Remarks: Octamethylcyclotetrasiloxane (D4) meets the current REACh Annex XIII criteria for PBT and vPvB. In Canada, D4 has been assessed and deemed to meet the PiT criteria. However, D4 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terrestrial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and

Recovery Act (RCRA)

This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded

in its purchased form.

Waste from residues Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

Remarks : VENTED PACKAGES ARE FORBIDDEN FOR AIR

TRANSPORT.

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Reproductive toxicity

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Aluminum oxide 1344-28-1
Dimethyl Siloxane, Dimethylvinylsiloxy-terminated 68083-19-2
Dimethyl, Methylhydrogen Siloxane, Trimethylsiloxy- 68037-59-2

terminated

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

California List of Hazardous Substances

Aluminum oxide 1344-28-1

California Permissible Exposure Limits for Chemical Contaminants

Aluminum oxide 1344-28-1

The ingredients of this product are reported in the following inventories:

KECI : All ingredients listed, exempt or notified.

TCSI : All ingredients listed or exempt.

REACH : For purchases from Dow Chemical EU legal entities, all

DOWSIL™ SE 4430 B



Version Revision Date: SDS Number: Date of last issue: 05/18/2017 6.0 03/09/2018 971641-00009 Date of first issue: 12/19/2014

ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Chemical legal entities with the intention to export into EEA please contact your DC

representative/local office.

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from

inventory listing.

PICCS : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA


1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

DOWSIL™ SE 4430 B



Version **Revision Date:** SDS Number: Date of last issue: 05/18/2017 03/09/2018 971641-00009 Date of first issue: 12/19/2014 6.0

workday during a 40-hour workweek

OSHA Z-1 / TWA 8-hour time weighted average

US WEEL / TWA Time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR -No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date 03/09/2018

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DOWSIL™ SE 4430 B



Version 6.0 Revision Date: 03/09/2018

SDS Number: 971641-00009

Date of last issue: 05/18/2017 Date of first issue: 12/19/2014

US / Z8