

## **KIT - SAFETY DATA SHEET**

Product identifier used on the

Kit Name MA420 (AO420) BLACK

Stock No.:

Other means of identification:

Recommended use of the chemical and restrictions on use:

 $\underline{\hbox{Chemical manufacturer address and telephone number:}}$ 

Manufacturer Name: ITW Polymers Adhesives, North America

Address: 30 Endicott Street Danvers, MA 01923

Component list			
Component A	AO420 ADHESIVE		
Component B	MA420 - AO420 EU BLACK ACTIVATOR		
Kit SDS Revision Date	1/13/2015		

# **Component A - SDS**

# SECTION 1: IDENTIFICATION

Product identifier used on the label:

Product Name: A 0420 A DHESIVE

Other means of identification:

Synonyms: None.

Recommended use of the chemical and restrictions on use: Product Use/Restriction: Not applicable.

Chemical manufacturer address and telephone number:

Manufacturer Name: ITW Polymers Adhesives, North America

Address: 30 Endicott Street Danvers, MA 01923 General Phone Number: (978) 777-1100

Emergency phone number:

Emergency Phone Number: (800) 424-9300

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300

# SECTION 2: HAZARD(S) IDENTIFICATION

 $\underline{\textit{Classification of the chemical in accordance with CFR 1910.1200(d)(f):}\\$ 

GHS Pictograms:

Signal Word: DANGER.

GHS Class: Flammable Liquid. Category 2. Serious Eye Damage. category 1.

Revision:: 1/13/2015

Skin corrosion. category 1. Skin Sensitization. category 1.

Specific Target Organ Toxicity - STOT, Single Exposure SE. Category 3.

H225 - Highly flammable liquid and vapor. Hazard Statements:

H318 - Causes serious eye damage. H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction.

H335 - May cause respiratory irritation.

Precautionary Statements: P210 - Keep away from heat/sparks/open flames/hotsurfaces. — No smoking.

P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do not induce vomiting.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P303+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.
Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/physician.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P321 - Specific treatment (see ... on this label).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use day chemical carbon dioxide to extinguish small fires. Use water for

P370+P378 - In case of fire: Use dry chemical, carbon dioxide to extinguish small fires. Use water for

large fires. P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.

 $P501 - Dispose \ of \ contents/container \ in \ accordance \ with \ Local, \ State, \ Federal \ and \ Provincial \ regulations.$ 

#### Hazards not otherwise classified that have been identified during the classification process:

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may Eye:

cause lacrimation, conjunctivitis, corneal damage and permanent injury.

Skin: Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling. Allergic reactions are

May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this

Inhalation: Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects.

Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal

Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible

tissue destruction.

Signs/Symptoms: Overexposure can cause headaches, dizziness, nausea, and vomiting.

Target Organs: Eves, Skin, Respiratory system, Digestive system, Central nervous system, Liver, Kidney, Olfactory

Function.

Aggravation of Pre-Existing Conditions: Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

Chemical Name	CAS#	Ingredient Percent	EC Num.
2-Propenoic acid, 2-methyl-, polymer with 2-chloro-1,3-butadiene	25053-30-9	1 - 10 by weight	
Methyl Methacrylate Monomer	80-62-6	60 - 70 by weight	
Methacrylic acid	79-41-4	1 - 10 by weight	
Proprietary Ingredient(s)	No Data	10 - 20 by weight	

#### SECTION 4: FIRST AID MEASURES

Description of necessary measures:

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.Eve Contact:

 $Immediately \ wash \ skin \ with \ plenty \ of soap \ and \ water for 15 \ to \ 20 \ minutes, \ while \ removing contaminated \ clothing \ and \ shoes. \ Get \ medical \ attention \ if \ irritation \ develops \ or \ persists.$ Skin Contact:

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

# SECTION 5: FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media: Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.

Unsuitable extinguishing media: Water may cause frothing.

Unusual Fire Hazards: Sealed containers at elevated temperatures may rupture explosively and spread fire due to

polymerization.

Special protective equipment and precautions for fire-fighters:

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.

Fire Fighting Instructions: Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to

minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

Vapors can flow along surfaces to distant ignition sources and flash back.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Personal Precautions:

Environmental precautions:

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Methods and materials for containment and cleaning up:

Spill Cleanup Measures:

Absorb spill with inert material (e,g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Collect spill with a non-sparking tool. Place into a suitable container for disposal. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Flammable, eliminate ignition sources. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to distant ignition sources and flash back. Ventilate area. Use proper personal protective equipment as listed in Section 8

protective equipment as listed in Section 8.

Reference to other sections:

Other Precautions: Pump or shovel to storage/salvage vessels. Add inhibitor to prevent polymerization.

#### SECTION 7: HANDLING and STORAGE

Precautions for safe handling:

Use with adequate ventilation. Avoid breathing vapor, aerosol or mist. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures. Do not Handling:

reuse containers without proper cleaning or reconditioning.

Hygiene Practices: Wash thoroughly after handling.

Special Handling Procedures: Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10)

during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product. Hazardous liquid or vapor residue may remain in emptied container. Do not reuse, heat, burn, pressurize, cut, weld, braze, solder, drill, grind, expose to sparks, flame, or ignition sources of empty containers without proper commercial cleaning or reconditioning.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, direct sunlight, and incompatible substances. Keep container tightly closed when not in use. Storage:

## SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

**Methyl Methacrylate Monomer:** 

TLV-STEL: 100 ppm TLV-TWA: 50 ppm Guideline ACGIH:

Sensitizer.

Guideline OSHA: PEL-TWA: 100 ppm

Methacrylic acid:

Guideline ACGIH: TLV-TWA: 20 ppm

Appropriate engineering controls:

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other

engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Individual protection measures:

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166. Eye/Face Protection:

Skin Protection Description: Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult

manufacturer's data for permeability data.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be

permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective:

#### Notes:

# SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

#### PHYSICAL AND CHEMICAL PROPERTIES:

Physical State Appearance: Paste. Color: off-white. Odor: Fragrant.

213°F (100.5°C) Boiling Point: -54°F (-47.7°C) Melting Point:

Specific Gravity: 0.96

Solubility: Not determined. Vapor Density: > 1 (air = 1) Vapor Pressure: 28 mmHg @68°F Percent Volatile: Not determined. Evaporation Rate: 3 (butyl acetate = 1) Not determined.

Molecular Formula: Mixture Molecular Weight: Mixture Flash Point: 50°F (10°C)

Flash Point Method: Tag closed cup. (TCC)

Lower Flammable/Explosive Limit: 1.7% Upper Flammable/Explosive Limit: 12.5% Auto Ignition Temperature: 789°F

VOC Content: <50 g/L mixed.

9.2. Other information:

Percent Solids by Weight Not determined.

## SECTION 10: STABILITY and REACTIVITY

Chemical Stability:

Chemical Stability: Unstable.

Possibility of hazardous reactions:

Hazardous Polymerization: Polymerization may occur under certain conditions.

Conditions To Avoid:

Conditions to Avoid: Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions.

Oxygen-free atmospheres or inert gas blanketing. Freezing conditions. Material can soften paint and

**Incompatible Materials:** 

Incompatible Materials: Oxidizing agents (eg peroxides, nitrates), reducing agents, acids, bases, azo-compounds, catalytic

metals (eg copper, iron), halogens. Free radical initiators. Oxygen scavengers.

## SECTION 11: TOXICOLOGICAL INFORMATION

# TOXICOLOGICAL INFORMATION:

## Methyl Methacrylate Monomer:

Administration into the eye - Rabbit Standard Draize test: 150 mg [Not reported.] (RTECS)

Skin: Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: >5 gm/kg [Skin and Appendages - Dermatitis, other(After systemic exposure) ] (RTECS)

Inhalation: Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: 78000 mg/m3/4H [Details of toxic effects

not reported other than lethal dose value] (RTECS)

Oral - Rat LD50 - Lethal dose, 50 percent kill: 7872 mg/kg [Behavioral - Muscle weakness Behavioral - Coma Lungs, Thorax, or Respiration - Respiratory depression] (RTECS) Ingestion:

Methacrylic acid:

Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 500 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

Oral - Rat LD50 - Lethal dose, 50 percent kill: 1060 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS) Ingestion:

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

#### SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste:

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous

waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

guidelines.

RCRA Number: D001

Important Disposal Information: DANGER! Rags, steel wool and waste soaked with this product may spontaneously catch fire if improperly

discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container.

#### SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Refer to Bill of Lading

DOT UN Number: Refer to Bill of Lading

IATA Shipping Name: Refer to Bill of Lading IATA UN Number: Refer to Bill of Lading

IMDG UN Number: Refer to Bill of Lading IMDG Shipping Name: Refer to Bill of Lading

## SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

2-Propenoic acid, 2-methyl-, polymer with 2-chloro-1,3-butadiene:

TSCA Inventory Status: Listed Canada DSL:

Methyl Methacrylate Monomer:

TSCA Inventory Status: Listed

Section 313: EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

Canada DSL: Listed

Methacrylic acid:

TSCA Inventory Status: Listed Canada DSL: Listed

WHMIS Hazard Class(es): B2; D2B Canadian Regulations.

All components of this product are on the Canadian Domestic Substances List.

WHMIS Pictograms:





## SECTION 16: ADDITIONAL INFORMATION

# **HMIS Ratings**:

HMIS Health Hazard: HMIS Fire Hazard: 3 HMIS Reactivity: HMIS Personal Protection:

Health Hazard	2*
Fire Hazard	3
Reactivity	2
Personal Protection	х

<sup>\*</sup> Chronic Health Effects

SDS Revision Date: May 25, 2015 SDS Revision Notes: GHS Update SDS Author: Actio Corporation

Disclaimer: This Health and Safety Information is correct to the best of our knowledge and belief at the date of its

This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment.

## Component B - SDS

#### SECTION 1: IDENTIFICATION

Product identifier used on the label:

Product Name: MA420 - AO420 EU BLACK ACTIVATOR

Other means of identification:

Recommended use of the chemical and restrictions on use:

Chemical manufacturer address and telephone number:

Manufacturer Name: ITW

30 Endicott Street Danvers, MA 01923 Address: General Phone Number: (978) 777-1100

Emergency phone number:

Emergency Phone Number: (800) 424-9300

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300

# SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

GHS Pictograms:



Signal Word: WARNING.

GHS Class: Organic peroxides. Type F.

Eye Irritation. Category 2. Skin Irritation. Category 2. Skin Sensitization. category 1.

Specific Target Organ Toxicity - STOT, Single Exposure SE. Category 3.

Hazard Statements: H242 - Heating may cause a fire. H319 - Causes serious eye irritation.

H315 - Causes skin irritation. H317 - May cause an allergic skin reaction.

H335 - May cause respiratory irritation

P210 - Keep away from heat/sparks/open flames/hotsurfaces. — No smoking. P234 - Keep only in original container. P235 - Keep cool. Precautionary Statements:

P240 - Ground/Bond container and receiving equipment. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area.

P271 - Ose only outdoors of in a well-verifiated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minuity fresent and easy to do. Continue rinsing.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P321 - Specific treatment (see ... on this label).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use dry chemical, carbon dioxide to extinguish small fires. Use water for

large fires.

P403 - Store in a well-ventilated place. P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up. P410 - Protect from sunlight.

P411 - Store at temperatures not exceeding ...°C/...°F. P420 - Store separately.

P501 - Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

Hazards not otherwise classified that have been identified during the classification process:

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Inhalation

Eye: Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may

cause lacrimation, conjunctivitis, corneal damage and permanent injury.

Skin: Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling. Allergic reactions are

possible.

May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.

Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects.

Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal

Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible

Signs/Symptoms: Overexposure can cause headaches, dizziness, nausea, and vomiting.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

Aggravation of Pre-Existing Conditions:

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixtures:

Chemical Name	CAS#	Ingredient Percent	EC Num.
Water	7732-18-5	1 - 10 by weight	
Styrene-ethylene/butylene-styrene block copolymer	66070-58-4	1 - 10 by weight	
Proprietary ingredient(s)	Trade Secret	20 - 30 by weight	
Benzoyl peroxide	94-36-0	20 - 30 by weight	202-327-6
Bisphenol A diglycidyl ether resin	25068-38-6	20 - 30 by weight	500-033-5
Diisodecyl adipate	27178-16-1	10 - 20 by weight	248-299-9
Dipropylene glycol dibenzoate	27138-31-4	1 - 10 by weight	248-258-5
Black iron oxide	1317-61-9	1 - 10 by weight	215-277-5

#### SECTION 4: FIRST AID MEASURES

#### Description of necessary measures:

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of Eye Contact:

the eyes by separating the eyelids with fingers. Get immediate medical attention.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give Ingestion:

anything by mouth to an unconscious person

### SECTION 5: FIRE FIGHTING MEASURES

#### Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media: Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.

Unsuitable extinguishing media: Water or foam may cause frothing.

Unusual Fire Hazards: Organic peroxides can decompose violently if heated strongly while confined. Sudden reaction and fire

may result if product is mixed with an oxidizing agent.

## $\underline{\hbox{Special protective equipment and precautions for fire-fighters:}}\\$

As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear. Protective Equipment:

Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to Fire Fighting Instructions:

minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Personal Precautions:  $\label{thm:condition} \mbox{Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.}$ 

Environmental precautions:

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

 $\underline{\text{Methods and materials for containment and cleaning up:}}$ 

Spill Cleanup Measures:

Absorb spill with inert material (e,g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective appropriate protection in Section 2 equipment as listed in Section 8.

Reference to other sections:

Other Precautions: Pump or shovel to storage/salvage vessels.

#### SECTION 7: HANDLING and STORAGE

Precautions for safe handling:

Handling: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.

Hygiene Practices: Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep Storage:

container tightly closed when not in use. Do not store in temperatures above 100 °F.

#### SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

#### **EXPOSURE GUIDELINES:**

#### Benzoyl peroxide:

Guideline ACGIH: TLV-TWA: 5 mg/m3 Guideline OSHA: PEL-TWA: 5 mg/m3

#### Appropriate engineering controls:

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other

engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

#### Individual protection measures:

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye

and face protection regulation, or the European standard EN 166.

Skin Protection Description: Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult

manufacturer's data for permeability data.

A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed Respiratory Protection:

exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower

safety station.

Notes: Only established PEL and TLV values for the ingredients are listed.

# SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

#### PHYSICAL AND CHEMICAL PROPERTIES:

Physical State Appearance: Viscous. Liquid.

Color: Natural Odor: Slight. odor. Boiling Point: Not determined. Melting Point: Not determined.

Specific Gravity: 1.25

Solubility: slightly soluble. Vapor Density: Not determined. Vapor Pressure: Not determined. Percent Volatile: Not determined.

<<1 (butyl acetate = 1) Evaporation Rate:

pH: Neutral. Molecular Formula: Mixture Molecular Weight: Mixture

Lower Flammable/Explosive Limit: Not determined. Upper Flammable/Explosive Limit: Not determined. Auto Ignition Temperature: Not determined. VOC Content: <50 g/L mixed.

#### 9.2. Other information:

Percent Solids by Weight Not determined.

### SECTION 10: STABILITY and REACTIVITY

Chemical Stability:

Chemical Stability: Unstable.

Possibility of hazardous reactions:

Hazardous Polymerization: Not reported.

Conditions To Avoid:

Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Contamination, direct sunlight, friction and prolonged storage above 100°F (38°C). Conditions to Avoid:

Incompatible Materials:

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

#### SECTION 11: TOXICOLOGICAL INFORMATION

#### TOXICOLOGICAL INFORMATION:

#### Benzoyl peroxide:

Administration into the eye - Rabbit Standard Draize test: 500 mg/24H [Mild] (RTECS)

Ingestion:

Oral - Rat LD50 - Lethal dose, 50 percent kill: 7710 mg/kg [Lungs, Thorax, or Respiration - Cyanosis Liver - Other changes Kidney/Ureter/Bladder - Other changes in urine composition]
Oral - Rat LD50 - Lethal dose, 50 percent kill: 6400 mg/kg [Details of toxic effects not reported other

than lethal dose value] (RTECS)

#### Bisphenol A diglycidyl ether resin:

Administration into the eye - Rabbit Standard Draize test: 100 mg [Mild]
Administration into the eye - Rabbit Standard Draize test: 20 mg/24H [Moderate]
Administration into the eye - Rabbit Standard Draize test: 5 mg/24H [Severe] (RTECS)

Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: >20 mL/kg [Details of toxic

effects not reported other than lethal dose value1

Administration onto the skin - Rat LD50 - Lethal dose, 50 percent kill: >1200 mg/kg [Details of toxic

effects not reported other than lethal dose value] (RTECS)

Oral - Rat LD50 - Lethal dose, 50 percent kill: 10700 uL/kg [Details of toxic effects not reported other Ingestion:

than lethal dose value]
Oral - Rat LD50 - Lethal dose, 50 percent kill: 13600 mg/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Nutritional and Gross Metabolic - Weight loss or decreased weight gain]

Oral - Rat LD50 - Lethal dose, 50 percent kill: 13.6 gm/kg [Details of toxic effects not reported other

Oral - Rat LD50 - Lethal dose, 50 percent kill: 11.4 gm/kg [Details of toxic effects not reported other

than lethal dose value]

Oral - Rat LD50 - Lethal dose, 50 percent kill: 30 gm/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Nutritional and Gross Metabolic - Weight loss or

decreased weight gain]
Oral - Rat LD50 - Lethal dose, 50 percent kill: 30 gm/kg [Details of toxic effects not reported other than lethal dose value]

Oral - Rat LD50 - Lethal dose, 50 percent kill: >1 gm/kg [Details of toxic effects not reported other

Oral - Rat LD50 - Lethal dose, 50 percent kill: 51 gillykg [Betails of toxic effects not reported offer than lethal dose value]
Oral - Rat LD50 - Lethal dose, 50 percent kill: 11400 mg/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Nutritional and Gross Metabolic (RTECS)

Diisodecyl adipate:

Ingestion: Oral - Rat LD50 - Lethal dose, 50 percent kill: 20.5 gm/kg [Details of toxic effects not reported other

than lethal dose value] (RTECS)

Dipropylene glycol dibenzoate:

Administration onto the skin - Rat LD50 - Lethal dose, 50 percent kill: >2000 mg/kg [Details of toxic Skin:

effects not reported other than lethal dose value] (RTECS)

Oral - Rat LD50 - Lethal dose, 50 percent kill: 3295 mg/kg [Brain and Coverings - Other degenerative changes Cardiac - Cardiomyopathy including infarction Liver - Other changes] (RTECS) Ingestion:

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: No ecotoxicity data was found for the product. No environmental information found for this product. Environmental Fate:

# SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste:

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

#### SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Refer to Bill of Lading
DOT UN Number: Refer to Bill of Lading

IATA Shipping Name: Refer to Bill of Lading
IATA UN Number: Refer to Bill of Lading

IMDG UN Number: Refer to Bill of Lading

IMDG Shipping Name: Refer to Bill of Lading

## SECTION 15: REGULATORY INFORMATION

# Safety, health and environmental regulations specific for the product:

#### Styrene-ethylene/butylene-styrene block copolymer:

TSCA Inventory Status: Listed

Canada DSL: Listed

Benzoyl peroxide:

TSCA Inventory Status: Listed

Section 313: EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

Canada DSL: Listed
EC Number: 202-327-6

Bisphenol A diglycidyl ether resin:

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 500-033-5

<u>Diisodecyl adipate</u>:

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 248-299-9

 $\underline{ \ \, \text{Dipropylene glycol dibenzoate}}:$ 

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 248-258-5

Black iron oxide:

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 215-277-5

Canadian Regulations. WHMIS Hazard Class(es): D2B

All components of this product are on the Canadian Domestic Substances List.

WHMIS Pictograms:



# SECTION 16: ADDITIONAL INFORMATION

### **HMIS Ratings**:

Disclaimer:

HMIS Health Hazard: 2\*
HMIS Fire Hazard: 2
HMIS Reactivity: 2
HMIS Personal Protection: X

Health Hazard	2*
Fire Hazard	2
Reactivity	2
Personal Protection	х

<sup>\*</sup> Chronic Health Effects

SDS Creation Date: January 13, 2016
SDS Revision Date: January 27, 2016
SDS Revision Notes: GHS Update
SDS Author: Actio Corporation

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. ITW Polymers Adhesives, NA, MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT

LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the ITW Polymers Adhesives, NA product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a ITW Polymers Adhesives, NA product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the ITW Polymers Adhesives, NA product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. ITW Polymers Adhesives, NA provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, ITW Polymers Adhesives, NA makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from ITW Polymers Adhesives, NA

 $\label{lem:copyright} \textbf{Copyright} \\ \textcircled{\onotation. All Rights Reserved.}$ 

MA420 (AO420) BLACK Stock No. 35701 Revision:: 1/13/2015