



# SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

**Product name: DOWSIL™ 96-083 Curing Agent**

**Issue Date: 12/20/2023**

**Print Date: 12/21/2023**

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

---

## 1. IDENTIFICATION

---

**Product name:** DOWSIL™ 96-083 Curing Agent

**Recommended use of the chemical and restrictions on use**

**Identified uses:** Vulcanising agents

### COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY  
2211 H.H. DOW WAY  
MIDLAND MI 48674  
UNITED STATES

**Customer Information Number:**

800-258-2436  
SDSQuestion@dow.com

### EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** CHEMTREC +1 800-424-9300

**Local Emergency Contact:** 800-424-9300

---

## 2. HAZARDS IDENTIFICATION

---

### Hazard classification

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Reproductive toxicity - Category 1B

### Label elements

**Hazard pictograms**



Signal word: **DANGER!**

**Hazards**

May damage fertility or the unborn child.

**Precautionary statements****Prevention**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

Keep only in original container.

Wear protective gloves, protective clothing, eye protection and/or face protection.

**Response**

IF exposed or concerned: Get medical advice/ attention.

**Storage**

Store in a well-ventilated place.

Store locked up.

**Disposal**

Dispose of contents and/or container to an approved waste disposal plant.

**Other hazards**

May generate flammable hydrogen gas. Avoid contact with water, alcohols, acidic, basic, or oxidizing materials.

---

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

**Chemical nature:** Silicone

This product is a mixture.

Component	CASRN	Concentration
Dimethylvinylated and trimethylated silica	68988-89-6	>= 14.57 - <= 19.38 %
Methylvinylcyclsiloxane	2554-06-5	>= 2.88 - <= 9.0 %
Ethylbenzene	100-41-4	>= 0.0799 - <= 0.1311 %

---

### 4. FIRST AID MEASURES

---

**Description of first aid measures****General advice:**

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air and keep comfortable for breathing; consult a physician.

**Skin contact:** Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

**Eye contact:** Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

**Ingestion:** No emergency medical treatment necessary. Rinse mouth with water.

**Most important symptoms and effects, both acute and delayed:**

May damage fertility or the unborn child.

**Indication of any immediate medical attention and special treatment needed**

**Notes to physician:** No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

---

## **5. FIREFIGHTING MEASURES**

---

### **Extinguishing media**

**Suitable extinguishing media:** Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Water spray.

**Unsuitable extinguishing media:** Dry chemical.

### **Special hazards arising from the substance or mixture**

**Hazardous combustion products:** Silicon oxides. Carbon oxides. Formaldehyde.

**Unusual Fire and Explosion Hazards:** Applying foam will release significant amounts of hydrogen gas that can be trapped under the foam blanket.. Exposure to combustion products may be a hazard to health.. Fire burns more vigorously than would be expected..

### **Advice for firefighters**

**Fire Fighting Procedures:** Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Do not allow extinguishing medium to contact container contents. Most fire extinguishing media will cause hydrogen evolution, and once the fire is put out, may accumulate in poorly ventilated or confined areas and result in flash fire or explosion if ignited. Remove undamaged containers from fire area if it is safe to do so.

**Special protective equipment for firefighters:** In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

---

## **6. ACCIDENTAL RELEASE MEASURES**

---

**Personal precautions, protective equipment and emergency procedures:** Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

**Environmental precautions:** Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

**Methods and materials for containment and cleaning up:** Soak up with inert absorbent material. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Materials in contact with water, moisture, acids or bases have the potential to generate hydrogen gas. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Recovered material should be stored in a vented container. The vent must prevent the ingress of water as further reaction with spilled materials can take place which could lead to overpressurization of the container. See sections: 7, 8, 11, 12 and 13.

---

## 7. HANDLING AND STORAGE

---

**Precautions for safe handling:** Do not get on skin or clothing. Do not breathe vapours or spray mist. Avoid contact with eyes. Do not swallow. Keep container tightly closed. Keep away from water. Protect from moisture. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied. Use with local exhaust ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

**Conditions for safe storage:** Keep in properly labelled containers. Store in original container. Store locked up. Keep tightly closed. Product may evolve minute quantities of flammable hydrogen gas which can accumulate. Adequately ventilate to maintain vapors well below flammability limits and exposure guidelines. Do not repackage. Clogged container vents may increase pressure build up. Store in accordance with the particular national regulations. Store in a closed container.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Explosives. Gases.

Unsuitable materials for containers: Do not store in or use containers except the original product package.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Dimethylvinylated and trimethylated silica	OSHA Z-3	TWA	20 million particles per cubic foot
	Further information: a: Based on impinger samples counted by light-field techniques.; mppcf X 35.3 = million particles per cubic meter = particles per c.c		
	OSHA Z-3	TWA Dust	20 Million particles per cubic foot, Silica

	OSHA Z-3	TWA Dust	80 mg/m3 / %SiO <sub>2</sub> , Silica
Ethylbenzene	ACGIH	TWA	20 ppm
	Further information: Ototoxicant; A3: Confirmed animal carcinogen with unknown relevance to humans		
	OSHA Z-1	TWA	435 mg/m3 100 ppm

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

**Exposure controls**

**Engineering controls:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

**Individual protection measures**

**Eye/face protection:** Use safety glasses (with side shields).

**Skin protection**

**Hand protection:** Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

---

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

**Appearance**

<b>Physical state</b>	liquid
<b>Color</b>	colourless
<b>Odor</b>	slight
<b>Odor Threshold</b>	No data available
<b>pH</b>	Not applicable, substance/mixture is non-soluble (in water)
<b>Melting point/range</b>	No data available
<b>Freezing point</b>	No data available
<b>Boiling point (760 mmHg)</b>	150 °C ( 302 °F)
<b>Flash point</b>	<b>Pensky-Martens closed cup</b> 121.1 °C ( 250.0 °F)
<b>Evaporation Rate (Butyl Acetate = 1)</b>	No data available
<b>Flammability (solid, gas)</b>	Not applicable
<b>Flammability (liquids)</b>	Not applicable
<b>Lower explosion limit</b>	No data available
<b>Upper explosion limit</b>	No data available
<b>Vapor Pressure</b>	No data available
<b>Relative Vapor Density (air = 1)</b>	No data available
<b>Relative Density (water = 1)</b>	1.08
<b>Water solubility</b>	insoluble
<b>Partition coefficient: n-octanol/water</b>	No data available
<b>Auto-ignition temperature</b>	No data available
<b>Decomposition temperature</b>	No data available
<b>Kinematic Viscosity</b>	5 cSt at 25 °C (77 °F)
<b>Explosive properties</b>	Not explosive
<b>Oxidizing properties</b>	The substance or mixture is not classified as oxidizing.
<b>Molecular weight</b>	No data available
<b>Particle size</b>	Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** Not classified as a reactivity hazard.

**Chemical stability:** Stable under normal conditions.

**Possibility of hazardous reactions:** Can react with strong oxidizing agents. When heated to temperatures above 180 °C (356 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required. Product may evolve flammable hydrogen gas on contact

with water, alcohols, acidic or basic materials, many metals or metallic compounds and can form explosive mixtures in air. Hazardous decomposition products will be formed at elevated temperatures.

**Conditions to avoid:** Exposure to moisture

**Incompatible materials:** Avoid contact with oxidizing materials.

**Hazardous decomposition products:**

Decomposition products can include and are not limited to: Formaldehyde.

---

## **11. TOXICOLOGICAL INFORMATION**

---

*Toxicological information appears in this section when such data are available.*

**Information on likely routes of exposure**

Inhalation, Eye contact, Skin contact, Ingestion.

**Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)**

**Acute Toxicity Endpoints:**

Not classified based on available information.

**Acute oral toxicity**

**Information for the Product:**

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, Rat, > 5,000 mg/kg Estimated.

**Information for components:**

**Dimethylvinylated and trimethylated silica**

For similar material(s): LD50, Rat, > 5,000 mg/kg

**Methylvinylcyclosiloxane**

LD50, Rat, > 15,000 mg/kg

**Ethylbenzene**

LD50, Rat, 3,500 mg/kg

**Acute dermal toxicity**

**Information for the Product:**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):  
LD50, Rabbit, > 2,000 mg/kg Estimated.

**Information for components:**

**Dimethylvinylated and trimethylated silica**

For similar material(s): LD50, Rabbit, > 2,000 mg/kg Estimated.

**Methylvinylcyclosiloxane**

The dermal LD50 has not been determined.

Based on testing for product(s) in this family of materials: LD50, > 2,000 mg/kg  
Estimated.

**Ethylbenzene**

LD50, Rabbit, 15,500 mg/kg

**Acute inhalation toxicity**

**Information for the Product:**

Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.

As product: The LC50 has not been determined.

**Information for components:**

**Dimethylvinylated and trimethylated silica**

For similar material(s): Maximum attainable concentration. LC50, Rat, 4 Hour, dust/mist, > 2.08 mg/l OECD Test Guideline 403 No deaths occurred at this concentration.

**Methylvinylcyclosiloxane**

LC50, Rat, male and female, 4 Hour, vapour, > 1.32 mg/l No deaths occurred at this concentration.

**Ethylbenzene**

LC50, Rat, 4 Hour, vapour, 17.2 mg/l

**Skin corrosion/irritation**

Not classified based on available information.

**Information for the Product:**

Based on information for component(s):  
Brief contact may cause slight skin irritation with local redness.  
May cause drying and flaking of the skin.

**Information for components:**

**Dimethylvinylated and trimethylated silica**



For similar material(s):  
Brief contact is essentially nonirritating to skin.  
May cause skin irritation due to mechanical abrasion.  
May cause drying and flaking of the skin.

**Methylvinylcyclosiloxane**

Brief contact may cause slight skin irritation with local redness.

**Ethylbenzene**

Brief contact may cause moderate skin irritation with local redness.  
Prolonged contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.  
May cause drying and flaking of the skin.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Information for the Product:**

Based on information for component(s):  
May cause slight eye irritation.

**Information for components:**

**Dimethylvinylated and trimethylated silica**

Solid or dust may cause irritation or corneal injury due to mechanical action.

**Methylvinylcyclosiloxane**

May cause slight eye irritation.

**Ethylbenzene**

May cause moderate eye irritation.  
Vapor may cause lacrimation (tears).

**Sensitization**

**For skin sensitization:**

Not classified based on available information.

**For respiratory sensitization:**

Not classified based on available information.

**Information for the Product:**

For skin sensitization:  
Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Information for components:**

**Dimethylvinylated and trimethylated silica**

For skin sensitization:  
No relevant data found.

For respiratory sensitization:  
No relevant data found.

**Methylvinylcyclosiloxane**

For skin sensitization:  
No relevant data found.

For respiratory sensitization:  
No relevant data found.

**Ethylbenzene**

Did not cause allergic skin reactions when tested in humans.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Not classified based on available information.

**Information for the Product:**

Product test data not available.

**Information for components:**

**Dimethylvinylated and trimethylated silica**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Methylvinylcyclosiloxane**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Ethylbenzene**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Aspiration Hazard**

Not classified based on available information.

**Information for the Product:**

Based on available information, aspiration hazard could not be determined.

**Information for components:**

**Dimethylvinylated and trimethylated silica**

Based on physical properties, not likely to be an aspiration hazard.

**Methylvinylcyclosiloxane**

Based on available information, aspiration hazard could not be determined.

**Ethylbenzene**

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia. May be fatal if swallowed and enters airways.

**Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)**

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Not classified based on available information.

**Information for the Product:**

Product test data not available.

**Information for components:**

**Dimethylvinylated and trimethylated silica**

For similar material(s):

Repeated exposures to dusts of this material are not anticipated to result in systemic toxicity or permanent lung injury; however, excessive exposures may cause less severe respiratory effects.

**Methylvinylcyclosiloxane**

No relevant data found.

**Ethylbenzene**

In animals, effects have been reported on the following organs:

May cause hearing loss based on animal data.

Kidney.

Liver.

Lung.

Although one early inhalation study on ethylbenzene reported an adverse effect on the testes, recent, more comprehensive studies have not shown this effect.

**Carcinogenicity**

Not classified based on available information.

**Information for the Product:**

Product test data not available.

**Information for components:**

**Dimethylvinylated and trimethylated silica**

For similar material(s): Did not cause cancer in laboratory animals.

**Methylvinylcyclosiloxane**

No relevant data found.

**Ethylbenzene**

Ethylbenzene has been shown to cause cancer in laboratory animals. There is no evidence that these findings are relevant to humans.

**Carcinogenicity**

<b>Component</b>	<b>List</b>	<b>Classification</b>
<b>Ethylbenzene</b>	IARC	Group 2B: Possibly carcinogenic to humans
	ACGIH	A3: Confirmed animal carcinogen with unknown relevance to humans.

**Teratogenicity**

May damage fertility or the unborn child.

**Information for the Product:**

Product test data not available.

**Information for components:**

**Dimethylvinylated and trimethylated silica**

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

**Methylvinylcyclosiloxane**

Has been toxic to the fetus in lab animals at doses nontoxic to the mother.

**Ethylbenzene**

Has caused birth defects in laboratory animals only at doses toxic to the mother. Has been toxic to the fetus in lab animals at doses nontoxic to the mother.

**Reproductive toxicity**

May damage fertility or the unborn child.

**Information for the Product:**

Product test data not available.

**Information for components:**

**Dimethylvinylated and trimethylated silica**

No relevant data found.

**Methylvinylcyclosiloxane**

In animal studies, has been shown to interfere with fertility.

**Ethylbenzene**

In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.

**Mutagenicity**

Not classified based on available information.

**Information for the Product:**

Product test data not available.

**Information for components:**

**Dimethylvinylated and trimethylated silica**

For similar material(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Methylvinylcyclosiloxane**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Ethylbenzene**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

---

---

## 12. ECOLOGICAL INFORMATION

---

*Ecotoxicological information appears in this section when such data are available.*

**Toxicity**

**Dimethylvinylated and trimethylated silica**

**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

For similar material(s):

LC50, Danio rerio (zebra fish), 96 Hour, 5,000 - 10,000 mg/l

**Acute toxicity to aquatic invertebrates**

For similar material(s):

EC50, Daphnia magna (Water flea), 24 Hour, > 1,000 mg/l

**Acute toxicity to algae/aquatic plants**

For similar material(s):

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Biomass, 440 mg/l

**Methylvinylcyclosiloxane**

**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Cyprinodon variegatus (sheepshead minnow), 96 Hour, > 1,000 mg/l

**Acute toxicity to aquatic invertebrates**

EL50, Acartia tonsa, 48 Hour, 221 mg/l, ISO 14669 and PARCOM method

**Acute toxicity to algae/aquatic plants**

ErC50, Skeletonema sp., 72 Hour, > 988 mg/l, ISO 10253

**Ethylbenzene**

**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 4.2 mg/l, OECD Test Guideline 203 or Equivalent

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), Static, 48 Hour, 1.8 - 2.4 mg/l

**Acute toxicity to algae/aquatic plants**

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth inhibition (cell density reduction), 3.6 - 4.6 mg/l, OECD Test Guideline 201 or Equivalent

**Toxicity to bacteria**

EC50, Bacteria, 16 Hour, > 12 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, Ceriodaphnia dubia (water flea), semi-static test, 7 d, 0.96 mg/l

**Toxicity to soil-dwelling organisms**

LC50, Eisenia fetida (earthworms), 2 d, survival, 0.047 mg/cm<sup>2</sup>

**Persistence and degradability**

**Dimethylvinylated and trimethylated silica**

**Biodegradability:** Biodegradation is not applicable.

**Methylvinylcyclosiloxane**

**Biodegradability:** For similar material(s): Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Fail

**Biodegradation:** 3.7 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 310

**Ethylbenzene**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

**Biodegradation:** 100 %

**Exposure time:** 6 d

**Method:** OECD Test Guideline 301E or Equivalent

**Theoretical Oxygen Demand:** 3.17 mg/mg Estimated.

**Chemical Oxygen Demand:** 2.62 mg/mg Dichromate

**Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	31.5 %
10 d	38.5 %
20 d	45.4 %

**Photodegradation**

**Sensitization:** OH radicals  
**Atmospheric half-life:** 55 Hour  
**Method:** Estimated.

#### Bioaccumulative potential

##### Dimethylvinylated and trimethylated silica

**Bioaccumulation:** Partitioning from water to n-octanol is not applicable.

##### Methylvinylcyclosiloxane

**Bioaccumulation:** Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

**Partition coefficient: n-octanol/water(log Pow):** 6.49

##### Ethylbenzene

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 3.15 Measured

**Bioconcentration factor (BCF):** 15 Fish Measured

#### Mobility in soil

##### Dimethylvinylated and trimethylated silica

No relevant data found.

##### Methylvinylcyclosiloxane

No relevant data found.

##### Ethylbenzene

**Partition coefficient (Koc):** 518 Estimated.

---

## 13. DISPOSAL CONSIDERATIONS

---

**Disposal methods:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN SDS SECTION 1: Identified Uses. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

**Treatment and disposal methods of used packaging:** Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility of the waste generator. Do not re-use containers for any purpose.

---

**14. TRANSPORT INFORMATION**

---

**DOT**

<b>Proper shipping name</b>	Environmentally hazardous substance, liquid, n.o.s.(Xylene)
<b>UN number</b>	UN 3082
<b>Class</b>	9
<b>Packing group</b>	III
<b>Reportable Quantity</b>	Xylene

**Classification for SEA transport (IMO-IMDG):**

	Not regulated for transport
<b>Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code</b>	Consult IMO regulations before transporting ocean bulk

**Classification for AIR transport (IATA/ICAO):**

Not regulated for transport

**Further information:**

VENTED PACKAGES ARE FORBIDDEN FOR AIR TRANSPORT.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

**15. REGULATORY INFORMATION**

---

**Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312**

Reproductive toxicity

**Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313**

The following components are subject to reporting levels established by SARA Title III, Section 313:

<b>Components</b>	<b>CASRN</b>
Ethylbenzene	100-41-4

**Pennsylvania Right To Know**

The following chemicals are listed because of the additional requirements of Pennsylvania law:



**Components**

Siloxanes and Silicones, Me hydrogen  
 Dimethyl Siloxane, Dimethylvinylsiloxy-terminated  
 Dimethylvinylated and trimethylated silica  
 Methylvinylcyclosiloxane

**CASRN**

63148-57-2  
 68083-19-2  
 68988-89-6  
 2554-06-5

**California Prop. 65**

WARNING: This product can expose you to chemicals including Ethylbenzene, which is/are known to the State of California to cause cancer, and Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**United States TSCA Inventory (TSCA)**

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**16. OTHER INFORMATION****Hazard Rating System****NFPA**

Health	Flammability	Instability
0	1	0

**HMIS**

Health	Flammability	Physical Hazard
0*	1	1

\* = Chronic Effects (See Hazards Identification)

**Revision**

Identification Number: 4060672 / A001 / Issue Date: 12/20/2023 / Version: 9.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

**Legend**

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
TWA	8-hour, time-weighted average

**Full text of other abbreviations**

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half

maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### **Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US