



SAFETY DATA SHEET

In accordance with OSHA 29 CFR 1910.1200

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016

1. Identification

1.1. Product identifier

Product Name 70-03A FLAME RETARDANT WHITE

Other means of identification

Other information Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives and/or sealants

Restrictions on use No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1(800) 726-7845 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)

E-mail msds@bostik.com

1.4. Emergency telephone number

Emergency Telephone CHEMTREC (Chemical Transportation Emergency Center)
Chemtrec: 1-800-424-9300 (US) , 1-703-527-3887 (Outside U.S.)
Rocky Mountain Poison Center: 1-866-767-5089

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Reproductive toxicity	Category 1B

Hazards not otherwise classified (HNOC)

Not applicable

2.2. Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes serious eye irritation
May cause an allergic skin reaction
May damage fertility or the unborn child

SAFETY DATA SHEET

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016



Appearance Paste

Physical state Liquid

Odor Musty

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing must not be allowed out of the workplace

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN: Wash with plenty of water and soap
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3. Other Information

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

3. Composition/information on ingredients

3.1. Substances

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%
Ammonium polyphosphate	68333-79-9	10 - 30
Carbonic acid, calcium salt (1:1)	471-34-1	5 - <10
Trimethoxyvinylsilane	2768-02-7	1 - <5
Titanium dioxide	13463-67-7	1 - <5
1-Propanamine, 3-(trimethoxysilyl)-	13822-56-5	0.1 - <1
Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-	22673-19-4	0.1 - <1
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	0.1 - <1

**The exact percentage (concentration) of composition has been withheld as a trade secret*

SAFETY DATA SHEET

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016

4. First-aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Ingestion	Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Small amounts of toxic methanol are released by hydrolysis. Call a physician immediately.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause redness and tearing of the eyes. May cause allergic skin reaction. Itching. Rashes. Hives. Erythema (skin redness).
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.
--------------------	--

5. Fire-Fighting Measures

5.1. Extinguishing media

Suitable Extinguishing Media Large Fire	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam. CAUTION: Use of water spray when fighting fire may be inefficient.
--	---

Unsuitable extinguishing media	Full water jet.
--------------------------------	-----------------

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.
Hazardous combustion products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO ₂). Silicon dioxide.
Explosion data	
Sensitivity to mechanical impact	None.

SAFETY DATA SHEET

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016

Sensitivity to static discharge None.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Do not touch or walk through spilled material. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling.

Other information Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Use personal protective equipment as required. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly.

Reference to other sections See section 8 for more information. See section 13 for more information.

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Protect from moisture. Keep away from food, drink and animal feeding stuffs.

Recommended storage temperature Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

7.3 References to other sections

Reference to other sections Section 10: STABILITY AND REACTIVITY
Section 13: DISPOSAL CONSIDERATIONS

SAFETY DATA SHEET

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016

8. Exposure Controls/Personal Protection

8.1. Control parameters

Exposure Limits

This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Carbonic acid, calcium salt (1:1) 471-34-1	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Titanium dioxide 13463-67-7	TWA: 0.2 mg/m ³ nanoscale respirable particulate matter TWA: 2.5 mg/m ³ finescale respirable particulate matter	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
Tin, dibutylbis(2,4-pentanedionato-O ,O')-, (OC-6-11)- 22673-19-4	TWA: 0.1 mg/m ³ Sn STEL: 0.2 mg/m ³ Sn Sk*	TWA: 0.1 mg/m ³ Sn (vacated) TWA: 0.1 mg/m ³ Sn (vacated) S*	IDLH: 25 mg/m ³ Sn TWA: 0.1 mg/m ³ except Cyhexatin Sn

Chemical name	Argentina	Brazil	S.D. 594/1999	Colombia
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 0.2 mg/m ³ TWA: 2.5 mg/m ³	-	TWA: 0.2mg/m ³ TWA: 2.5mg/m ³
Tin, dibutylbis(2,4-pentanedionato-O ,O')-, (OC-6-11)- 22673-19-4	TWA: 0.1 mg/m ³ STEL: 0.2 mg/m ³ Sk*	TWA: 0.1 mg/m ³ STEL: 0.2 mg/m ³	LPP: 0.09 mg/m ³ Sk*	STEL: 0.2mg/m ³ TWA: 0.1mg/m ³

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Carbonic acid, calcium salt (1:1) 471-34-1	-	TWA: 10mg/m ³	-	TWA: 10 mg/m ³
Titanium dioxide 13463-67-7	TWA: 10mg/m ³	TWA: 10mg/m ³	0.2 mg/m ³ TWA (nanoscale, respirable particulate matter); 2.5 mg/m ³ TWA (finescale, respirable particulate matter)	TWA: 10 mg/m ³
Tin, dibutylbis(2,4-pentanedionato-O ,O')-, (OC-6-11)- 22673-19-4	STEL: 0.2mg/m ³	STEL: 0.2mg/m ³ TWA: 0.1mg/m ³	0.2 mg/m ³ STEL (as Sn) 0.1 mg/m ³ TWA (as Sn)	Skin STEL: 0.2 mg/m ³ TWA: 0.1 mg/m ³

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Methyl alcohol 67-56-1	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³

SAFETY DATA SHEET

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016

Chemical name	Argentina	Brazil	S.D. 594/1999	Colombia
Methyl alcohol 67-56-1	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 156 ppm TWA: 200 mg/m ³ STEL: 250 ppm Skin	LPP: 175 ppm LPP: 229 mg/m ³ LPT: 250 ppm LPT: 328 mg/m ³ Sk*	STEL: 250ppm TWA: 200ppm

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Methyl alcohol 67-56-1	STEL: 250ppm TWA: 200ppm	STEL: 250ppm STEL: 328mg/m ³ TWA: 200ppm TWA: 262mg/m ³	250 ppm STEL 200 ppm TWA	Skin STEL: 250 ppm TWA: 200 ppm

8.2. Exposure controls

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes or clothing. Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Regular cleaning of equipment, work area and clothing is recommended.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Paste
Color White
Odor Musty
Odor threshold No information available

Property	Values	Remarks • Method
pH	No data available	None known

SAFETY DATA SHEET

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016

pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flash point	140 °C / 284 °F	None known
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	Reacts with water	Reacts with water
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

9.2. Other information

Explosive properties	No information available	
Oxidizing properties	No information available	
Solvent content (%)	No information available	
Solid content (%)	98.2	
Softening point	No information available	
Molecular weight	No information available	
VOC content	2.7 %	No information available
Density	1.364 g/ml	
Bulk density	No information available	

10. Stability and Reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

SAFETY DATA SHEET

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016

Hazardous decomposition products Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

11. Toxicological information

11.1. Information on toxicological effects

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	16,886.90 mg/kg
ATEmix (dermal)	85,084.50 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapor)	222.20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ammonium polyphosphate 68333-79-9	=4740 mg/kg (Rattus)	-	> 4.85 mg/L (Rat) 4 h
Carbonic acid, calcium salt (1:1) 471-34-1	LD50 > 2000 mg/kg (Rattus) OECD 420	LD50 >2000 mg/kg (Rattus) OECD 402	LC50 (4h) >3mg/ml (Rattus)
Trimethoxyvinylsilane 2768-02-7	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
1-Propanamine, 3-(trimethoxysilyl)- 13822-56-5	LD50 (Rattus) > 2000 mg/ kg (2,97 ml/kg) (OECD 401)	LD50 (Oryctolagus cuniculus) > 2000 mg/kg 11,3 ml/kg) OECD 402	-
Tin, dibutylbis(2,4-pentanedionato-O ,O')-, (OC-6-11)- 22673-19-4	LD50 = 1864 mg/kg (Rattus) OECD 401	LD50 > 2000 mg/kg (Rattus) OECD 402	LC50 4hr: 16.8 mg/l (Rattus) (OECD TG 403)

SAFETY DATA SHEET

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	LD50 (Rattus) > 2000 mg/kg OECD 423	LD50 (Rattus) > 3 170 mg/kg OECD 402	=500 mg/m ³ (Rattus) 4 h
---	--	---	-------------------------------------

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		72 hours	irritant

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			Eye Damage

Respiratory or skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

SAFETY DATA SHEET

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016

Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)- (22673-19-4)

Method	Species	Results
OECD Test No. 476: In Vitro Mammalian Cell Gene Mutation Tests using the Hprt and xprt genes	in vitro	Mutagenic

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Carcinogenicity This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	A3	Group 2B	-	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity

Classification based on data available for ingredients. Contains a known or suspected reproductive toxin. May damage fertility or the unborn child.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)- (22673-19-4)

Method	Species	Results
OECD Test No. 414: Prenatal Development Toxicity Study	Rat Oral in vivo	Read-across. Reproductive toxicant. NOAEL: 1 mg/kg bw/day
OECD Test No. 421: Reproduction/Developmental Toxicity Screening Test	Rat Oral in vivo	Read-across Reproductive toxicant NOAEL 1.9-2.3 mg/kg bw/day

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Results
OECD Test No. 414: Prenatal Development Toxicity Study	Rat, Rabbit	Reproductive toxicant

STOT - single exposure

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapor		90 days	0.058 NOAEL

SAFETY DATA SHEET

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016

Subchronic Inhalation Toxicity: 90-day Study					
---	--	--	--	--	--

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Target organ effects Respiratory system, Eyes, Skin, Lungs.

Aspiration hazard Based on available data, the classification criteria are not met.

Other adverse effects No information available.

Interactive effects No information available.

12. Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ammonium polyphosphate 68333-79-9	-	LC50: =123mg/L (96h, Oncorhynchus mykiss) LC50: 685 - 1066mg/L (96h, Oncorhynchus mykiss) LC50: 389 - 654mg/L (96h, Pimephales promelas) LC50: >500mg/L (96h, Brachydanio rerio)	-	-
Carbonic acid, calcium salt (1:1) 471-34-1	IC50 72H Algae >1000 mg/l	CL50 96H >1000 mg/l	-	EC50 48H Daphnia >1000 mg/l
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-
1-Propanamine, 3-(trimethoxysilyl)- 13822-56-5	EC50 (72h) > 1000 mg/l (Desmodesmus subspicatus) EU Method C.3 (Algal Inhibition test)	LC50 (96h) > >934 mg/L (Danio rerio) OECD 203	-	EC50 (48h) = 331 mg/L (Daphnia magna) OECD 202
Tin, dibutylbis(2,4-pentanedioato-O,O')-, (OC-6-11)- 22673-19-4	>2.0 mg/l	>2.0 mg/l	-	EC50 0.0036 mg/l 48Hr (Daphnia magna)
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	EC50 72Hr 0.705 mg/l (Pseudokirchnerella subcapitata)	LC50 (96h) = 5.29 mg/l (Oryzias latipes)	-	LC50 48Hr 8.58 mg/l (Daphnia magna)

12.2. Persistence and degradability

Persistence and degradability No information available.

SAFETY DATA SHEET

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Trimethoxyvinylsilane 2768-02-7	1.1
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	0.35

12.4. Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

13. Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

14. Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

DOT

UN number or ID number UN3077
Extended proper shipping name Environmentally hazardous substance, solid, n.o.s. (Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-, Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate)
Transport hazard class(es) 9
Packing group III
Special Provisions 8, 146, 335, 384, 441, A112, B54, B120, IB8, IP3, N20, N91, T1, TP33
DOT Marine Pollutant I
Marine pollutant Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-, Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate
Description UN3077, Environmentally hazardous substance, solid, n.o.s. (Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-, Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate), 9, III, Marine pollutant
Emergency Response Guide 171

SAFETY DATA SHEET

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016

Number

Note:

49 CFR 171.4(c) "Exceptions. Except when all or part of the transportation is by vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicle, rail car or aircraft."

IATA

UN number or ID number
UN proper shipping name

UN3077
Environmentally hazardous substance, solid, n.o.s. (Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-, Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate)

Transport hazard class(es)

9

Packing group

III

Special Provisions

A97, A158, A179, A197, A215

Description

UN3077, Environmentally hazardous substance, solid, n.o.s. (Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-, Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate), 9, III

IMDG

UN number or ID number
UN proper shipping name

UN3077
Environmentally hazardous substance, solid, n.o.s. (Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-, Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate)

Transport hazard class(es)

9

Packing group

III

EmS-No.

F-A, S-F

Special Provisions

274, 335, 966, 967, 969

IMDG Marine Pollutant Name

Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-, Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate

Description

UN3077, Environmentally hazardous substance, solid, n.o.s. (Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-, Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate), 9, III, Marine pollutant

15. Regulatory Information

International Inventories

TSCA	Complies
DSL	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Complies - The components of this product are either listed or exempt from listing on inventory. Active

Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

SAFETY DATA SHEET

70-03A FLAME RETARDANT WHITE
Revision Number 2

Revision date 05-Feb-2025
Supersedes date 29-Jun-2016

16. Other Information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT: Specific Target Organ Toxicity
ATE: Acute Toxicity Estimate
LC50: 50% Lethal Concentration
LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation

Prepared By Product Stewardship and Regulatory Affairs.

Revision date 05-Feb-2025

Revision Note SDS sections updated. 1. 2. 3. 4. 5. 6. 7. 8. 10. 11. 12. 13. 14. 15. 16.

Disclaimer

All information contained herein is believed to be accurate as of the date of publication, is provided "as-is" and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Bostik Inc. ("Company") expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user's application(s). **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN.** The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at <https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-management/medical-device-policy/> which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical devices to determine the suitability of all raw material, products and components, including any medical grade products, in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.

End of Safety Data Sheet