

**CA5013****Safety Data Sheet**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 09/24/2020

Version: 1.1

**SECTION 1: Identification****1.1. Identification**

Product form : Mixture  
Product name : CA5013

**1.2. Recommended use and restrictions on use**

Recommended use : Cyanoacrylate instant adhesive  
Restrictions on use : Product for industrial use only

**1.3. Supplier**

ResinLab, LLC  
N109 W13300 Ellsworth Drive  
Germantown, WI 53022 - United States  
T 1-877-259-1669  
[www.resinlab.com](http://www.resinlab.com)

**1.4. Emergency telephone number**

Emergency number : CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International)

**SECTION 2: Hazard(s) identification****2.1. Classification of the substance or mixture****GHS US classification**

Flammable liquids Category 4 H227 Combustible liquid  
Serious eye damage/eye irritation Category 2B H320 Causes eye irritation

Full text of H statements : see section 16

**2.2. GHS Label elements, including precautionary statements****GHS US labeling**

Signal word (GHS US) : Warning  
Hazard statements (GHS US) : H227 - Combustible liquid  
H320 - Causes eye irritation  
Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

**2.3. Other hazards which do not result in classification**

No additional information available

**2.4. Unknown acute toxicity (GHS US)**

Not applicable

**SECTION 3: Composition/Information on ingredients****3.1. Substances**

Not applicable

**3.2. Mixtures**

Name	Product identifier	%	GHS US classification
Beta-Methoxyethyl Cyanoacrylate	(CAS-No.) 27816-23-5	≥ 90	Flam. Liq. 4, H227 Eye Irrit. 2B, H320

# CA5013

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
1,4-dihydroxybenzene	(CAS-No.) 123-31-9	< 0.1	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms, call a doctor. Allow the victim to rest.
- First-aid measures after skin contact : Do not pull bonded skin apart. Use a blunt object such as a spoon to gently release the bonded skin. Soaking in warm soapy water will aid with the debonding. Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn. Burns should be treated normally after the adhesive has been removed from the skin. If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Immediately rinse with plenty of water (for at least 15 minutes). If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will help debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. In case of solid particles trapped behind eye, seek medical attention. Get medical advice/attention.
- First-aid measures after ingestion : Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Avoid swallowing solid adhesive after detachment.

#### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after eye contact : Mild eye irritation.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Specific hazards arising from the chemical

- Fire hazard : Combustible liquid.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
- Methods for cleaning up : Take up liquid spill into absorbent material. Flood area with water to polymerize and then scrape off of the floor. Do not allow the material to come in contact with cotton, wool, leather, fiberglass or carbon fiber. The reaction between cyanoacrylate and these materials results in a rapid exothermic reaction that can cause serious burns and release an irritating smoke.

# CA5013

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Avoid contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Do not return unused adhesive to original container. Do not refrigerate open containers.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Beta-Methoxyethyl Cyanoacrylate (27816-23-5)		
Not applicable		
1,4-dihydroxybenzene (123-31-9)		
ACGIH	Local name	Hydroquinone
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	TLV® Basis: Eye irr; eye dam. Notations: DSEN; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace.

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses with side shields

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



# CA5013

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: clear
Odor	: Odorless
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 74 – 76 °C
Flash point	: 80 – 93 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1.1 g/cm <sup>3</sup>
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
VOC content	No data available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Heat. No flames, no sparks. Eliminate all sources of ignition. Avoid contact with hot surfaces.

#### 10.5. Incompatible materials

Amines. alcohols. metals. Reducing agents. Oxidizing agent. Water.

#### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### 1,4-dihydroxybenzene (123-31-9)

LD50 oral rat	> 375 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))

# CA5013

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 1,4-dihydroxybenzene (123-31-9)

ATE US (oral)	500 mg/kg body weight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

### 1,4-dihydroxybenzene (123-31-9)

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after eye contact	: Mild eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. Harmful to aquatic life.
-------------------	---

### 1,4-dihydroxybenzene (123-31-9)

LC50 fish 1	0.638 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	0.061 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	0.33 mg/l (Equivalent or similar to OECD 201, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

### 12.2. Persistence and degradability

### 1,4-dihydroxybenzene (123-31-9)

Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.48 – 1.1 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.83 g O <sub>2</sub> /g substance
ThOD	1.89 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

### 1,4-dihydroxybenzene (123-31-9)

BCF fish 1	40 (72 h, Leuciscus idus, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	0.59 (Experimental value, 20 - 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

### 1,4-dihydroxybenzene (123-31-9)

Partition coefficient n-octanol/water (Log Koc)	1.585 (log Koc, SRC PCKOCWIN v2.0, Experimental value)
Ecology - soil	Highly mobile in soil.

### 12.5. Other adverse effects

No additional information available

# CA5013

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Transport document description : NA1993 Combustible liquid, n.o.s. (Beta-Methoxyethyl Cyanoacrylate), Comb Liq, III  
UN-No.(DOT) : NA1993  
Proper Shipping Name (DOT) : Combustible liquid, n.o.s.  
Beta-Methoxyethyl Cyanoacrylate  
Class (DOT) : Comb Liq - Combustible liquid  
Packing group (DOT) : III - Minor Danger  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203  
DOT Packaging Bulk (49 CFR 173.xxx) : 241  
DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name  
DOT Special Provisions (49 CFR 172.102) : 148 - Except for transportation by aircraft, when transported as a limited quantity or a consumer commodity, the maximum net capacity specified in §173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 150  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
Other information : No supplementary information available.

#### Transportation of Dangerous Goods

Not applicable

#### Transport by sea

Not regulated

#### Air transport

Transport document description (IATA) : UN 3334 Aviation regulated liquid, n.o.s. (Beta-Methoxyethyl Cyanoacrylate), 9, III  
UN-No. (IATA) : 3334  
Proper Shipping Name (IATA) : Aviation regulated liquid, n.o.s.  
Beta-Methoxyethyl Cyanoacrylate  
Class (IATA) : 9 - Miscellaneous Dangerous Goods  
Packing group (IATA) : III - Minor Danger

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

# CA5013

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

1,4-dihydroxybenzene	CAS-No. 123-31-9	< 0.1%
----------------------	------------------	--------

### Beta-Methoxyethyl Cyanoacrylate (27816-23-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

PMN - PMN - indicates a commenced PMN substance.

### 1,4-dihydroxybenzene (123-31-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ

100 lb

RQ (Reportable quantity, section 304 of EPA's List of Lists)

100 lb

SARA Section 302 Threshold Planning Quantity (TPQ)

10000 lb 500lb if the substance is solid in powder form with particle size less than 100 microns, or is in solution or molten form

## 15.2. International regulations

### CANADA

#### Beta-Methoxyethyl Cyanoacrylate (27816-23-5)

Listed on the Canadian DSL (Domestic Substances List)

#### 1,4-dihydroxybenzene (123-31-9)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

Contains no REACH candidate substance

### National regulations

No additional information available

## 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
1,4-dihydroxybenzene(123-31-9)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H227	Combustible liquid
H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H320	Causes eye irritation
H341	Suspected of causing genetic defects
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Indication of changes:

Section	Changed item	Change	Comments
---------	--------------	--------	----------

# CA5013

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3			Software not classifying main chemical per BIG and Annex IV DB. Force classified and then reissued SDS. There were no chemicals listed in composition but the mixture was classified so it didn't make sense. 9/24/2020
---	--	--	--

SDS US - ResinLab

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*