

Revision Number: 004.0 Issue date: 08/22/2014

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE IS 5100 4 GA EN/FR/ES

known as 5100 Flexseal Penetrating

Product type: Anaerobic
Restriction of Use: None identified

Company address: Henkel Corporation Henkel Way One

Rocky Hill, Connecticut 06067

IDH number: 233057

Item number: 28261
Region: United States

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

WARNING: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

HARMFUL IF INHALED.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY INHALATION	4
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1

## PICTOGRAM(S)



### **Precautionary Statements**

IDH number: 233057

Prevention: Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Use only outdoors or in

a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace.

Wear eye and face protection. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Call a poison control center or physician if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get

medical attention. Take off contaminated clothing.

Storage: Not prescribed

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

9 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Product name: LOCTITE IS 5100 4 GA EN/FR/ES known as 5100 Flexseal Penetrating Page 1 of 6

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Alkyl methacrylate	Proprietary	30 - 60	
Polyglycol dimethacrylate	Proprietary	10 - 30	
Acrylate	Proprietary	10 - 30	
Polyurethane Methacrylate Resin	Unknown	5 - 10	
Cumene hydroperoxide	80-15-9	1 - 5	
2-Hydroxyethyl methacrylate	868-77-9	1 - 5	
Cumene	98-82-8	0.1 - 1	

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Get medical attention. Wash clothing

before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

**Ingestion:** DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

#### 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

**Hazardous combustion products:** Oxides of carbon. Irritating organic vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to

prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure

Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed. Refer to Section 8.

Storage: For safe storage, store between 5 °C (41°F) and 30 °C (86°F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Alkyl methacrylate	None	None	None	None
Polyglycol dimethacrylate	None	None	None	None
Acrylate	None	None	None	None
Polyurethane Methacrylate Resin	None	None	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
2-Hydroxyethyl methacrylate	None	None	None	3 ppm Ceiling
50 ppm (245 mg/m3) Cumene 50 ppm TWA PEL (SKIN)		None	None	

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Clear, to, Pale yellow

Odor: Mild

Odor threshold: Not available. PH: Not applicable

Vapor pressure: <5 mm hg (80 °F (26.7 °C))

Boiling point/range: > 300 °F (> 148.9 °C)

Melting point/ range: Not available.

Specific gravity: 0.998 at 80 °F (26.67 °C)

Vapor density: 0.998

Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Solubility of the state of the

VOC content:
Viscosity:

Not available.

Viscosity:

Not available.

Viscosity:

Not available.

**Decomposition temperature:** Not available.

## 10. STABILITY AND REACTIVITY

**Stability**: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing. Polymerization may occur at elevated temperature or in the

presence of incompatible materials.

**Hazardous decomposition** 

products:

IDH number: 233057

Oxides of carbon. Irritating organic vapours.

Incompatible materials: Strong oxidizing agents. Strong acids and strong bases. Free radical initiators. Heat, sunlight,

UV light, contamination or an oxygen free atmosphere. Reducing agents.

Reactivity: Not available.

Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation: Harmful if inhaled. Inhalation of vapors or mists of the product may be irritating to the

respiratory system.

**Skin contact:** Causes skin irritation. May cause allergic skin reaction. **Eye contact:** Causes serious eye irritation.

**Ingestion:** May irritate mouth, throat, and stomach if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Alkyl methacrylate	Oral LD50 (RAT) = > 2,000 mg/kg	Irritant, Allergen
Polyglycol dimethacrylate	None	Irritant, Allergen
Acrylate	None	Irritant, Allergen
Polyurethane Methacrylate Resin	None	No Data
Cumene hydroperoxide	None	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
2-Hydroxyethyl methacrylate	Oral LD50 (RAT) = 11.2 g/kg Oral LD50 (RAT) = 5,050 mg/kg	Irritant, Allergen
Cumene	Oral LD50 (RAT) = 2.91 g/kg Oral LD50 (RAT) = 1,400 mg/kg Inhalation LC50 (RAT, 4 h) = 8000 ppm	Central nervous system, Irritant, Lung

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Alkyl methacrylate	No	No	No
Polyglycol dimethacrylate	No	No	No
Acrylate	No	No	No
Polyurethane Methacrylate Resin	No	No	No
Cumene hydroperoxide	No	No	No
2-Hydroxyethyl methacrylate	No	No	No
Cumene	No	Group 2B	No

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

## 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Cumene hydroperoxide (CAS# 80-15-9).

CERCLA Reportable quantity: Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

**Canada Regulatory Information** 

IDH number: 233057

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Sheila Gines, Regulatory Affairs Specialist

**Issue date:** 08/22/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 233057