

Revision Number: 006.0 Issue date: 01/10/2018

# 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name:** LOCTITE DRI 517 known as 517

**VIBRA-SEAL** 

Product type: Pre-applied thread sealant

Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 231500

Item number: 25669 Region: **United States** 

**Contact information:** 

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW	
WARNING:	MAY CAUSE AN ALLERGIC SKIN REACTION.	

HAZARD CLASS	HAZARD CATEGORY
SKIN SENSITIZATION	1

#### PICTOGRAM(S)



#### **Precautionary Statements**

Prevention: Avoid breathing vapors, mist, or spray. Contaminated work clothing should not be allowed out

of the workplace. Wear protective gloves.

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Response:

Wash contaminated clothing before reuse.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Mica	12001-26-2	5 - 10	
Ethene, homopolymer	9002-88-4	5 - 10	
Ethene, tetrafluoro-, homopolymer	9002-84-0	1 - 5	
Diiron trioxide	1309-37-1	1 - 5	
Triiron tetraoxide	1317-61-9	1 - 5	

Product name: LOCTITE DRI 517 known as 517 VIBRA-SEAL IDH number: 231500

Titanium dioxide	13463-67-7	1 - 5
Sodium nitrite	7632-00-0	0.1 - 1
Quartz (SiO2), <1% respirable	14808-60-7	0.1 - 1
1-(3-Chloroallyl)-3,5,7-triaza-1- azoniaadamantane chloride	4080-31-3	0.1 - 1

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get medical attention.

**Skin contact:** Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Wash clothing before reuse. Get medical

attention.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

**Ingestion:** DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

# 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Aldehydes. Alcohols. Irritating organic

vapours.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to

prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure

Controls / Personal Protection" prior to clean up.

# 7. HANDLING AND STORAGE

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8. Handling:

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Mica	3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA	None	None
Ethene, homopolymer	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles.	15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Ethene, tetrafluoro-, homopolymer	None	None	None	10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.
Diiron trioxide	5 mg/m3 TWA Respirable fraction.	10 mg/m3 PEL Fume. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Triiron tetraoxide	None	None	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Sodium nitrite	None	None	None	2 mg/m3 TWA Respirable fraction.
Quartz (SiO2), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust.	None	None
1-(3-Chloroallyl)-3,5,7-triaza-1- azoniaadamantane chloride	None	None	None	None

**Engineering controls:** 

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eyelface protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color:Medium, BrownOdor:AmmoniacalOdor threshold:Not available.

**pH**: 9.4

Vapor pressure: 20 mm hg Approximately

Boiling point/range: Not available. Melting point/ range: Not determined Specific gravity: 1.1365 Vapor density: Not available. Flash point: Aqueous solution Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability Not applicable **Evaporation rate:** Not available. Solubility in water: Completely soluble Partition coefficient (n-octanol/water): Not available.

VOC content:

Viscosity:

Not available.

Not available.

Not available.

Not available.

Decomposition temperature: Not available.

#### 10. STABILITY AND REACTIVITY

**Stability**: Stable under normal conditions of storage and use.

**Hazardous reactions:** None under normal processing.

Hazardous decomposition products:

Oxides of carbon. Oxides of nitrogen. Alcohols. Aldehydes. Acrylic monomers. Irritating

organic vapours.

**Incompatible materials:** Strong oxidizing agents. Fluorine.

Reactivity: Not available.

Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

#### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

# Potential Health Effects/Symptoms

Inhalation of vapors or mists of the product may be irritating to the respiratory system. May cause skin irritation. May cause an allergic skin reaction. Inhalation:

Skin contact:

Eye contact:

May cause eye irritation.

May cause gastrointestinal tract irritation if swallowed. Ingestion:

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Mica	None	Lung
Ethene, homopolymer	None	No Target Organs
Ethene, tetrafluoro-, homopolymer	None	No Target Organs
Diiron trioxide	None	Allergen, Cardiac, Central nervous system, Irritant, Kidney, Liver, Lung
Triiron tetraoxide	None	Cardiac, Central nervous system, Irritant, Kidney, Liver, Lung
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity
Sodium nitrite	Oral LD50 (Rat) = 85 mg/kg Oral LD50 (Mouse) = 175 mg/kg Oral LD50 (Rabbit) = 186 mg/kg Inhalation LC50 (Rat, 4 h) = 5.5 mg/l	Blood, Central nervous system, Mutagen, Vascular
Quartz (SiO2), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity
1-(3-Chloroallyl)-3,5,7-triaza-1- azoniaadamantane chloride	Oral LD50 (Rat) = 500 mg/kg Oral LD50 (Rabbit) = 78.5 mg/kg Dermal LD50 (Rabbit) = 565 mg/kg	Allergen, Irritant, Reproductive

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Mica	No	No	No
Ethene, homopolymer	No	No	No
Ethene, tetrafluoro-, homopolymer	No	No	No
Diiron trioxide	No	No	No
Triiron tetraoxide	No	No	No
Titanium dioxide	No	Group 2B	No
Sodium nitrite	No	No	No
Quartz (SiO2), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes
1-(3-Chloroallyl)-3,5,7-triaza-1- azoniaadamantane chloride	No	No	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

IDH number: 231500

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:**Not a RCRA hazardous waste.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None

International Air Transportation (ICAO/IATA)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Not regulated
None
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

# 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: Ethene, tetrafluoro-, homopolymer (CAS# 9002-84-0).

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
Immediate Health, Delayed Health
None above reporting de minimis.

CERCLA Reportable quantity: Sodium nitrite (CAS# 7632-00-0) 100 lbs. (45.4 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2

Prepared by: Product Safety and Regulatory Affairs

Issue date: 01/10/2018

IDH number: 231500 Product name: LOCTITE DRI 517 known as 517 VIBRA-SEAL

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.