

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Product Use/Class: CHEMGLAZE 9944B Wash Primer, Part B

Importer:

Supplier: Socomore 791 Westport Parkway Fort Worth, TX 76177 Telephone: 817-335-1826

Chemtrec 24 Hr Transportation Emergency No. 800 424-9300 (Outside Continental U.S. 703 527-3887)

Supplier:

EFFECTIVE DATE: 08/14/2017

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A Carcinogenicity Category 2 Reproductive toxicity Category 1B Specific target organ systemic toxicity (single exposure) Category 3 Specific target organ systemic toxicity (single exposure) Category 1 Respiratory system Specific target organ systemic toxicity (repeated exposure) Category 2 Central nervous system, Nervous system Specific target organ systemic toxicity (repeated exposure) Category 1 Liver Hazardous to the aquatic environment - acute hazard Category 3 Hazardous to the aquatic environment - chronic hazard Category 3

GHS LABEL ELEMENTS:

Symbol(s)



Signal Word DANGER

Hazard Statements

Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May damage fertility or the unborn child. May cause drowsiness or dizziness. May cause respiratory irritation. Causes damage to organs.(Respiratory system) May cause damage to organs through prolonged or repeated exposure.(Central nervous system, Nervous system) Causes damage to organs through prolonged or repeated exposure.(Liver) Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/eye protection/face protection. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment.

Response

Call a POISON CENTER or doctor/physician if you feel unwell. IF exposed: Call a POISON CENTER or doctor/physician. Specific treatment (see supplemental first aid instructions on this label). IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take off contaminated clothing and wash before reuse.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

Other Hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

Acute: Vapor harmful; may affect the brain or nervous system causing dizziness, headache or nausea. Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. May be harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

Chronic: May cause kidney damage. Prolonged or repeated contact may result in dermatitis. IARC has designated Methyl isobutyl ketone to be in Group 2B - possibly carcinogenic to humans. ACGIH considers Ethyl alcohol to be an A3 carcinogen (confirmed animal carcinogen with unknown relevance in humans).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Range
Ester solvent	108-65-6	65 - 70 %
Ester solvent	88917-22-0	10 - 15 %
Secondary butanol	78-92-2	5 - 10 %
Ethyl alcohol	64-17-5	5 - 10 %
Phosphoric acid	7664-38-2	1 - 5 %
Methyl isobutyl ketone	108-10-1	0.1 - 1 %

4. FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

FIRST AID - SKIN CONTACT: Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

FIRST AID - INHALATION: Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

MOST IMPORTANT SYMPTOMS AND HAZARDOUS EFFECTS: Refer to section 2 of this SDS.

PROTECTION OF FIRST AID PROVIDER: Appropriate protective equipment or clothing should be used.

NOTES TO PHYSICIANS: Treat per symptoms.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog **UNSUITABLE EXTINGUISHING MEDIA:** Not determined for this product.

SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL: Flammable liquid and vapor. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water spray may be ineffective. If water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES: Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid contact. Avoid breathing vapors. Use self-contained breathing equipment.

ENVIRONMENTAL PRECAUTIONS: Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form. Contain and remove with inert absorbent material.

7. HANDLING AND STORAGE

HANDLING: Keep closure tight and container upright to prevent leakage. Ground and bond containers when transferring material. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat, sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored.

STORAGE: Do not store or use near heat, sparks, or open flame. Store only in well-ventilated areas. Do not puncture, drag, or slide container. Keep container closed when not in use.

INCOMPATIBILITY: Strong acids, bases, and strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

COMPONENT EXPOSURE LIMIT

onin on him obe		
Ester solvent	108-65-6	Not Established
Ester solvent	88917-22-0	Not Established
Secondary butanol	78-92-2	ACGIH-TWA: 100 ppm
Ethyl alcohol	64-17-5	ACGIH-STEL: 1,000 ppm
Phosphoric acid	7664-38-2	ACGIH-STEL: 3 mg/m3 ACGIH-TWA: 1 mg/m3
Methyl isobutyl ketone	108-10-1	ACGIH-STEL: 75 ppm ACGIH-TWA: 20 ppm

ENGINEERING CONTROLS: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area. Sufficient ventilation (using explosion-proof equipment) should be provided to prevent flammable vapor/air mixtures from accumulating.

PERSONAL PROTECTION MEASURES/EQUIPMENT:

RESPIRATORY PROTECTION: Use a NIOSH approved chemical/mechanical filter respirator designed to remove a combination of particulates and organic vapor if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. For respirator use observe OSHA regulations (29CFR 1910.134) or use in accordance with applicable laws and regulations of your country or particular locality.

SKIN PROTECTION: Use neoprene, nitrile, or rubber gloves to prevent skin contact.

EYE PROTECTION: Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

OTHER PROTECTIVE EQUIPMENT: Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

HYGIENIC PRACTICES: Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

PHYSICAL STATE:	Liquid	VAPOR PRESSURE:	N.D.
APPEARANCE:	Clear	VAPOR DENSITY:	Heavier than Air
ODOR:	Solvent	DENSITY:	0.94 g/cm3
ODOR THRESHOLD:	N.D.	SOLUBILITY IN H2O:	Insoluble
pH:	N.A.	COEFFICIENT OF WATER/OIL	N.D.
		DISTRIBUTION:	
FREEZE POINT:	N.D.	AUTOIGNITION TEMPERATURE:	N.D.
BOILING RANGE:	78 - 200 °C	DECOMPOSITION	N.D.
		TEMPERATURE:	
FLASH POINT:	69 °F, 20 °C Tagliabue	VISCOSITY, DYNAMIC:	N.D.
	Closed Cup		
EVAPORATION RATE:	Slower than n-butyl-	VISCOSITY, KINEMATIC:	N.D.
	acetate		
FLAMMABILITYY	N.D.	VOLATILE BY WEIGHT:	98.26 %
LOWER EXPLOSIVE LIMIT:	1.3 %(V)	VOLATILE BY VOLUME:	99.00 %
UPPER EXPLOSIVE LIMIT:	19 %(V)	VOC CALCULATED:	7.68 lb/gal, 921 g/l
			2 0

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions.

STABILITY: Product is stable under normal storage conditions.

CONDITIONS TO AVOID: High temperatures. Sources of ignition.

INCOMPATIBILITY: Strong acids, bases, and strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, Corrosive acid vapors

11. TOXICOLOGICAL INFORMATION

EXPOSURE PATH: Refer to section 2 of this SDS.

SYMPTOMS: Refer to section 2 of this SDS.

CHRONIC EFFECTS: Refer to section 2 of this SDS.

TOXICITY MEASURES:

Acute toxicity : No classification proposed

Chemical Name	LD50/LC50
Ester solvent	Oral LD50: Rat 8,532 mg/kg
	Dermal LD50: Rabbit > 5 g/kg
Ester solvent	N.D.
Secondary butanol	Oral LD50: Rat 2,200 mg/kg
	Dermal LD50: Rat > 2 g/kg
	Dermal LD50: Rabbit > 2,000 mg/kg
	Inhalation LC50: Rat 48,500 mg/m3 /4 h
Ethyl alcohol	Oral LD50: Rat 7,060 mg/kg
	Inhalation LC50: Rat 124.7 mg/l /4 h
Phosphoric acid	Oral LD50: Rat 1,530 mg/kg
	Dermal LD50: Rabbit 2,740 mg/kg
Methyl isobutyl ketone	Oral LD50: Rat 2,080 mg/kg
	Dermal LD50: Rabbit 3,000 mg/kg
	Inhalation LC50: Rat 8.2 mg/l /4 h

Skin corrosion/irritation: Category 2 - Causes skin irritation.

Components contributing to classification: Ester solvent. Phosphoric acid.

Serious eye damage/eye irritation: Category 2A - Causes serious eye irritation.

Components contributing to classification: Ester solvent. Ester solvent. Secondary butanol. Ethyl alcohol. Phosphoric acid.

Skin sensitization: No classification proposed

Respiratory sensitization: No classification proposed

Germ cell mutagenicity: No classification proposed

- **Carcinogenicity:** Category 2 Suspected of causing cancer. Components contributing to classification: Methyl isobutyl ketone.
- **Reproductive toxicity:** Category 1B May damage fertility or the unborn child. Components contributing to classification: Secondary butanol. Methanol.
- **Specific target organ systemic toxicity (single exposure):** Category 3 May cause drowsiness or dizziness. Components contributing to classification: Ester solvent.

Specific target organ systemic toxicity (single exposure): Category 3 - May cause respiratory irritation. Components contributing to classification: Ester solvent.

Specific target organ systemic toxicity (single exposure): Category 1 - Causes damage to organs.(Respiratory system)

Components contributing to classification: Phosphoric acid.

Specific target organ systemic toxicity (repeated exposure): Category 2 - May cause damage to organs through prolonged or repeated exposure.(Central nervous system, Nervous system)

Components contributing to classification: Ethyl alcohol.

Specific target organ systemic toxicity (repeated exposure): Category 1 - Causes damage to organs through prolonged or repeated exposure.(Liver)

Components contributing to classification: Ethyl alcohol.

Aspiration hazard: No classification proposed

12. ECOLOGICAL INFORMATION

ECOTOXICITY:

Chemical Name	Ecotoxicity	
Ester solvent	<u>Fish:</u> Pimephales promelas 161 mg/196 h Static <u>Invertebrates:</u> Daphnia magna > 500 mg/148 h	
Ester solvent	N.D.	
Secondary butanol	<u>Fish:</u> Pimephales promelas 3,380 - 3,990 mg/l96 h flow-through <u>Invertebrates:</u> Daphnia magna 1,859 - 7,143 mg/l48 h Static	
Ethyl alcohol	<u>Fish:</u> Pimephales promelas > 100 mg/l96 h Static Pimephales promelas 13,400 - 15,100 mg/l96 h flow-through <u>Invertebrates:</u> Daphnia magna 9,268 - 14,221 mg/l48 h Daphnia magna 2 mg/l48 h Static	
Phosphoric acid	N.D.	
Methyl isobutyl ketone	<u>Fish:</u> Pimephales promelas 496 - 514 mg/l96 h flow-through <u>Invertebrates:</u> Daphnia magna 170 mg/l48 h <u>Plants:</u> Pseudokirchneriella subcapitata 400 mg/l96 h	

PERSISTENCE AND DEGRADABILITY: Not determined for this product.

BIOACCUMULATIVE: Not determined for this product.

MOBILITY IN SOIL: Not determined for this product.

OTHER ADVERSE EFFECTS: Not determined for this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

14. TRANSPORT INFORMATION

US DOT Road	
DOT Proper Shipping Name:	Paint
DOT Hazard Class:	3
SECONDARY HAZARD:	None
DOT UN/NA Number:	1263
Packing Group:	II
Emergency Response Guide Number:	128
IATA Cargo	
PROPER SHIPPING NAME:	Paint

DOT Hazard Class:	3
HAZARD CLASS:	None
UN-NUMBER:	1263
PACKING GROUP:	II
EMS:	3L
IMDG PROPER SHIPPING NAME: DOT Hazard Class: HAZARD CLASS: UN-NUMBER: PACKING GROUP: EMS:	Paint 3 None 1263 II F-E

The listed transportation classification applies to non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

15. REGULATORY INFORMATION

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CEPA STATUS: All components of this product are on the Canadian DSL list.

16. OTHER INFORMATION

Revision: New GHS SDS Format

Effective Date: 08/14/2017

DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.