

Safety Data Sheet

Version 1.0
Revision Date 02/18/2019

SDS Number 300000078615
Print Date 03/28/2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Dynasolve 750

Product Use Description : Polymer Remover

Manufacturer/Importer/Distributor : Versum Materials US, LLC
8555 South River Parkway
Tempe, AZ 85284-2601
Exporter EIN No. 47-5632014
www.versummaterials.com

Telephone : 800 837 2724

Emergency telephone number (24h) : 1-800-424-9300
(+1) 703-741-5970 (CHEMTREC)

2. HAZARDS IDENTIFICATION

GHS classification

Flammable liquids - Category 3
Acute toxicity - Oral Category 4
Acute toxicity - Inhalation Category 4
Acute toxicity - Dermal Category 4
Skin Corrosion/Irritation - Category 1C
Serious Eye Damage/Eye Irritation - Category 1
Reproductive toxicity - Category 1B
Specific target organ toxicity - single exposure - Category 1

GHS label elements

Hazard pictograms/symbols



Signal Word: Danger

Hazard Statements:

Safety Data Sheet

Version 1.0

Revision Date 02/18/2019

SDS Number 300000078615

Print Date 03/28/2019

H226:Flammable liquid and vapor.
H302+H312+H332:Harmful if swallowed, in contact with skin or if inhaled
H314:Causes severe skin burns and eye damage.
H360:May damage fertility or the unborn child
H370:Causes damage to organs.

Precautionary Statements:

Prevention : P201:Obtain special instructions before use.
P210:Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
P233:Keep container tightly closed.
P240:Ground/Bond container and receiving equipment.
P241:Use explosion-proof electrical/ventilating/lighting/equipment.
P242:Use only non-sparking tools.
P243:Take precautionary measures against static discharge.
P271:Use only outdoors or in a well-ventilated area.
P260:Do not breathe dust/fume/gas/mist/vapours/spray.
P270:Do not eat, drink or smoke when using this product.
P280:Wear protective gloves/protective clothing/eye protection/face protection.
P264:Wash hands thoroughly after handling.

Response : P308+P313 :IF exposed or concerned: Get medical advice/attention.
P301+P310 :IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P330 :Rinse mouth.
P303+P361+P353 :IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 :IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 :IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 :Immediately call a POISON CENTRE/doctor.
P321 :Specific treatment (see on this label).
P370+P378 :In case of fire, use recommended extinguishing media for extinction.

Storage : P403+P235:Store in a well-ventilated place. Keep cool.
P405:Store locked up.

Disposal : P501:Disposal of contents/container to be specified in accordance with regulations.

Hazards not otherwise classified

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

2/12

Versum Materials US,LLC

Dynasolve 750

Safety Data Sheet

Version 1.0

Revision Date 02/18/2019

SDS Number 300000078615

Print Date 03/28/2019

Components	CAS Number	Concentration (Weight)
Propan-2-ol, 1-methoxy-	107-98-2	40% - 60 %
Methyl-2-pyrrolidinone, 1-	872-50-4	20% - 40 %
1-Phenoxy-2-propanol	770-35-4	20% - 40 %
Methyl alcohol	67-56-1	2.5% - 10 %
Potassium Hydroxide	1310-58-3	< 5 %

4. FIRST AID MEASURES

- General advice : Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.
- Eye contact : Hold eyelids apart, initiate and maintain gentle and continuous irrigation care is not promptly available, continue to irrigate for one hour.
- Skin contact : Immediately remove contaminated clothing, and any extraneous chemical, if possible to do so without delay. Flush immediately with copious amounts of water. Initiate and maintain continuous irrigation until the patient receives medical care. If medical care is not promptly available, continue to irrigate for one hour. Cover wound with sterile dressing.
- Ingestion : Medical care must emphasize the control of acidosis and the use of intravenous bicarbonate has been lifesaving. Evidence is good that treatment of methanol absorption is enhanced through the administration of ethanol, which should be given to produce a blood level of at least 0.1%. Ethanol diminishes the production of toxic metabolites of methanol. Blood methanol level of 50 mg/100mL is an indication for hemodialysis, which has improved the prognosis of methanol intoxication. Methanol is often confused with beverage alcohol (ethylalcohol). Care must cause of methanol poisoning. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice. Prevent aspiration of vomit. Turn victim's head to the side.
- Inhalation : If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. If unconscious place in recovery position and seek medical advice. Move to fresh air.
- Most important symptoms/effects - acute and delayed : Asthma. Eye disease. Skin disorders and Allergies. Neurological disorders
- Immediate Medical Attention and Special Treatment
- Risks : In case of ingestion or massive inhalation, observe victim as an inpatient hours between exposure and acidosis and blindness.

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam.

3/12

Versum Materials US,LLC

Dynasolve 750

Safety Data Sheet

Version 1.0

Revision Date 02/18/2019

SDS Number 300000078615

Print Date 03/28/2019

Carbon dioxide (CO₂).

Dry chemical.

Dry sand.

Limestone powder.

- Specific hazards : Incomplete combustion may form carbon monoxide. Flash back possible over considerable distance. Fire or intense heat may cause violent rupture of packages. Burning produces noxious and toxic fumes. May form explosive mixtures in air. Downwind personnel must be evacuated.
- Special protective equipment for fire-fighters : Avoid contact with the skin. A face shield should be worn. Use personal protective equipment. Wear self contained breathing apparatus for fire fighting if necessary.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations., Do not allow run-off from firefighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

- Personal Precautions, Protective Equipment, and Emergency Procedures : Remove all sources of ignition. Use self-contained breathing apparatus and chemically protective clothing. Evacuate personnel to safe areas.
- Environmental precautions : Local authorities should be advised if significant spillages cannot be contained. Prevent spilled product from entering streams or drinking water supplies. Shut off or remove all ignition sources. Construct a dike to prevent spreading.
- Methods for cleaning up : Absorb with inert absorbent materials such as: Dry sand. Vermiculite. Activated charcoal. Approach suspected leak areas with caution. Call Emergency Response number for advice. Place in appropriate chemical waste container.
- Additional advice : If possible, stop flow of product.

7. HANDLING AND STORAGE

Handling

Avoid contact with skin and eyes. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. See "Flammable and Combustible Liquid Code" NFPA No. 30, National Fire Protection Association, Boston, MA. Use personal protective equipment. When using, do not eat, drink or smoke.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat and sources of ignition. Keep away from oxidizers.

Technical measures/Precautions

Keep away from open flames, hot surfaces and sources of ignition.

Safety Data Sheet

Version 1.0

Revision Date 02/18/2019

SDS Number 300000078615

Print Date 03/28/2019

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures

Provide readily accessible eye wash stations and safety showers.

Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits.

Personal protective equipment

- | | | |
|---|---|---|
| Respiratory protection | : | Wear appropriate respirator when ventilation is inadequate. |
| Hand protection | : | Neoprene gloves.
Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. |
| Eye protection | : | Full face shield with goggles underneath. |
| Skin and body protection | : | Impervious clothing.
Rubber or plastic boots.
Slicker Suit. |
| Environmental exposure controls | : | Local authorities should be advised if significant spillages cannot be contained. Prevent spilled product from entering streams or drinking water supplies. Shut off or remove all ignition sources. |
| Special instructions for protection and hygiene | : | Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash hands at the end of each workshift and before eating, smoking or using the toilet. Provide readily accessible eye wash stations and safety showers. |

Exposure limit(s)

Safety Data Sheet

Version 1.0

Revision Date 02/18/2019

SDS Number 300000078615

Print Date 03/28/2019

Propan-2-ol, 1-methoxy-	Short Term Exposure Limit (STEL): ACGIH	100 ppm	-
Propan-2-ol, 1-methoxy-	Recommended exposure limit (REL): NIOSH	100 ppm	360 mg/m3
Propan-2-ol, 1-methoxy-	Short Term Exposure Limit (STEL): NIOSH	150 ppm	540 mg/m3
Propan-2-ol, 1-methoxy-	Time Weighted Average (TWA): ACGIH	50 ppm	-
Methyl-2-pyrrolidinone, 1-	Time Weighted Average (TWA): WEEL	10 ppm	40 mg/m3
Methyl alcohol	Time Weighted Average (TWA): ACGIH	200 ppm	-
Methyl alcohol	Short Term Exposure Limit (STEL): ACGIH	250 ppm	-
Methyl alcohol	Short Term Exposure Limit (STEL): NIOSH	250 ppm	325 mg/m3
Methyl alcohol	Recommended exposure limit (REL): NIOSH	200 ppm	260 mg/m3
Methyl alcohol	Permissible exposure limit: OSHA Z1	200 ppm	260 mg/m3
Potassium Hydroxide	Ceiling Limit Value: ACGIH	-	2 mg/m3
Potassium Hydroxide	Ceiling Limit Value and Time Period (if specified): NIOSH	-	2 mg/m3

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid. Blue-green
Odor	: No data available.
Odor threshold	: No data available.
pH	: No data available.
Melting point/range	: No data available.
Boiling point/range	: 248 °F (120 °C)
Flash point	: 106 °F (41 °C) Pensky-Martens Closed Cup
Evaporation rate	: No data available.
Flammability (solid, gas)	: Refer to product classification in Section 2
Upper/lower explosion/flammability limit	: No data available.
Vapor pressure	: 11.18 mmHg
Water solubility	: Miscible with water.
Relative vapor density	: No data available.
Relative density	: 1.01 (water = 1)
Partition coefficient: n-	: No data available.

Safety Data Sheet

Version 1.0

Revision Date 02/18/2019

SDS Number 300000078615

Print Date 03/28/2019

octanol/water [log Kow]

Auto-ignition temperature : No data available.

Decomposition temperature : No data available.

Viscosity : No data available.

Density : No data available.

: 63.052 lb/ft3 (1.01 g/cm3)

10. STABILITY AND REACTIVITY

Chemical Stability : Stable under normal conditions.

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : Reactive metals (e.g. sodium, calcium, zinc etc.).
Materials reactive with hydroxyl compounds.
Acids.
Oxidizing agents.

Hazardous decomposition products : Carbon monoxide.
Carbon dioxide (CO₂).
Aldehydes
Flammable hydrocarbon fragments.
Nitrogen oxides (NO_x).

Possibility of hazardous Reactions/Reactivity : No data available.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Likely routes of exposure

Effects on Eye : Causes eye burns. May cause blindness.

Effects on Skin : Harmful in contact with skin. Causes skin burns. If absorbed through the skin, may cause central nervous system effects, such as headache, nausea, dizziness, confusion, breathing difficulties.

Inhalation Effects : Harmful if inhaled. Can cause severe eye, skin and respiratory tract burns. Inhalation of aerosol may cause irritation to the upper respiratory tract. May cause central nervous system effects, such as headache, nausea, dizziness, confusion, breathing difficulties. Severe cases of overexposure can result in respiratory failure.

Ingestion Effects : Harmful if swallowed. If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach. Can cause optic

Safety Data Sheet

Version 1.0

Revision Date 02/18/2019

SDS Number 300000078615

Print Date 03/28/2019

nerve damage and blindness.

Symptoms : No data available.

Acute toxicity

Acute Oral Toxicity : No data is available on the product itself.

Acute Oral Toxicity - Components

Propan-2-ol, 1-methoxy-	LD50 : 5,700 mg/kg	Species : Rat
Methyl-2-pyrrolidinone, 1-	LD50 : 3,914 mg/kg	Species : Rat
Methyl alcohol	LD50 : 5,628 mg/kg	Species : Rat
Potassium Hydroxide	LD50 : 273 mg/kg	Species : Rat

Inhalation : No data is available on the product itself.

Inhalation - Components

Propan-2-ol, 1-methoxy-	LC50 (4 h) : 22 mg/l	Species : Rat
Methyl-2-pyrrolidinone, 1-	LC50 (4 h) : > 5.1 mg/l	Species : Rat
Methyl alcohol	LC50 (1 h) : > 84 mg/l	Species : Rat

Acute Dermal Toxicity : No data is available on the product itself.

Acute Dermal Toxicity - Components

Propan-2-ol, 1-methoxy-	LD50 : 13,000 mg/kg	Species : Rabbit
Methyl-2-pyrrolidinone, 1-	LD50 : 8,000 mg/kg	Species : Rabbit
Methyl alcohol	LD50 : 16,000 mg/kg	Species : Rabbit
Potassium Hydroxide	LD50 : 1,260 mg/kg	Species : Rabbit

Skin corrosion/irritation : Causes skin burns.

Serious eye damage/eye irritation : Risk of serious damage to eyes.

Sensitization. : No data available.

Chronic toxicity or effects from long term exposures

Carcinogenicity : No data available.

Reproductive toxicity : 1-Methyl-2-Pyrrolidone has caused embryotoxic and teratogenic effects in laboratory animals.

Germ cell mutagenicity : No data is available on the product itself.

Specific target organ systemic toxicity (single exposure) : Causes damage to organs., Central nervous system., Can cause optic nerve damage and blindness.

Specific target organ systemic : No data available.

Safety Data Sheet

Version 1.0

Revision Date 02/18/2019

SDS Number 300000078615

Print Date 03/28/2019

toxicity (repeated exposure)

Aspiration hazard : No data available.

Delayed and Immediate Effects and Chronic Effects from Short and Long Term Exposure

This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater. This product may cause adverse reproductive effects. Asthma., Eye disease., Skin disorders and Allergies., Neurological disorders

Methanol has relatively low acute toxicity in non-primates, but causes profound species-specific toxicity dependent on the extent to which formate accumulates. Sensitive primate species develop increased blood formate concentrations after methanol exposure, while rodents, rabbits and dogs do not. Exposure of non-primate lab animals to high methanol doses result in Central Nervous System (CNS) depression. Toxic effects in primates including metabolic acidosis and ocular toxicity, effects not normally found in lower animals.

12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Aquatic toxicity : No data is available on the product itself.

Toxicity to fish - Components

Propan-2-ol, 1-methoxy-	LC50 (96 h) : > 4,600 mg/l	Species : Golden Orfe (Leuciscus lodus L, Golden variety)
Propan-2-ol, 1-methoxy-	LC50 (96 h) : 20,800 mg/l	Species : Fathead minnow (Pimephales promelas)
Methyl-2-pyrrolidinone, 1-	LC50 (96 h) : 832 mg/l	Species : Bluegill (Lepomis macrochirus)
Methyl-2-pyrrolidinone, 1-	LC50 (96 h) : 4,000 mg/l	Species : Golden Orfe (Leuciscus lodus L, Golden variety)
Methyl alcohol	EC 50 (48 h) : 13,200 mg/l	Species : Rainbow Trout
Methyl alcohol	EC 50 (48 h) : 16,000 mg/l	Species : Bluegill (Lepomis macrochirus)
Potassium Hydroxide	LC50 (96 h) : 10 mg/l	Species : Fish

Toxicity to daphnia - Components

Propan-2-ol, 1-methoxy-	EC 50 (48 h) : > 500 mg/l	Species : Daphnia
Methyl-2-pyrrolidinone, 1-	EC 50 (48 h) : > 4,000 mg/l	Species : Daphnia
Methyl alcohol	EC 50 (48 h) : > 10,000 mg/l	Species : Daphnia

Toxicity to other organisms : No data available.

Persistence and degradability

9/12

Versum Materials US, LLC

Dynasolve 750

Safety Data Sheet

Version 1.0

Revision Date 02/18/2019

SDS Number 300000078615

Print Date 03/28/2019

Biodegradability : No data is available on the product itself.

Mobility : No data available.

Bioaccumulation : No data is available on the product itself.

Bioaccumulation - Components

Propan-2-ol, 1-methoxy-
Methyl-2-pyrrolidinone, 1-
Methyl alcohol

Negligible bioaccumulation potential.
Negligible bioaccumulation potential.
Negligible bioaccumulation potential.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products : Contact supplier if guidance is required.

Contaminated packaging : Dispose of container and unused contents in accordance with federal, state, and local requirements.

14. TRANSPORT INFORMATION

DOT

UN/ID No. : UN2924
Proper shipping name : Flammable liquids, corrosive, n.o.s., (Glycol ethers, Potassium Hydroxide)
Class or Division : 3
Packing group : III
Label(s) : 3 (8)
Marine Pollutant : No

IATA

UN/ID No. : UN2924
Proper shipping name : Flammable liquid, corrosive, n.o.s., (Glycol ethers, Potassium Hydroxide)
Class or Division : 3
Packing group : III
Label(s) : 3 (8)
Marine Pollutant : No

IMDG

UN/ID No. : UN2924
Proper shipping name : FLAMMABLE LIQUID, CORROSIVE, N.O.S., (Glycol ethers, Potassium Hydroxide)
Class or Division : 3
Packing group : III
Label(s) : 3 (8)
Marine Pollutant : No

Safety Data Sheet

Version 1.0
Revision Date 02/18/2019

SDS Number 300000078615
Print Date 03/28/2019

TDG

UN/ID No. : UN2924
Proper shipping name : FLAMMABLE LIQUID, CORROSIVE, N.O.S., (Glycol ethers, Potassium Hydroxide)
Class or Division : 3
Packing group : III
Label(s) : 3 (8)
Marine Pollutant : No

Further Information

The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact customer service.

15. REGULATORY INFORMATION

Toxic Substance Control Act (TSCA) 12(b) Component(s):

None.

Country	Regulatory list	Notification
USA	TSCA	Included on Inventory.
EU	EINECS	Included on EINECS inventory or polymer substance, monomers included on EINECS inventory or no longer polymer.
Canada	DSL	Included on Inventory.
Australia	AICS	Included on Inventory.
Japan	ENCS	Not on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.

EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification
Fire Hazard. Acute Health Hazard Chronic Health Hazard

EPA SARA Title III Section 313 (40 CFR 372) Component(s) above 'de minimus' level
Methyl-2-pyrrolidinone, 1-
Methyl alcohol

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)
WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.
Methyl-2-pyrrolidinone, 1-
Methyl alcohol

16. OTHER INFORMATION

11/12

Versum Materials US,LLC

Dynasolve 750

Safety Data Sheet

Version 1.0

Revision Date 02/18/2019

SDS Number 300000078615

Print Date 03/28/2019

HMIS Rating

Health : 3
Flammability : 2
Physical hazard : 0

Prepared by : Versum Materials, Product Regulatory Department

Telephone : 800 837 2724

Preparation Date : 03/28/2019

For additional information, please visit Versum Materials' Product Stewardship web site.
<http://www.versummaterials.com/productstewardship/>
