

SECTION 1: Identification**1.1. Identification**

Product form : Mixture
Product name : CA6207

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesives, binding agents
Recommended use : Cyanoacrylate
Restrictions on use : Product for industrial use only

1.3. Supplier

ResinLab, LLC
N109 W13300 Ellsworth Drive
Germantown, WI 53022 - United States
T 1-877-259-1669
msds@resinlab.com - www.resinlab.com

1.4. Emergency telephone number

Emergency number : CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS US classification**

Flammable liquids Category 4	H227	Combustible liquid
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

H227 - Combustible liquid
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

Precautionary statements (GHS US) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - If on skin: Wash with plenty of water.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a poison center or doctor if you feel unwell.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.

CA6207

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Ethyl 2-cyanoacrylate	(CAS-No.) 7085-85-0	75 – 90

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a poison center/doctor/physician if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Roll or peel skin apart if bonded.
- First-aid measures after eye contact : Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid caused abrasive damage.
- First-aid measures after ingestion : Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Avoid swallowing solid adhesive after detachment. . Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : Irritation.
- Symptoms/effects after eye contact : Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Specific hazards arising from the chemical

- Fire hazard : Combustible liquid.
- Hazardous decomposition products in case of fire : Toxic fumes may be released

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

CA6207

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Do not allow the material to come in contact with cotton, wool, leather, fiberglass or carbon fiber. The reaction between cyanoacrylate and these materials results in a rapid exothermic reaction that can cause serious burns and release an irritating smoke. . Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Do not allow the material to come in contact with cotton, wool, leather, fiberglass or carbon fiber. The reaction between cyanoacrylate and these materials results in a rapid exothermic reaction that can cause serious burns and release an irritating smoke.

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.

Information on mixed storage : Do not store with: self-igniting. Strong oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethyl 2-cyanoacrylate (7085-85-0)		
ACGIH	Local name	Ethyl cyanoacrylate
ACGIH	ACGIH OEL TWA	0.2 ppm
ACGIH	ACGIH OEL STEL	1 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr; asthma. Notations: DSEN; RSEN
ACGIH	Regulatory reference	ACGIH 2024

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves. Do not wear cotton or natural fiber gloves.

Eye protection:

Safety glasses with side shields

Skin and body protection:

Wear suitable protective clothing

CA6207

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Clear light yellow light green
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 83 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 1.06
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
VOC content	No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Oxidizing agent. Amines. Water. Strong bases. Cotton fibers. Wool.

10.6. Hazardous decomposition products

Nitrogen oxides.

CA6207

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Ethyl 2-cyanoacrylate (7085-85-0)	
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Skin, 14 day(s))

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause respiratory irritation.

Ethyl 2-cyanoacrylate (7085-85-0)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Symptoms/effects after inhalation : May cause respiratory irritation.
Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

Ethyl 2-cyanoacrylate (7085-85-0)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

Ethyl 2-cyanoacrylate (7085-85-0)	
Partition coefficient n-octanol/water (Log Pow)	0.776 (Experimental value, EU Method A.8: Partition Coefficient, 22 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Ethyl 2-cyanoacrylate (7085-85-0)	
Surface tension	Not applicable (water solubility < 1 mg/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.834 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

CA6207

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : NA1993 Combustible liquid, n.o.s. (Ethyl 2-cyanoacrylate), Comb Liq, III
UN-No.(DOT) : NA1993
Proper Shipping Name (DOT) : Combustible liquid, n.o.s.
Ethyl 2-cyanoacrylate
Class (DOT) : Comb Liq - Combustible liquid
Packing group (DOT) : III - Minor Danger
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102) : 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e, a multipurpose bulk truck (MBT)).
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not subject

Air transport

Transport document description (IATA) : UN 3334 Aviation regulated liquid, n.o.s. (Ethyl 2-cyanoacrylate), 9, III
UN-No. (IATA) : 3334
Proper Shipping Name (IATA) : Aviation regulated liquid, n.o.s.
Ethyl 2-cyanoacrylate
Class (IATA) : 9 - Miscellaneous Dangerous Substances and Articles
Packing group (IATA) : III - Low danger

SECTION 15: Regulatory information

15.1. US Federal regulations

CA6207

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethyl 2-cyanoacrylate (7085-85-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Ethyl 2-cyanoacrylate (7085-85-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Contains no substance(s) listed on the REACH Candidate List

Ethyl 2-cyanoacrylate (7085-85-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Ethyl 2-cyanoacrylate (7085-85-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Ethyl 2-cyanoacrylate(7085-85-0)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 12/16/2024

Full text of hazard classes and H-statements:

H227	Combustible liquid
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation

SDS US - ResinLab

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.