

Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document Group: | 41-7894-3 | Version Number: | 1.01 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 03/03/21 | Supercedes Date: | 04/15/20 |

SECTION 1: Identification

1.1. Product identifier

3M[™] Scotch-Weld[™] Acrylic Adhesive Accelerator A3-2, Gray, Part A

Product Identification Numbers

62-2959-7530-4, 62-2959-8530-3 7100234571, 7100233358

1.2. Recommended use and restrictions on use

Recommended use Adhesive

1.3. Supplier's details

MANUFACTURER: DIVISION: ADDRESS: Telephone: 3M Industrial Adhesives and Tapes Division 3M Center, St. Paul, MN 55144-1000, USA 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number 1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification Skin Sensitizer: Category 1B.

2.2. Label elements Signal word Warning

Symbols Exclamation mark |

Pictograms



Hazard Statements May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|--|---------------|-------------------------|
| Dibenzoate Propanol | 27138-31-4 | 45 - 65 Trade Secret * |
| Acrylate Polymer | 25101-28-4 | 10 - 30 Trade Secret * |
| Catalyst (NJTS Reg. No. 04499600-6922) | Trade Secret* | 1 - 20 Trade Secret * |
| Organic Peroxide | 13122-18-4 | 0.1 - 10 Trade Secret * |

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

3MTM Scotch-WeldTM Acrylic Adhesive Accelerator A3-2, Gray, Part A 03/03/21

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance Carbon monoxide Carbon dioxide <u>Condition</u> During Combustion During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store in a dry place. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber Neoprene Nitrile Rubber

Respiratory protection None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Appearance | | | | | |
|---------------------------|--|--|--|--|--|
| Physical state | Liquid | | | | |
| Color | Gray | | | | |
| Specific Physical Form: | Paste | | | | |
| Odor | Hydrocarbon | | | | |
| Odor threshold | No Data Available | | | | |
| рН | Not Applicable | | | | |
| Melting point | Not Applicable | | | | |
| Boiling Point | >=150 °F | | | | |
| Flash Point | > 200 °F [<i>Test Method</i> :Closed Cup] | | | | |
| Evaporation rate | No Data Available | | | | |
| Flammability (solid, gas) | Not Applicable | | | | |
| Flammable Limits(LEL) | No Data Available | | | | |
| Flammable Limits(UEL) | No Data Available | | | | |
| Vapor Pressure | No Data Available | | | | |
| Vapor Density | No Data Available | | | | |
| Density | 1.08 g/ml | | | | |
| Specific Gravity | 1.08 [<i>Ref Std</i> :WATER=1] | | | | |
| Solubility in Water | Nil | | | | |
| Solubility- non-water | No Data Available | | | | |
| - | | | | | |

3M[™] Scotch-Weld[™] Acrylic Adhesive Accelerator A3-2, Gray, Part A 03/03/21

| Partition coefficient: n-octanol/ water | No Data Available |
|---|---|
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Viscosity | 20,000 centipoise |
| Hazardous Air Pollutants | 0 % weight |
| Volatile Organic Compounds | 60.5 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1] [<i>Details</i> :EU VOC content] |
| Percent volatile | < 6 |
| VOC Less H2O & Exempt Solvents | <=2.8 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1] [<i>Details</i> :when used as intended with Part B] |
| VOC Less H2O & Exempt Solvents | 60.5 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1] [<i>Details</i> :as supplied] |
| VOC Less H2O & Exempt Solvents | <pre><=0.3 % [Test Method:calculated SCAQMD rule 443.1] [Details:when used as intended with Part B]</pre> |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid Heat Sparks and/or flames

10.5. Incompatible materials Amines Strong acids Strong bases Strong oxidizing agents

10.6. Hazardous decomposition products <u>Substance</u> None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|---------------------------------------|-----------------------------------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE2,000 - 5,000 mg/kg |
| Dibenzoate Propanol | Dermal | Rat | LD50 > 2,000 mg/kg |
| Dibenzoate Propanol | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 200 mg/l |
| Dibenzoate Propanol | Ingestion | Rat | LD50 3,295 mg/kg |
| Acrylate Polymer | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Acrylate Polymer | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Catalyst (NJTS Reg. No. 04499600-6922) | Dermal | Professio nal judgeme nt | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Catalyst (NJTS Reg. No. 04499600-6922) | Ingestion | Rat | LD50 > 2,000 mg/kg |
| Organic Peroxide | Dermal | Rat | LD50 > 2,000 mg/kg |
| Organic Peroxide | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 0.8 mg/l |
| Organic Peroxide | Ingestion | Rat | LD50 12,905 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---------------------|---------|---------------------------|
| Dibenzoate Propanol | Rabbit | No significant irritation |
| Organic Peroxide | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---------------------|---------|---------------------------|
| Dibenzoate Propanol | Rabbit | No significant irritation |
| Organic Peroxide | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|--|---------|----------------|
| Dibenzoate Propanol | Guinea | Not classified |
| | pig | |
| Catalyst (NJTS Reg. No. 04499600-6922) | Mouse | Not classified |

3M[™] Scotch-Weld[™] Acrylic Adhesive Accelerator A3-2, Gray, Part A 03/03/21

| Organic Peroxide | Guinea pig | Sensitizing |
|------------------|---------------|-------------|
|------------------|---------------|-------------|

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|---------------|
| Dibenzoate Propanol | In Vitro | Not mutagenic |
| Catalyst (NJTS Reg. No. 04499600-6922) | In Vitro | Not mutagenic |

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure |
|---------------------|-----------|--|---------|-------------|--------------|
| | | | | | Duration |
| Dibenzoate Propanol | Ingestion | Not classified for female reproduction | Rat | NOAEL 500 | 2 generation |
| | - | | | mg/kg/day | - |
| Dibenzoate Propanol | Ingestion | Not classified for male reproduction | Rat | NOAEL 400 | 2 generation |
| | - | - | | mg/kg/day | - |
| Dibenzoate Propanol | Ingestion | Not classified for development | Rat | NOAEL 1,000 | during |
| - | _ | - | | mg/kg/day | gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--|-----------|-----------------|----------------|---------|----------------------|----------------------|
| Catalyst (NJTS Reg. No. 04499600-6922) | Ingestion | nervous system | Not classified | Rat | NOAEL 2,000 mg/kg | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------------|-----------|---------------------------------|----------------|---------|-----------------------------|----------------------|
| Dibenzoate Propanol | Ingestion | hematopoietic system liver | Not classified | Rat | NOAEL 2,500 mg/kg/day | 90 days |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards Not applicable

Health Hazards

Respiratory or Skin Sensitization

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar

3M[™] Scotch-Weld[™] Acrylic Adhesive Accelerator A3-2, Gray, Part A 03/03/21

emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document Group: | 41-7894-3 | Version Number: | 1.01 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 03/03/21 | Supercedes Date: | 04/15/20 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com