

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 05/28/2020 Version: 1.0

SECTION 1: Identification Identification 1.1. : EP1290 Clear A Product name Recommended use and restrictions on use 1.2. Recommended use : Epoxy resin Restrictions on use : Product for industrial use only 1.3. Supplier ResinLab. LLC N109 W13300 Ellsworth Drive Germantown, WI 53022 - United States T 1-877-259-1669 msds@resinlab.com - www.resinlab.com 1.4. **Emergency telephone number** Emergency number : CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International) SECTION 2: Hazard(s) identification 2.1. **Classification of the substance or mixture GHS US classification** Skin corrosion/irritation Category 2 H315 Causes skin irritation Serious eye damage/eye irritation Category 2 H319 Causes serious eye irritation Skin sensitization, Category 1 H317 May cause an allergic skin reaction Full text of H statements : see section 16 GHS Label elements, including precautionary statements 2.2. **GHS US labeling** Hazard pictograms (GHS US) Signal word (GHS US) Warning Hazard statements (GHS US) H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. Precautionary statements (GHS US) P264 - Wash hands, forearms and face thoroughly after handling. P272 - Contaminated work clothing must not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 - If on skin: Wash with plenty of water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P391 - Collect spillage. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances Not applicable

3.2. Mixtures

OFOTION A. F.

Name	Product identifier	%	GHS US classification
Epoxy Resin	(CAS-No.) 25068-38-6	75 – 90	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

SECT	ON 4: First-aid measures		
4.1.	Description of first aid measures		
First-a	id measures after inhalation	:	Remove person to fresh air and keep comfortable for breathing.
First-a	id measures after skin contact	:	Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-a	id measures after eye contact	:	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-a	id measures after ingestion	:	Rinse mouth out with water. Get medical advice/attention if you feel unwell.
4.2.	Most important symptoms and effe	cts (a	acute and delayed)
Sympt	oms/effects after skin contact	:	Irritation. May cause an allergic skin reaction.
Sympt	oms/effects after eye contact	:	Eye irritation.
4.3.	Immediate medical attention and s	pecia	I treatment, if necessary
Treat sy	mptomatically.		
SECT	ON 5: Fire-fighting measures		
5.1.	Suitable (and unsuitable) extinguis	hing	media
Suitab	le extinguishing media	:	Water spray. Dry powder. Foam. Carbon dioxide.
Unsuit	able extinguishing media	:	Do not use a heavy water stream.
5.2.	Specific hazards arising from the c	hemi	cal
5.3.	Special protective equipment and p	oreca	utions for fire-fighters
Protec	tion during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECT	ON 6: Accidental release mea	isure	es
6.1.	Personal precautions, protective e	quipn	nent and emergency procedures
6.1.1.	For non-emergency personnel		
	ency procedures	:	Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.
6.1.2.	For emergency responders		
Protec	tive equipment	:	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2.	Environmental precautions		
Avoid re	lease to the environment.		
6.3.	Methods and material for containm	ient a	nd cleaning up
For co	ntainment	:	Collect spillage.
Metho	ds for cleaning up	:	Take up liquid spill into absorbent material.
Other	information	:	Dispose of materials or solid residues at an authorized site.
6.4.	Reference to other sections		
For furth	ner information refer to section 13.		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, includi	ng any incompatibilities
Storage conditions	: Store in a well-ventilated place. Keep cool.
SECTION 8: Exposure controls/pers	onal protection
8.1. Control parameters	
Epoxy Resin (25068-38-6)	
Not applicable	
8.2. Appropriate engineering controls	
Appropriate engineering controls	: Use only with adequate ventilation.
Environmental exposure controls	: Avoid release to the environment.
8.3. Individual protection measures/Per	
8.3. Individual protection measures/Per	
Hand protection:	
Protective gloves	
Eye protection:	
Safety glasses with side shields	
Skin and body protection:	
Wear suitable protective clothing	
Respiratory protection:	

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Color	: clear
Odor	: clear
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	No data available
Boiling point	: > 100 °C
Flash point	: > 93 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
10/15/2020	EN (English US)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1.16 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
VOC content	No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Acids. Bases (Alkalis). Oxidizing agent.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO2). Phenolic compounds.

1. Information on toxicological effects	
cute toxicity (oral)	: Not classified
cute toxicity (dermal)	: Not classified
cute toxicity (inhalation)	: Not classified
Epoxy Resin (25068-38-6)	
LD50 oral rat	> 2000 mg/kg (OECD 420: Acute Oral toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
kin corrosion/irritation	: Causes skin irritation.
erious eye damage/irritation	: Causes serious eye irritation.
espiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
carcinogenicity	: Not classified
Epoxy Resin (25068-38-6)	
NOAEL (chronic,oral,animal/male,2 years)	15 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicit (migrated information)
NOAEL (chronic,oral,animal/female,2 years)	100 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Epoxy Resin (25068-38-6)	
NOAEL (oral,rat,90 days)	50 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: other:japanese MITI guidelines for toxicity testing of chemicals
Aspiration hazard	: Not classified
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

SECTION 12: Ecological information		
12.1. Toxicity		
Ecology - general	: Toxic to aquatic life. Toxic to aquatic life with long lasting effects.	
Epoxy Resin (25068-38-6)		
LC50 fish 1	2.3 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, Nominal concentration)	
EC50 Daphnia 1	2 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)	
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	

12.2. Persistence and degradability

Epoxy Resin (25068-38-6)		
Persistence and degradability	Not readily biodegradable in water.	

12.3. Bioaccumulative potential

Epoxy Resin (25068-38-6)			
	BCF other aquatic organisms 1	31 (Estimated value, Fresh weight)	
	Partition coefficient n-octanol/water (Log Pow)	3 (Estimated value, 25 °C)	
	Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

12.4. Mobility in soil

Epoxy Resin (25068-38-6)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Partition coefficient n-octanol/water (Log Koc)	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal	considerations
13.1. Disposal methods	
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
SECTION 14: Transpo	rt information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG)	: UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin), 9, III
UN-No. (IMDG)	: 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	Bisphenol-A-(epichlorohydrin) epoxy resin ; Epoxy Resin
Class (IMDG)	: 9 - Miscellaneous dangerous substances and articles
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5L
Marine pollutant	: Yes
Air transport	
Transport document description (IATA)	: UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A-(epichlorohydrin) epoxy resin;), 9, III
UN-No. (IATA)	: 3082
Proper Shipping Name (IATA)	: Environmentally hazardous substance, liquid, n.o.s.
	Bisphenol-A-(epichlorohydrin) epoxy resin ;
Class (IATA)	: 9 - Miscellaneous Dangerous Goods
Packing group (IATA)	: III - Minor Danger

SECTION 15: Reg	gulatory	information	

15.1. US Federal regulations

Epoxy Resin (25068-38-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).	

15.2. International regulations

CANADA

Epoxy Resin (25068-38-6)	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations Contains no REACH candidate substance

National regulations No additional information available

15.3. US State regulations

WARNING: This product can expose you to 1-chloro-2,3-epoxypropane, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H315	Causes skin irritation	
H317	May cause an allergic skin reaction	
H319	Causes serious eye irritation	
H401	Toxic to aquatic life	
H411	Toxic to aquatic life with long lasting effects	

SDS US - ResinLab

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.