

## SECTION 1 Identification

### 1.1. Product identifier

Product form : Mixture  
Product name : EP1282 Black A

### 1.2. Other means of identification

No additional information available

### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Epoxy resin  
Restrictions on use : Product for industrial use only

### 1.4. Supplier's details

ResinLab, LLC  
N109 W13300 Ellsworth Drive  
Germantown, WI, 53022  
United States  
T 1-877-259-1669  
[msds@resinlab.com](mailto:msds@resinlab.com) - [www.resinlab.com](http://www.resinlab.com)

### 1.5. Emergency phone number

Emergency number : CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International)

## SECTION 2 Hazard Identification

### 2.1. Classification of the substance or mixture

#### GHS US classification

Skin corrosion/irritation, Category 2  
Serious eye damage/eye irritation, Category 2  
Skin sensitization, Category 1

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.

Full text of H statements : see section 16

### 2.2. Label elements

#### GHS US labeling

Hazard pictograms (GHS US)

:



Signal word (GHS US)

: Warning

Hazard statements (GHS US)

: H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation

Precautionary statements (GHS US)

: P261 - Avoid breathing dust, fume, gas, mist, vapors, spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P280 - Wear protective gloves.  
P302+P352 - If on skin: Wash with plenty of water.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

# EP1282 Black A

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.  
P337+P313 - If eye irritation persists: Get medical advice or attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%
Epoxy Resin	CAS-No.: 25068-38-6	75 – 90
1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid	CAS-No.: 74398-71-3	10 – 30
carbon black	CAS-No.: 1333-86-4	0.5 – 1

Full text of hazard classes and H-statements : see section 16

## SECTION 4 First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general : If you feel unwell, seek medical advice.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Rinse mouth out with water. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : None under normal conditions.  
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Eye irritation.  
Symptoms/effects after ingestion : None under normal conditions.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

# EP1282 Black A

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.  
Explosion hazard : No direct explosion hazard.  
Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon oxides (CO, CO<sub>2</sub>).

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6 Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

##### For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

##### For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.  
Environmental precautions : Avoid release to the environment.

#### 6.2. Methods and materials for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.  
Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

### SECTION 7 Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

# EP1282 Black A

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Additional hazards when processed : Contains a component(s) that is encapsulated within the product and not expected to be released during normal processing conditions or a foreseeable emergency. Do not breathe dust created by sanding, grinding or machining.

### 7.2. Conditions for safe storage, including incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.  
Storage conditions : Keep cool. Protect from sunlight.  
Packaging materials : Store always product in container of same material as original container.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

carbon black (1333-86-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Carbon black
ACGIH® TLV® TWA	3 mg/m³ (Inhalable fraction)
Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Carbon black
OSHA PEL TWA	3.5 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

**Personal protective equipment:**  
Wear recommended personal protective equipment.

Hand protection:
Protective gloves
Eye protection:
Safety glasses with side shields
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

# EP1282 Black A

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### Personal protective equipment symbol(s):



## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: Black
Odor	: mild
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 113 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 1.14 g/cm <sup>3</sup>
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Strong acids. Bases. Oxidizing agents. Amines. Mercaptans. Peroxides.

# EP1282 Black A

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Epoxy Resin (25068-38-6)

LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

#### carbon black (1333-86-4)

LD50 oral rat	> 10000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 28 day(s))
LD50 dermal rabbit	> 8000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 4.6 mg/m <sup>3</sup>
ATE US (dust, mist)	0.005 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

#### Epoxy Resin (25068-38-6)

pH	No data available in the literature
----	-------------------------------------

#### carbon black (1333-86-4)

pH	4 – 10 (5 %, 20 °C)
----	---------------------

Serious eye damage/irritation : Causes serious eye irritation.

#### Epoxy Resin (25068-38-6)

pH	No data available in the literature
----	-------------------------------------

#### carbon black (1333-86-4)

pH	4 – 10 (5 %, 20 °C)
----	---------------------

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

#### Epoxy Resin (25068-38-6)

NOAEL (chronic,oral,animal/male,2 years)	15 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
--	---

# EP1282 Black A

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Epoxy Resin (25068-38-6)	
NOAEL (chronic,oral,animal/female,2 years)	100 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified

carbon black (1333-86-4)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0071 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	> 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0011 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard : Not classified

Epoxy Resin (25068-38-6)	
Viscosity	No data available in the literature
carbon black (1333-86-4)	
Viscosity	Not applicable
1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid (74398-71-3)	
Viscosity	294.118 – 490.196 mm²/s

Symptoms/effects after inhalation : None under normal conditions.  
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Eye irritation.  
Symptoms/effects after ingestion : None under normal conditions.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Ecology - general : Toxic to aquatic life.  
Hazardous to the aquatic environment, short-term (acute) : Toxic to aquatic life.  
Hazardous to the aquatic environment, long-term (chronic) : Not classified

Epoxy Resin (25068-38-6)	
LC50 - Fish [1]	1.3 mg/l (96 h, Pisces, Literature study)
EC50 - Crustacea [1]	≈ 2 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	9.4 mg/l (EPA 660/3 - 75/009, Selenastrum capricornutum, Static system, Fresh water, Experimental value, Biomass)
EC50 72h - Algae [2]	> 11 mg/l Test organisms (species): Scenedesmus capricornutum

# EP1282 Black A

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Epoxy Resin (25068-38-6)	
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
carbon black (1333-86-4)	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 72h - Algae [1]	> 10000 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	> 10000 mg/l Test organisms (species):
ErC50 algae	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)

### 12.2. Persistence and degradability

EP1282 Black A	
Persistence and degradability	Not rapidly degradable
Epoxy Resin (25068-38-6)	
Persistence and degradability	Not readily biodegradable in water.
carbon black (1333-86-4)	
Persistence and degradability	Biodegradability in soil: not applicable, Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid (74398-71-3)	
Persistence and degradability	Not rapidly degradable

### 12.3. Bioaccumulative potential

Epoxy Resin (25068-38-6)	
Partition coefficient n-octanol/water (Log Pow)	3 (Estimated value, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
carbon black (1333-86-4)	
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

Epoxy Resin (25068-38-6)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Ecology - soil	No (test)data on mobility of the substance available.
carbon black (1333-86-4)	
Surface tension	Not applicable (solid)



# EP1282 Black A

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

carbon black (1333-86-4)	
Ecology - soil	No (test)data on mobility of the substance available. Not toxic to plants. Not toxic to animals.

### 12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

## SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

## SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

### 14.1. UN number

UN-No. (DOT)	: Not regulated
UN-No. (IMDG)	: 3082
UN-No. (IATA)	: 3082

### 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT)	: Not regulated
Proper Shipping Name (IMDG)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)
Proper Shipping Name (IATA)	: Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin)

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT)	: Not regulated
----------------------------------	-----------------

#### IMDG

Transport hazard class(es) (IMDG)	: 9
Hazard labels (IMDG)	: 9



#### IATA

Transport hazard class(es) (IATA)	: 9
Hazard labels (IATA)	: 9



### 14.4. Packing group

Packing group (DOT)	: Not regulated
Packing group (IMDG)	: III

# EP1282 Black A

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Packing group (IATA) : III

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

#### DOT

Not regulated

#### IMDG

Special provision (IMDG) : 274, 335, 969  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : LP01, P001  
Packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1, TP29  
EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE  
EmS-No. (Spillage) : S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS  
Stowage category (IMDG) : A

#### IATA

Special provision (IATA) : A97, A158, A197  
PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y964  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 964  
PCA max net quantity (IATA) : 450L  
CAO packing instructions (IATA) : 964  
CAO max net quantity (IATA) : 450L  
ERG code (IATA) : 9L

## SECTION 15 Regulatory information

### 15.1. Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Epoxy Resin	25068-38-6	Present	Active	XU
carbon black	1333-86-4	Present	Active	
1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid	74398-71-3	Present	Active	TP;XU

### 15.2. International regulations

#### CANADA

##### Epoxy Resin (25068-38-6)

Listed on the Canadian DSL (Domestic Substances List)

# EP1282 Black A

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

<b>carbon black (1333-86-4)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid (74398-71-3)</b>
Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

<b>Epoxy Resin (25068-38-6)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

<b>carbon black (1333-86-4)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)


### National regulations

<b>Epoxy Resin (25068-38-6)</b>
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

<b>carbon black (1333-86-4)</b>
Listed on IARC (International Agency for Research on Cancer)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

<b>1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid (74398-71-3)</b>
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

### 15.3. State regulations

 <b>WARNING:</b>	This product can expose you to chemicals including Epichlorohydrin, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .
--	---

Component	State or local regulations
carbon black(1333-86-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)  
Issue date : 6/3/2025

# EP1282 Black A

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Full text of hazard classes and H-statements	
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H401	Toxic to aquatic life

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.