EP1282 Black B

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Issue date: 6/3/2025 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : EP1282 Black B

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Epoxy hardener
Restrictions on use : Product for industrial use only

1.4. Supplier's details

ResinLab, LLC
N109 W13300 Ellsworth Drive
Germantown, WI, 53022
United States
T 1-877-259-1669
msds@resinlab.com - www.resinlab.com

1.5. Emergency phone number

Emergency number : CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 1	H314	Causes severe skin burns and eye damage.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 1B	H360	May damage fertility or the unborn child.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :

Signal word (GHS US) : Danger
Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H360 - May damage fertility or the unborn child
Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dusts or mists.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a poison center or doctor.
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Fatty acids, c18-unsat., dimers,polymers with 3,3'-(oxybis(2,1-ethanediyloxy))bis(1-propanamine)	CAS-No.: 68541-13-9	50 – 75
polyoxypropylenediamine	CAS-No.: 9046-10-0	10 – 30
Bisphenol A	CAS-No.: 80-05-7	5 – 10
3,3'-oxybis(ethyleneoxy)bis(propylamine)	CAS-No.: 4246-51-9	5-10

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact : Rinse immediately with plenty of water for 15 minutes. Remove/Take off immediately all contaminated clothing. Get medical advice/attention.
First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Serious damage to eyes.
Symptoms/effects after ingestion : Burns.
Chronic symptoms : May damage fertility or the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released. ammonia. Nitrogen oxides. Carbon oxides (CO, CO2).

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

Environmental precautions : Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Store locked up.

Packaging materials : Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Impervious gloves

Eye protection:
Chemical goggles or face shield. Safety glasses with side shields

Skin and body protection:
Wear suitable protective clothing

Respiratory protection:
In case of inadequate ventilation, wear respiratory protection.

Personal protective equipment symbol(s):

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	:	Liquid
Color	:	Amber
Odor	:	Amine-like
Odor threshold	:	No data available
pH	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	> 93 °C
Flammability (solid, gas)	:	Not applicable.
Vapor pressure	:	No data available
Relative vapor density at 20°C	:	No data available
Relative density	:	No data available
Density	:	0.99 g/cm³
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available
Explosion limits	:	No data available
Particle characteristics	:	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Acids. Peroxides. Oxidizing agents. Product slowly corrodes copper, aluminum, zinc, and galvanized surfaces. Sodium hypochlorite. Bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

polyoxypropylenediamine (9046-10-0)	
LD50 oral rat	2627 mg/kg
LD50 dermal rat	2980 mg/kg
LD50 dermal rabbit	2980 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal)
ATE US (oral)	2627 mg/kg body weight
ATE US (dermal)	2980 mg/kg body weight

Bisphenol A (80-05-7)	
LD50 oral rat	2000 – 5000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	3000 mg/kg body weight (Rabbit, Experimental value, Dermal)
ATE US (oral)	2000 mg/kg body weight
ATE US (dermal)	3000 mg/kg body weight

3,3'-oxybis(ethyleneoxy)bis(propylamine) (4246-51-9)	
LD50 oral rat	3160 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2150 mg/kg (Equivalent or similar to OECD 402, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LD50 dermal rabbit	2500 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns.

polyoxypropylenediamine (9046-10-0)	
pH	11.7

Bisphenol A (80-05-7)	
pH	No data available in the literature

Serious eye damage/irritation : Assumed to cause serious eye damage

polyoxypropylenediamine (9046-10-0)	
pH	11.7

Bisphenol A (80-05-7)	
pH	No data available in the literature

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : May damage fertility or the unborn child.

3,3'-oxybis(ethyleneoxy)bis(propylamine) (4246-51-9)	
LOAEL (animal/male, F0/P)	100 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
NOAEL (animal/male, F0/P)	< 100 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:EPA, Health Effects Test Guidelines; OPPTS 870.3650: Combined Repeated Dose Toxicity Study With the Reproduction/Developmental Toxicity Screening Test
NOAEL (animal/female, F0/P)	100 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:EPA, Health Effects Test Guidelines; OPPTS 870.3650: Combined Repeated Dose Toxicity Study With the Reproduction/Developmental Toxicity Screening Test

STOT-single exposure : Not classified

Bisphenol A (80-05-7)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

Bisphenol A (80-05-7)	
LOAEL (oral,rat,90 days)	600 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

3,3'-oxybis(ethyleneoxy)bis(propylamine) (4246-51-9)	
LOAEL (oral,rat,90 days)	100 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:

Aspiration hazard : Not classified

polyoxypropylenediamine (9046-10-0)	
Viscosity	10.9 mm²/s (20 °C, OECD 114: Viscosity of Liquids)
Bisphenol A (80-05-7)	
Viscosity	Not applicable

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Serious damage to eyes.
Symptoms/effects after ingestion : Burns.
Chronic symptoms : May damage fertility or the unborn child.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short–term (acute) : Harmful to aquatic life.
Hazardous to the aquatic environment, long–term (chronic) : Harmful to aquatic life with long lasting effects.

polyoxypropylenediamine (9046-10-0)	
LC50 - Fish [1]	772.14 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Cyprinodon variegatus, Static system, Salt water, Experimental value, GLP)

polyoxypropylenediamine (9046-10-0)	
EC50 - Crustacea [1]	80 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 72h - Algae [1]	15 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	2.1 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	15 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC (chronic)	7.64 mg/l Test organisms (species):

Bisphenol A (80-05-7)	
LC50 - Fish [1]	4.6 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	10.2 mg/l (ASTM E-35.21, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Lethal)
EC50 96h - Algae [1]	1.1 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [2]	1.4 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronic)	3.6 mg/l Test organisms (species): other:Rotifer (Brachionus calyciflorus) Duration: '48 h'

3,3'-oxybis(ethyleneoxy)bis(propylamine) (4246-51-9)	
LC50 - Fish [1]	215 – 464 mg/l (DIN 38412-15, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	218 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
LC50 - Fish [2]	215 – 464 mg/l Test organisms (species): Leuciscus idus
EC50 72h - Algae [1]	> 500 mg/l (DIN 38412-9, Scenedesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	> 1 mg/l Test organisms (species): Daphnia magna
NOEC chronic fish	> 1 mg/l Test organisms (species): Leuciscus idus

12.2. Persistence and degradability

EP1282 Black B	
Persistence and degradability	Not rapidly degradable

polyoxypropylenediamine (9046-10-0)	
Persistence and degradability	Not readily biodegradable in water.

Bisphenol A (80-05-7)	
Persistence and degradability	Readily biodegradable in the soil, Readily biodegradable in water.
Chemical oxygen demand (COD)	0.036 g O_2/g substance
ThOD	2.5 g O_2/g substance

Fatty acids, c18-unsat., dimers,polymers with 3,3'-(oxybis(2,1-ethanediyloxy))bis(1-propanamine) (68541-13-9)	
Persistence and degradability	Not rapidly degradable

3,3'-oxybis(ethyleneoxy)bis(propylamine) (4246-51-9)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

polyoxypropylenediamine (9046-10-0)	
Partition coefficient n-octanol/water (Log Pow)	1.34 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Not bioaccumulative.

Bisphenol A (80-05-7)	
BCF - Fish [1]	5.1 – 67 (42 day(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	3.4 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 21.5 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

3,3'-oxybis(ethyleneoxy)bis(propylamine) (4246-51-9)	
BCF - Fish [1]	0.89 – 3.2 (BCFBAF v3.01, Pisces, Estimated value)
Partition coefficient n-octanol/water (Log Pow)	-1.3 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

polyoxypropylenediamine (9046-10-0)	
Surface tension	Data waiving
Ecology - soil	No (test)data on mobility of the substance available.

Bisphenol A (80-05-7)	
Surface tension	No data available (test not performed)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.8 – 2.97 (log Koc, OECD 106: Adsorption/Desorption Using a Batch Equilibrium Method, Experimental value, GLP)
Ecology - soil	Low potential for adsorption in soil.

3,3'-oxybis(ethyleneoxy)bis(propylamine) (4246-51-9)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.2 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods	:	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	:	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	:	Disposal must be done according to official regulations.
Additional information	:	Do not re-use empty containers.

SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

14.1. UN number

UN-No. (DOT)	:	UN2735
UN-No. (IMDG)	:	2735
UN-No. (IATA)	:	2735

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT)	:	Polyamines, liquid, corrosive, n.o.s. (Poly(oxypropylene)diamine ; Diethylene glycol Bis(3-aminopropyl) Ether)
Proper Shipping Name (IMDG)	:	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Poly(oxypropylene)diamine ; Diethylene glycol Bis(3-aminopropyl) Ether)
Proper Shipping Name (IATA)	:	Polyamines, liquid, corrosive, n.o.s. (Poly(oxypropylene)diamine ; Diethylene glycol Bis(3-aminopropyl) Ether)

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT)	:	8
Hazard labels (DOT)	:	8

IMDG

Transport hazard class(es) (IMDG)	:	8
Hazard labels (IMDG)	:	8

IATA

Transport hazard class(es) (IATA)	:	8
Hazard labels (IATA)	:	8

14.4. Packing group

Packing group (DOT)	:	III
Packing group (IMDG)	:	III
Packing group (IATA)	:	III

14.5. Environmental hazards

Marine pollutant : Yes (IMDG only)

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN2735

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 52 - Stow ‘‘separated from’’ acids

IMDG

Special provision (IMDG) : 223, 274

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P001, LP01

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T7

Tank special provisions (IMDG) : TP1, TP28

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE

EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES

Stowage category (IMDG) : A

Segregation (IMDG) : SGG18, SG35

Properties and observations (IMDG) : Colorless to yellowish liquids or solutions with a pungent odor. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Reacts violently with acids. Cause burns to skin, eyes and mucous membranes.

IATA

Special provision (IATA) : A3, A803

PCA Excepted quantities (IATA)	:	E1
PCA Limited quantities (IATA)	:	Y841
PCA limited quantity max net quantity (IATA)	:	1L
PCA packing instructions (IATA)	:	852
PCA max net quantity (IATA)	:	5L
CAO packing instructions (IATA)	:	856
CAO max net quantity (IATA)	:	60L
ERG code (IATA)	:	8L

SECTION 15 Regulatory information

15.1. Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
polyoxypropylenediamine	9046-10-0	Present	Active	XU
Bisphenol A	80-05-7	Present	Active	
Fatty acids, c18-unsat., dimers,polymers with 3,3'-(oxybis(2,1-ethanediyloxy))bis(1-propanamine)	68541-13-9	Present	Active	XU
3,3'-oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Present	Active	

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
Bisphenol A	CAS-No. 80-05-7	5 – 10%

15.2. International regulations

CANADA

polyoxypropylenediamine (9046-10-0)

Listed on the Canadian DSL (Domestic Substances List)

Bisphenol A (80-05-7)

Listed on the Canadian DSL (Domestic Substances List)

Fatty acids, c18-unsat., dimers,polymers with 3,3'-(oxybis(2,1-ethanediyloxy))bis(1-propanamine) (68541-13-9)

Listed on the Canadian DSL (Domestic Substances List)

3,3'-oxybis(ethyleneoxy)bis(propylamine) (4246-51-9)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Bisphenol A (80-05-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

3,3'-oxybis(ethyleneoxy)bis(propylamine) (4246-51-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

polyoxypropylenediamine (9046-10-0)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Bisphenol A (80-05-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Fatty acids, c18-unsat., dimers,polymers with 3,3'-(oxybis(2,1-ethanediyloxy))bis(1-propanamine) (68541-13-9)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

3,3'-oxybis(ethyleneoxy)bis(propylamine) (4246-51-9)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

15.3. State regulations

WARNING: This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Bisphenol A(80-05-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Issue date : 6/3/2025

Full text of hazard classes and H-statements	
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H360	May damage fertility or the unborn child
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.