

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024) Issue date: 4/4/2025 Version: 1.0

SECTION 1 Identification	
1.1. Product identifier	
Product form Trade name	: Substance : EP965 Clear A
1.2. Other means of identification	
No additional information available	
1.3. Recommended use of the chemical an	nd restrictions on use
Recommended use Restrictions on use	: Epoxy resin : Product for industrial use only
1.4. Supplier's details	
ResinLab, LLC N109 W13300 Ellsworth Drive Germantown, WI, 53022 United States T 1-877-259-1669 <u>msds@resinlab.com</u> - <u>www.resinlab.com</u>	
1.5. Emergency phone number	
Emergency number	: CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International)
SECTION 2 Hazard Identification	
2.1. Classification of the substance or mix	cture
GHS US classification Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2 Skin sensitization, Category 1 Full text of H statements : see section 16	H315 Causes skin irritation.H319 Causes serious eye irritation.H317 May cause an allergic skin reaction.
2.2. Label elements	
GHS US labeling	
Hazard pictograms (GHS US)	
Signal word (GHS US) Hazard statements (GHS US)	 Warning H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation
Precautionary statements (GHS US)	 P261 - Avoid breathing dust, fume, gas, mist, vapors, spray. P264 - Wash hands, forearms and face thoroughly after handling. P272 - Contaminated work clothing must not be allowed out of the workplace. P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection. P302+P352 - If on skin: Wash with plenty of water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Name	:	Epoxy Resin
CAS-No.	:	25068-38-6

Name	Product identifier	%
Epoxy Resin	CAS-No.: 25068-38-6	≥ 90
Full text of bazard classes and H-statements : see section 16	· · · · · · · · · · · · · · · · · · ·	·

3.2. Mixtures

Not applicable

SECTION 4 First aid measures

4.1. Description of necessary first-aid me	easures
First-aid measures after inhalation First-aid measures after skin contact	 Remove person to fresh air and keep comfortable for breathing. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	 Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
4.2. Most important symptoms/effects, a	cute and delayed
Symptoms/effects after inhalation	: No effects known.
Symptoms/effects after skin contact Symptoms/effects after eye contact	: Tingling/irritation of the skin. : Irritation of the eye tissue.
Symptoms/effects after ingestion	: No effects known.
Chronic symptoms	: Skin rash/inflammation. Runny nose.
4.3. Indication of immediate medical atte	ention and special treatment needed, if necessary
Other medical advice or treatment	: Treat symptomatically.

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 5: Fire-fighting measures		
5.1. Suitable (and unsuitable) extinguishing	g media	
Suitable extinguishing media Unsuitable extinguishing media	Dry chemical. Water fog. Water spray. Foam. Dry powder.Do not use a heavy water stream.	
5.2. Specific hazards arising from the chemical		
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Not easily combustible. Heating increases the fire hazard. Reactions involving a fire hazard: see "Reactivity Hazard". No direct explosion hazard. Reactions with explosion hazards: see "Reactivity Hazard". Toxic fumes may be released. Carbon oxides (CO, CO2). 	
5.3. Special protective equipment and prec	autions for fire-fighters	
Firefighting instructions Protection during firefighting	 Complete protective clothing. Prevent fire-fighting water from entering environment. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. 	

SECTION 6 Accidental release measure	es
6.1. Personal precautions, protective equip	ment and emergency procedures
General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
For non-emergency personnel	
Protective equipment Emergency procedures	 Wear recommended personal protective equipment. Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.
For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions	: Avoid release to the environment. Prevent soil and water pollution. Prevent spreading in sewers.
6.2. Methods and materials for containment	and cleaning up
For containment	: Absorb spilled material with sand or earth. Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Take up liquid spill into absorbent material. Clean contaminated surfaces with an excess of water. This material and its container must be disposed of in a safe way, and as per local legislation.
Other information	: Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

SECTION 7 Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	 Avoid contact with skin and eyes. Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace. Provide local exhaust or general room ventilation. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Hygiene measures	: Always wash hands after handling the product. Wash contaminated clothing before reuse. Wear personal protective equipment. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
7.2. Conditions for safe storage, includi	ng incompatibilities
Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store in a well-ventilated place. Keep cool.
Storage area	: Store in a well-ventilated place. Protect from heat and direct sunlight.

: Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Packaging materials

No additional information available

8.2. Appropriate engineering controls	
Appropriate engineering controls	: Use only with adequate ventilation. Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace.
Environmental exposure controls	: Avoid release to the environment.
8.3. Individual protection measures, suc	ch as personal protective equipment
Personal protective equipment: Wear recommended personal protective equipm	ient.

Hand protection:
Wear protective gloves
Eye protection:
Safety glasses with side shields
Skin and body protection:
Wear protective clothing
Respiratory protection:
In case of inadequate ventilation, wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties	3
Physical state	: Liquid
Color	: Clear
Odor	: Mild epoxy odor
Odor threshold	: No data available
рН	: No data available
Melting point	: -16 °C (EU Method A.1: Melting/freezing point)
Freezing point	: No data available

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Boiling point	: No data available
Flash point	: 252 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: < 0.00000001 hPa (25 °C, EU Method A.4: Vapour Pressure)
Relative vapor density at 20°C	: No data available
Relative density	: 1.16 (25 °C, ASTM D4052: Density, Relative Density, and API Gravity of Liquids by Digital
	Density Meter)
Density	1.16 g/cm ³
Molecular mass	: < 700 g/mol
Solubility	: Soluble in aromatic hydrocarbons. insoluble in water. Soluble in acetone.
	Water: 3 mg/l (20 °C, EU Method A.6: Water solubility)
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: > 300 °C
Decomposition temperature	: 320 °C (EU Method A.2: Boiling point)
Viscosity	No data available
Explosion limits	: No data available
Explosive properties	: Not explosive.
Particle characteristics	: Particle size : Not applicable (liquid)

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content	:	0 %
Other properties	:	Slightly volatile.

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Acids. Amines. Mercaptans. Oxidizing agents. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11 Toxicological information		
11.1. Information on toxicologic	al effects	
Acute toxicity (oral)	: Not classified	
Acute toxicity (dermal)	: Not classified	
Acute toxicity (inhalation)	: Not classified	

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Epoxy Resin (25068-38-6)	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
Skin corrosion/irritation	: Causes skin irritation.
Epoxy Resin (25068-38-6)	
рН	No data available in the literature
Serious eye damage/irritation	: Causes serious eye irritation.
Epoxy Resin (25068-38-6)	
рН	No data available in the literature
Respiratory or skin sensitization Germ cell mutagenicity	: May cause an allergic skin reaction. : Not classified
Carcinogenicity	: Not classified
Epoxy Resin (25068-38-6)	
NOAEL (chronic,oral,animal/male,2 years)	15 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
NOAEL (chronic,oral,animal/female,2 years)	100 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Epoxy Resin (25068-38-6)	
Viscosity	No data available in the literature
Symptoms/effects after inhalation	: No effects known.
Symptoms/effects after skin contact	: Tingling/irritation of the skin.
Symptoms/effects after eye contact	: Irritation of the eye tissue.
Symptoms/effects after ingestion	: No effects known.
eymptomo, one oto and mgoodon	

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: Dangerous for the environment.
Ecology - air	: Not included in the list of substances which may contribute to the greenhouse effect (IPCC). Not
	included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014). Not
	classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Ecology - water	: Toxic to crustacea (Daphnia). Toxic to crustacea (Daphnia) with long lasting effects. Toxic to fishes. Toxic to algae.		
lazardous to the aquatic environment, short-term	: Toxic to aquatic life.		
acute)	Nuclear Stand		
Hazardous to the aquatic environment, long–term chronic)	: Not classified.		
Epoxy Resin (25068-38-6)			
LC50 - Fish [1]	1.3 mg/l (96 h, Pisces, Literature study)		
EC50 - Crustacea [1]	≈ 2 mg/l Test organisms (species): Daphnia magna		
EC50 72h - Algae [1]	9.4 mg/l (EPA 660/3 - 75/009, Selenastrum capricornutum, Static system, Fresh water, Experimental value, Biomass)		
EC50 72h - Algae [2]	> 11 mg/l Test organisms (species): Scenedesmus capricornutum		
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
12.2. Persistence and degradability			
EP965 Clear A (25068-38-6)			
Persistence and degradability	Not rapidly degradable		
Epoxy Resin (25068-38-6)			
Persistence and degradability	Not readily biodegradable in water.		
12.3. Bioaccumulative potential			
Epoxy Resin (25068-38-6)			
Partition coefficient n-octanol/water (Log Pow)	3 (Estimated value, 25 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
12.4. Mobility in soil			
Epoxy Resin (25068-38-6)			
Surface tension	59 mN/m (20 °C, 0.09 g/l)		
Ecology - soil	No (test)data on mobility of the substance available.		
12.5. Other adverse effects			
Dzone	: Not classified		
Fluorinated greenhouse gases	: No		

SECTION 13 Disposal considerations		
Regional waste regulation	: Disposal must be done according to official regulations.	
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.	
Sewage disposal recommendations	: Disposal must be done according to official regulations.	
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.	
Additional information	: Consult an expert on waste disposal or treatment.	

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 14 Transport information		
In accordance with DOT / IMDG / IATA		
14.1. UN number		
UN-No. (DOT) UN-No. (IMDG) UN-No. (IATA)	: Not regulated : 3082 : 3082	
14.2. UN Proper Shipping Name		
Proper Shipping Name (DOT) Proper Shipping Name (IMDG) Proper Shipping Name (IATA)	 Not regulated ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin) Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin) 	
14.3. Transport hazard class(es)		
DOT Transport hazard class(es) (DOT)	: Not regulated	
IMDG Transport hazard class(es) (IMDG) Hazard labels (IMDG)	: 9 : 9	
IATA Transport hazard class(es) (IATA) Hazard labels (IATA)		
14.4. Packing group		
Packing group (DOT) Packing group (IMDG) Packing group (IATA)	: Not regulated : III : III	
14.5. Environmental hazards		
Other information	: No supplementary information available.	
14.6. Transport in bulk		
Not applicable		
14.7. Special precautions for user		
DOT Not regulated		
IMDG Transport regulations (IMDG) Special provision (IMDG) Limited quantities (IMDG) Excepted quantities (IMDG)	 Subject to the provisions 274, 335, 969 5 L E1 	
4/4/2025 (logue data)	EN (English LIC) 9/4	

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Packing instructions (IMDG) Packing provisions (IMDG) IBC packing instructions (IMDG) Tank instructions (IMDG) Tank special provisions (IMDG) EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG)	 LP01, P001 PP1 IBC03 T4 TP1, TP29 F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS A
IATA Special provision (IATA) Transport regulations (IATA) PCA Excepted quantities (IATA) PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) PCA packing instructions (IATA) PCA max net quantity (IATA)	 A97, A158, A197 Subject to the provisions E1 Y964 30kgG 964 450L

Nume	CAUNO.	Listing	status	1 1495	
Epoxy Resin	25068-38-6	Present	Active	XU	

Listing

Commercial

Flags

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

CAS-No

15.2. International regulations

CAO packing instructions (IATA)

SECTION 15 Regulatory information

CAO max net quantity (IATA)

15.1. Federal regulations

ERG code (IATA)

CANADA

Name

Epoxy Resin (25068-38-6)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Epoxy Resin (25068-38-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

: 964

: 9L

: 450L

National regulations

Epoxy Resin (25068-38-6)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

15.3. State regulations

This product can expose you to chemicals including Epichlorohydrin, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024) Issue date : 4/4/2025

Full text of hazard	Full text of hazard classes and H-statements	
H315	Causes skin irritation	
H317	May cause an allergic skin reaction	
H319	Causes serious eye irritation	
H401	Toxic to aquatic life	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.