

SECTION 1: Identification

1.1. Identification

Product name : EP965LVLX Black B

1.2. Recommended use and restrictions on use

Recommended use : Epoxy hardener

1.3. Supplier

ResinLab, LLC
 N109 W13300 Ellsworth Drive
 Germantown, WI 53022 - United States
 T 1-877-259-1669
msds@resinlab.com - www.resinlab.com

1.4. Emergency telephone number

Emergency number : CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Skin corrosion/irritation Category 1B	H314	Causes severe skin burns and eye damage
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Reproductive toxicity Category 1B	H360	May damage fertility or the unborn child
Specific target organ toxicity (repeated exposure) Category 1	H372	Causes damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) :

- H302 - Harmful if swallowed
- H314 - Causes severe skin burns and eye damage
- H317 - May cause an allergic skin reaction
- H360 - May damage fertility or the unborn child
- H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :

- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 - Wash hands, forearms and face thoroughly after handling.
- P270 - Do not eat, drink or smoke when using this product.
- P272 - Contaminated work clothing must not be allowed out of the workplace.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.
- P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
- P302+P352 - If on skin: Wash with plenty of water.
- P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 - If exposed or concerned: Get medical advice/attention.
- P310 - Immediately call a poison center or doctor.
- P314 - Get medical advice/attention if you feel unwell.
- P330 - Rinse mouth.
- P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
- P363 - Wash contaminated clothing before reuse.

EP965LVLX Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P391 - Collect spillage.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
4-Nonylphenol, branched	(CAS-No.) 84852-15-3	30 – 50
N-(2-Aminoethyl)piperazine	(CAS-No.) 140-31-8	10 – 30
Benzyl alcohol	(CAS-No.) 100-51-6	10 – 30
Amine Epoxy Resin Adduct Trade Secret CAS number		5 – 10
Bisphenol A	(CAS-No.) 80-05-7	1 – 5

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a physician immediately.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
- First-aid measures after skin contact : Rinse immediately with plenty of water for 15 minutes. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Serious damage to eyes.
- Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Specific hazards arising from the chemical

- Hazardous decomposition products in case of fire : Toxic fumes may be released, Carbon oxides (CO, CO₂), Nitrogen oxides

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes and clothing.

EP965LVLX Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

4-Nonylphenol, branched (84852-15-3)

Not applicable

N-(2-Aminoethyl)piperazine (140-31-8)

Not applicable

Benzyl alcohol (100-51-6)

AIHA	WEEL TWA	10 ppm
------	----------	--------

Bisphenol A (80-05-7)

Not applicable

Amine Epoxy Resin Adduct Trade Secret CAS number

Not applicable

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses with side shields

Skin and body protection:

Wear suitable protective clothing

EP965LVLX Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection:

In case of inadequate ventilation, wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Amber
Odor	: Amine-like
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 93 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 0.98 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
VOC content	No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Alkaline Metals. Strong acids. Strong oxidizing agents. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Refer to section 5.2 for hazardous decomposition products during combustion.

EP965LVLX Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

ATE US (oral)	1666.811 mg/kg body weight
---------------	----------------------------

4-Nonylphenol, branched (84852-15-3)

LD50 oral rat	1412 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 14 day(s))
ATE US (oral)	1412 mg/kg body weight

N-(2-Aminoethyl)piperazine (140-31-8)

LD50 oral rat	2097 mg/kg body weight (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	866 mg/kg bw/day (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
ATE US (oral)	2097 mg/kg body weight
ATE US (dermal)	866 mg/kg body weight

Benzyl alcohol (100-51-6)

LD50 oral rat	1620 mg/kg bw/day (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (EPA OTS 798.1100, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 4178 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
ATE US (oral)	1580 mg/kg body weight

Bisphenol A (80-05-7)

LD50 oral rat	2000 – 5000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	3000 mg/kg body weight (Rabbit, Experimental value, Dermal)
ATE US (oral)	2000 mg/kg body weight
ATE US (dermal)	3000 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Assumed to cause serious eye damage
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : May damage fertility or the unborn child.
STOT-single exposure : Not classified

Bisphenol A (80-05-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

Amine Epoxy Resin Adduct Trade Secret CAS number

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

4-Nonylphenol, branched (84852-15-3)

LOAEL (oral,rat,90 days)	400 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (oral,rat,90 days)	100 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

N-(2-Aminoethyl)piperazine (140-31-8)

STOT-repeated exposure	Causes damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation).
------------------------	---

EP965LVLX Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzyl alcohol (100-51-6)	
NOAEL (oral,rat,90 days)	400 mg/kg body weight Animal: rat, Guideline: other:OECD Guideline 451 (Carcinogenicity Studies)
Bisphenol A (80-05-7)	
LOAEL (oral,rat,90 days)	600 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Amine Epoxy Resin Adduct Trade Secret CAS number	
STOT-repeated exposure	Causes damage to organs (Skin, respiratory tract) through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

4-Nonylphenol, branched (84852-15-3)	
EC50 - Crustacea [1]	84 µg/l (ASTM E729-88, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Lethal)
NOEC chronic fish	0.006 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '91 d'
N-(2-Aminoethyl)piperazine (140-31-8)	
LC50 - Fish [1]	2190 mg/l (96 h, Pimephales promelas, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	58 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Experimental value, GLP)
ErC50 algae	> 1000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Fresh water, Experimental value, GLP)
Benzyl alcohol (100-51-6)	
LC50 - Fish [1]	460 mg/l (EPA OPP 72-1, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	230 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	770 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC (chronic)	51 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	48897 mg/l Test organisms (species): other: Duration: '30 d'
Bisphenol A (80-05-7)	
LC50 - Fish [1]	4.6 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	10.2 mg/l (ASTM E-35.21, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Lethal)
LOEC (chronic)	3.6 mg/l Test organisms (species): other:Rotifer (Brachionus calyciflorus) Duration: '48 h'

12.2. Persistence and degradability

4-Nonylphenol, branched (84852-15-3)	
Persistence and degradability	Not readily biodegradable in water.
N-(2-Aminoethyl)piperazine (140-31-8)	
Persistence and degradability	Not readily biodegradable in water.
Chemical oxygen demand (COD)	0.56 g O ₂ /g substance
Benzyl alcohol (100-51-6)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Bisphenol A (80-05-7)	
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
Chemical oxygen demand (COD)	0.036 g O ₂ /g substance

EP965LVLX Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Bisphenol A (80-05-7)	
ThOD	2.5 g O ₂ /g substance

12.3. Bioaccumulative potential

4-Nonylphenol, branched (84852-15-3)	
BCF - Fish [1]	1200 – 1300 (Equivalent or similar to OECD 305, 16 day(s), Gasterosteus aculeatus, Flow-through system, Salt water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	5.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

N-(2-Aminoethyl)piperazine (140-31-8)	
BCF - Fish [1]	0.3 – 6.3 (OECD 305: Bioconcentration: Flow-Through Fish Test, 6 week(s), Cyprinus carpio, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	-1.48 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Benzyl alcohol (100-51-6)	
BCF - Fish [1]	1.4 l/kg (BCFBAF v3.01, Estimated value)
Partition coefficient n-octanol/water (Log Pow)	1 – 1.1 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Bisphenol A (80-05-7)	
BCF - Fish [1]	5.1 – 67 (42 day(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	3.4 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 21.5 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

4-Nonylphenol, branched (84852-15-3)	
Surface tension	38.9 mN/m (20 °C, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	4 (log Koc, Calculated value)
Ecology - soil	Low potential for mobility in soil.

N-(2-Aminoethyl)piperazine (140-31-8)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	4.57 (log Koc, Read-across, GLP)
Ecology - soil	Low potential for mobility in soil.

Benzyl alcohol (100-51-6)	
Surface tension	39 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.1 – 1.3 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

Bisphenol A (80-05-7)	
Surface tension	No data available (test not performed)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.8 – 2.97 (log Koc, OECD 106: Adsorption/Desorption Using a Batch Equilibrium Method, Experimental value, GLP)
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

No additional information available

EP965LVLX Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : UN3267 Corrosive liquid, basic, organic, n.o.s. (4-Nonylphenol, branched ; N-(2-Aminoethyl)piperazine), 8, II

UN-No.(DOT) : UN3267

Proper Shipping Name (DOT) : Corrosive liquid, basic, organic, n.o.s.
4-Nonylphenol, branched ; N-(2-Aminoethyl)piperazine

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger

Hazard labels (DOT) : 8 - Corrosive



Dangerous for the environment : Yes

Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids

Emergency Response Guide (ERG) Number : 153

EP965LVLX Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (4-Nonylphenol, branched ; N-(2-Aminoethyl)piperazine), 8, II

UN-No. (IMDG) : 3267
CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
4-Nonylphenol, branched ; N-(2-Aminoethyl)piperazine

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : II - substances presenting medium danger

Limited quantities (IMDG) : 1 L

Marine pollutant : Yes



Air transport

Transport document description (IATA) : UN 3267 Corrosive liquid, basic, organic, n.o.s. (4-Nonylphenol, branched ; N-(2-Aminoethyl)piperazine), 8, II

UN-No. (IATA) : 3267

Proper Shipping Name (IATA) : Corrosive liquid, basic, organic, n.o.s.
4-Nonylphenol, branched ; N-(2-Aminoethyl)piperazine

Class (IATA) : 8 - Corrosives

Packing group (IATA) : II - Medium danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

4-Nonylphenol, branched	CAS-No. 84852-15-3	30 – 50%
Bisphenol A	CAS-No. 80-05-7	1 – 5%

4-Nonylphenol, branched (84852-15-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

EPA TSCA Regulatory Flag : SP - SP - indicates a substance that is identified in a proposed Significant New Use Rule.

N-(2-Aminoethyl)piperazine (140-31-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Benzyl alcohol (100-51-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Bisphenol A (80-05-7)

Subject to reporting requirements of United States SARA Section 313

15.2. International regulations

CANADA

4-Nonylphenol, branched (84852-15-3)

Listed on the Canadian DSL (Domestic Substances List)

N-(2-Aminoethyl)piperazine (140-31-8)

Listed on the Canadian DSL (Domestic Substances List)

EP965LVLX Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzyl alcohol (100-51-6)

Listed on the Canadian DSL (Domestic Substances List)

Bisphenol A (80-05-7)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Contains the following REACH ingredient(s): 4-Nonylphenol, branched (EC 284-325-5, CAS 84852-15-3), Bisphenol A (EC 201-245-8, CAS 80-05-7)

4-Nonylphenol, branched (84852-15-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

N-(2-Aminoethyl)piperazine (140-31-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Benzyl alcohol (100-51-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Bisphenol A (80-05-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

4-Nonylphenol, branched (84852-15-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

N-(2-Aminoethyl)piperazine (140-31-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Benzyl alcohol (100-51-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Bisphenol A (80-05-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Amine Epoxy Resin Adduct Trade Secret CAS number

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.3. US State regulations

⚠ WARNING: This product can expose you to Bisphenol A (BPA), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
N-(2-Aminoethyl)piperazine(140-31-8)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Benzyl alcohol(100-51-6)	U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List

EP965LVLX Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Bisphenol A(80-05-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 06/11/2024

Full text of H-phrases:

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H360	May damage fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

SDS US - ResinLab

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.