

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024) Issue date: 5/20/2025 Version: 1.0

### **SECTION 1 Identification**

### 1.1. Product identifier

Product form : Mixture

Product name : EP965SC7 Clear B

### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Epoxy hardener

Restrictions on use : Product for industrial use only

### 1.4. Supplier's details

ResinLab, LLC N109 W13300 Ellsworth Drive Germantown, WI, 53022 United States T 1-877-259-1669

msds@resinlab.com - www.resinlab.com

#### 1.5. Emergency phone number

Emergency number : CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International)

# **SECTION 2 Hazard Identification**

### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Skin corrosion/irritation, Category 1B H314 Causes severe skin burns and eye damage.

Skin sensitization, Category 1 H317 May cause an allergic skin reaction.

Reproductive toxicity, Category 2 H361 Suspected of damaging fertility or the unborn child.

Specific target organ toxicity — Repeated exposure, Category H372 Causes damage to organs through prolonged or repeated exposure.

Full text of H statements : see section 16

### 2.2. Label elements

### **GHS US labeling**

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H361 - Suspected of damaging fertility or the unborn child

H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dusts or mists.

P264 - Wash hands, forearms and face thoroughly after handling.

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

 ${\tt P305+P351+P338-IF\ IN\ EYES: Rinse\ cautiously\ with\ water\ for\ several\ minutes.\ Remove}$ 

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a poison center or doctor.

P314 - Get medical advice or attention if you feel unwell.

P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P391 - Collect spillage.

P405 - Store locked up.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

No additional information available

### **SECTION 3 Composition/information on ingredients**

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	CAS-No.: 68082-29-1	30 – 50
Benzyl alcohol	CAS-No.: 100-51-6	15 - 20
4-Nonylphenol, branched	CAS-No.: 84852-15-3	10 – 30
Isophorone diamine	CAS-No.: 2855-13-2	10 - 20
Amine Epoxy Resin Adduct	CAS-No.: Proprietary	10 - 20
Triethylenetetramine	CAS-No.: 112-24-3	1 – 5

Full text of hazard classes and H-statements : see section 16

### Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

#### **SECTION 4 First aid measures**

### 4.1. Description of necessary first-aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse immediately with plenty of water for 15 minutes. Remove/Take off immediately all

contaminated clothing. Get immediate medical advice/attention. Thoroughly clean shoes before

reuse. Wash clothing before reuse.

First-aid measures after eye contact : Immediately rinse with plenty of water (for at least 15 minutes). Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Rinse mouth out with water. Do not induce vomiting. Call a physician immediately. Never give

anything by mouth to an unconscious person.

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

### **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use water jet to extinguish.

### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

### **SECTION 6 Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin

and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Environmental precautions : Avoid release to the environment.

# 6.2. Methods and materials for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

5/20/2025 (Issue date) EN (English US) 3/16

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

### **SECTION 7 Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the

workplace. Obtain special instructions before use. Do not handle until all safety precautions have

been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed

out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands

after handling the product.

### 7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

### **SECTION 8 Exposure controls/personal protection**

### 8.1. Control parameters

Triethylenetetramine (112-24-3)
USA - AIHA - Occupational Exposure Limits

WEEL TWA 1 ppm (skin)

Benzyl alcohol (100-51-6)

**USA - AIHA - Occupational Exposure Limits** 

WEEL TWA 10 ppm

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the

workplace.

Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures, such as personal protective equipment

### Hand protection:

Protective gloves

### Eye protection:

Safety glasses with side shields

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

In case of inadequate ventilation, wear respiratory protection.

5/20/2025 (Issue date) EN (English US) 4/16

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### Personal protective equipment symbol(s):







# **SECTION 9 Physical and chemical properties**

### 9.1. Basic physical and chemical properties

: Liquid Physical state : Amber Color : Amine-like Odor Odor threshold : No data available pΗ : No data available Melting point : Not applicable Freezing point : No data available Boiling point : > 176 °C : > 93 °C Flash point Flammability (solid, gas) : Not applicable. Vapor pressure No data available Relative vapor density at 20°C No data available : No data available Relative density : 0.98 g/cm<sup>3</sup> Density : Not miscible. Solubility Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available : No data available Decomposition temperature

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

: No data available

No data available

No data available

VOC content : 20 %

# **SECTION 10 Stability and reactivity**

#### 10.1. Reactivity

Viscosity

**Explosion limits** 

Particle characteristics

The product is non-reactive under normal conditions of use, storage and transport.

# 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Bases (Alkalis). Acids. Oxidizing agents. May slowly corrode copper, aluminum, zinc, and galvanized surfaces. Peroxides. N-Nitrosamines, many of which are known to be potent carcinogens, may be formed when the product comes in contact with nitrous acid, nitrites or atmospheres with high nitrous oxide concentrations.

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

# 10.6. Hazardous decomposition products

ammonia. Carbon oxides (CO, CO2). Nitrogen oxides.

# **SECTION 11 Toxicological information**

# 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (illinatation)	Not classified				
4-Nonylphenol, branched (84852-15-3)					
LD50 oral rat	1412 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 14 day(s))				
ATE US (oral)	1412 mg/kg body weight				
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine (68082-29-1)					
LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))				
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))				
Triethylenetetramine (112-24-3)					
LD50 oral rat	1716 mg/kg body weight (BASF test, Rat, Experimental value, Oral)				
LD50 dermal rabbit	1465 mg/kg body weight (BASF test, Rabbit, Experimental value, Dermal)				
ATE US (oral)	1716 mg/kg body weight				
ATE US (dermal)	1465 mg/kg body weight				
Isophorone diamine (2855-13-2)					
LD50 oral rat	1030 mg/kg (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))				
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))				
LC50 Inhalation - Rat	> 5.01 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))				
ATE US (oral)	1030 mg/kg body weight				
Benzyl alcohol (100-51-6)					
LD50 oral rat	1620 mg/kg bw/day (Rat, Male, Experimental value, Oral, 14 day(s))				
LD50 oral	1580 mg/kg body weight Animal: mouse, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1410 - 1770				
LD50 dermal rabbit	> 2000 mg/kg body weight (EPA OTS 798.1100, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))				
LC50 Inhalation - Rat	> 4178 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:				
ATE US (oral)	1580 mg/kg body weight				
	I control of the cont				

Skin corrosion/irritation : Causes severe skin burns.

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

4-Nonylphenol, branched (84852-15-3)				
рН	No data available in the literature			
Fatty acids, C18-unsatd., dimers, oligomeric	c reaction products with tall-oil fatty acids and triethylenetetramine (68082-29-1)			
рН	10.98 (1 %, 25 °C, CIPAC MT 75: Determination of pH)			
Triethylenetetramine (112-24-3)				
рН	10.7			
Isophorone diamine (2855-13-2)				
рН	11.6			
Benzyl alcohol (100-51-6)				
рН	No data available in the literature			
Serious eye damage/irritation	: Assumed to cause serious eye damage			
4-Nonylphenol, branched (84852-15-3)	No data available in the literature			
<u> </u>				
	c reaction products with tall-oil fatty acids and triethylenetetramine (68082-29-1)			
pH	10.98 (1 %, 25 °C, CIPAC MT 75: Determination of pH)			
Triethylenetetramine (112-24-3)				
pH	10.7			
Isophorone diamine (2855-13-2)				
рН	11.6			
Benzyl alcohol (100-51-6)				
рН	No data available in the literature			
Respiratory or skin sensitization Germ cell mutagenicity	May cause an allergic skin reaction.     Not classified			
Carcinogenicity	: Not classified			
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.			
4-Nonylphenol, branched (84852-15-3)				
NOAEL (animal/female, F0/P)	15 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study), Remarks on results: other:Generation: All generations tested: F0, F1, F2, F3 (migrated information)			
NOAEL (animal/male, F1)	15 mg/kg body weight Animal: rat, Animal sex: male, Guideline: other:EPA OPPTS 837.3800 (US EPA OPPTS 1998)			
STOT-single exposure	: Not classified			
Amine Epoxy Resin Adduct (Proprietary)				
STOT-single exposure	May cause respiratory irritation.			
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.			
4-Nonylphenol, branched (84852-15-3)				
LOAEL (oral,rat,90 days)	400 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)			

5/20/2025 (Issue date) EN (English US) 7/16

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

4-Nonylphenol, branched (84852-15-3)		
NOAEL (oral,rat,90 days)	100 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Fatty acids, C18-unsatd., dimers, oligon	neric reaction products with tall-oil fatty acids and triethylenetetramine (68082-29-1)	
NOAEL (oral,rat,90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)	
Isophorone diamine (2855-13-2)		
LOAEL (oral,rat,90 days)	160 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)	
Benzyl alcohol (100-51-6)		
NOAEL (oral,rat,90 days)	400 mg/kg body weight Animal: rat, Guideline: other:OECD Guideline 451 (Carcinogenicity Studies)	
Amine Epoxy Resin Adduct (Proprietary	)	
STOT-repeated exposure	Causes damage to organs (Skin, Respiratory tract) through prolonged or repeated exposure.	
Aspiration hazard	: Not classified	
4-Nonylphenol, branched (84852-15-3)		
Viscosity	No data available in the literature	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine (68082-29-1)		
Viscosity	No data available in the literature	
Triethylenetetramine (112-24-3)		
Viscosity	No data available in the literature	
Isophorone diamine (2855-13-2)		
Viscosity	19 mm²/s (20 °C, OECD 114: Viscosity of Liquids)	
Benzyl alcohol (100-51-6)	·	
Viscosity	No data available in the literature	
Symptoms/effects after skin contact Symptoms/effects after eye contact Symptoms/effects after ingestion	Burns. May cause an allergic skin reaction.     Serious damage to eyes.     Burns.	

# **SECTION 12 Ecological information**

-		_				
и	7) 1		CC	t O	VIC	ity
	4.	_		ľ	$\lambda_{1}$	ILY

Ecology - general	:	Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Ecology - water	:	Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.
I lampuda un ta tiba anuatia anuinananant abant tanna	_	Vanctaria ta agrestia lifa

Hazardous to the aquatic environment, short–term : Very toxic to aquatic life.

(acute)

Hazardous to the aquatic environment, long-term : Very toxic to aquatic life with long lasting effects.

(chronic)

4-Nonylphenol, branched (84852-15-3)		
EC50 - Crustacea [1]	84 μg/l (ASTM E729-88, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Lethal)	

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

4-Nonylphenol, branched (84852-15-3)			
EC50 72h - Algae [1]	0.33 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)		
EC50 96h - Algae [1]	0.027 mg/l (EPA OTS 797.1050, Skeletonema costatum, Static system, Salt water, Experimental value, Cell numbers)		
EC50 96h - Algae [2]	0.41 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)		
NOEC chronic fish	0.006 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '91 d'		
Fatty acids, C18-unsatd., dimers, oligomeric i	reaction products with tall-oil fatty acids and triethylenetetramine (68082-29-1)		
LC50 - Fish [1]	7.07 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, Nominal concentration)		
EC50 - Crustacea [1]	7.07 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)		
EC50 72h - Algae [1]	4.34 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)		
ErC50 algae	4.34 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Experimental value, Nominal concentration)		
Triethylenetetramine (112-24-3)			
LC50 - Fish [1]	495 mg/l (96 h, Pimephales promelas, Fresh water, Literature study)		
EC50 - Crustacea [1]	31.1 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Literature study)		
Isophorone diamine (2855-13-2)			
LC50 - Fish [1]	110 mg/l (EU Method C.1, 96 h, Leuciscus idus, Semi-static system, Fresh water, Experimental value, Nominal concentration)		
EC50 - Crustacea [1]	23 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)		
EC50 72h - Algae [1]	37 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)		
EC50 72h - Algae [2]	> 50 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)		
ErC50 algae	> 50 mg/l (EU Method C.3, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)		
LOEC (chronic)	10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC (chronic)	3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
Benzyl alcohol (100-51-6)			
LC50 - Fish [1]	460 mg/l (EPA OPP 72-1, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Nominal concentration)		
EC50 - Crustacea [1]	230 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Fresh water, Experimental value, Locomotor effect)		
EC50 72h - Algae [1]	770 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)		
EC50 72h - Algae [2]	500 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)		

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Benzyl alcohol (100-51-6)		
EC50 96h - Algae [1]	76828 mg/l Test organisms (species): other:	
ErC50 algae	770 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)	
NOEC (chronic)	51 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC chronic fish	48897 mg/l Test organisms (species): other: Duration: '30 d'	

# 12.2. Persistence and degradability

EP965SC7 Clear B		
Persistence and degradability	Not rapidly degradable	
4-Nonylphenol, branched (84852-15-3)		
Persistence and degradability	Not readily biodegradable in water.	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine (68082-29-1)		
Persistence and degradability	Not readily biodegradable in water.	
Triethylenetetramine (112-24-3)		
Persistence and degradability	Not readily biodegradable in water.	
Isophorone diamine (2855-13-2)		
Persistence and degradability	Not readily biodegradable in water.	
Benzyl alcohol (100-51-6)		
Persistence and degradability	Biodegradable in the soil, Readily biodegradable in water.	
Amine Epoxy Resin Adduct (Proprietary)		
Persistence and degradability	Not rapidly degradable	

# 12.3. Bioaccumulative potential

4-Nonylphenol, branched (84852-15-3)		
BCF - Fish [1]	1200 – 1300 (Equivalent or similar to OECD 305, 16 day(s), Gasterosteus aculeatus, Flow-through system, Salt water, Experimental value, Fresh weight)	
Partition coefficient n-octanol/water (Log Pow)	5.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 23 °C)	
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine (68082-29-1)		
BCF - Other aquatic organisms [1]	77.4 l/kg (BCFBAF v3.01, QSAR, Fresh weight)	
Partition coefficient n-octanol/water (Log Pow)	0.3 – 3.55 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Triethylenetetramine (112-24-3)		
Partition coefficient n-octanol/water (Log Pow)	-2.65 (Estimated value, KOWWIN)	
Bioaccumulative potential	Not bioaccumulative.	

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Isophorone diamine (2855-13-2)			
BCF - Fish [1]	1.8 – 3.2 (BCFBAF v3.01, Pisces, Estimated value)		
Partition coefficient n-octanol/water (Log Pow)	0.99 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 23 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
Benzyl alcohol (100-51-6)			
BCF - Fish [1]	1.4 l/kg (BCFBAF v3.01, Estimated value)		
Partition coefficient n-octanol/water (Log Pow)	1 – 1.1 (Experimental value, 20 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		

# 12.4. Mobility in soil

4-Nonylphenol, branched (84852-15-3)				
Surface tension	38.9 mN/m (20 °C, EU Method A.5: Surface tension)			
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	4 (log Koc, Calculated value)			
Ecology - soil	Low potential for mobility in soil.			
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine (68082-29-1)				
Surface tension	63.93 mN/m (23 °C, 0.15 g/l, EU Method A.5: Surface tension)			
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	6.5 – 8.6 (log Koc, SRC PCKOCWIN v2.0, Calculated value)			
Ecology - soil	Adsorbs into the soil.			
Triethylenetetramine (112-24-3)				
Surface tension	No data available in the literature			
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.885 (log Koc, SRC PCKOCWIN v2.0, Calculated value)			
Ecology - soil	Highly mobile in soil.			
Isophorone diamine (2855-13-2)				
Surface tension	34.7 mN/m (23 °C)			
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.6 – 2.3 (log Koc, SRC PCKOCWIN v2.0, Calculated value)			
Ecology - soil	Low potential for adsorption in soil.			
Benzyl alcohol (100-51-6)				
Surface tension	39 mN/m (20 °C)			
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.1 – 1.3 (log Koc, SRC PCKOCWIN v2.0, Calculated value)			
Ecology - soil	Highly mobile in soil.			

# 12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### **SECTION 13 Disposal considerations**

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

# **SECTION 14 Transport information**

In accordance with DOT / IMDG / IATA

### 14.1. UN number

UN-No. (DOT) : UN3267 UN-No. (IMDG) : 3267 UN-No. (IATA) : 3267

### 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Corrosive liquid, basic, organic, n.o.s. (4-Nonylphenol, branched; Isophorone diamine)
Proper Shipping Name (IMDG) : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (4-Nonylphenol, branched; Isophorone

diamine)

Proper Shipping Name (IATA) : Corrosive liquid, basic, organic, n.o.s. (4-Nonylphenol, branched; Isophorone diamine)

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



### **IMDG**

Transport hazard class(es) (IMDG) : 8
Hazard labels (IMDG) : 8



#### IATA

Transport hazard class(es) (IATA) : 8
Hazard labels (IATA) : 8



### 14.4. Packing group

Packing group (DOT) : III
Packing group (IMDG) : III
Packing group (IATA) : III

# 14.5. Environmental hazards

Dangerous for the environment : Yes

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Marine pollutant : Yes



Other information : No supplementary information available.

#### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

DOT

UN-No. (DOT) : UN3267

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table

2 for UN2672).

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Quantity Limitations Passenger aircraft/rail (49 : 5 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters",52 - Stow "separated from" acids

**IMDG** 

Special provision (IMDG): 223, 274Limited quantities (IMDG): 5 LExcepted quantities (IMDG): E1Packing instructions (IMDG): P001, LP01IBC packing instructions (IMDG): IBC03

Tank instructions (IMDG) : To

Tank special provisions (IMDG) : TP1, TP28

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES

Stowage category (IMDG) : A Stowage and handling (IMDG) : SW2

Segregation (IMDG) : SGG18, SG35

Properties and observations (IMDG) : Reacts violently with acids. Causes burns to skin, eyes and mucous membranes.

**IATA** 

Special provision (IATA) : A3, A803
PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y841
PCA limited quantity max net quantity (IATA) : 1L

5/20/2025 (Issue date) EN (English US) 13/16

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

PCA packing instructions (IATA) : 852
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 856
CAO max net quantity (IATA) : 60L
ERG code (IATA) : 8L

### **SECTION 15 Regulatory information**

### 15.1. Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
4-Nonylphenol, branched	84852-15-3	Present	Active	SP
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	68082-29-1	Present	Active	XU
Triethylenetetramine	112-24-3	Present	Active	
Isophorone diamine	2855-13-2	Present	Active	
Benzyl alcohol	100-51-6	Present	Active	
Amine Epoxy Resin Adduct	Proprietary	Not present	-	

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

4-Nonylphenol, branched CAS-No. 84852-15-3 10 – 30%

## 15.2. International regulations

### CANADA

### **4-Nonylphenol**, branched (84852-15-3)

Listed on the Canadian DSL (Domestic Substances List)

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine (68082-29-1)

Listed on the Canadian DSL (Domestic Substances List)

## **Triethylenetetramine (112-24-3)**

Listed on the Canadian DSL (Domestic Substances List)

### Isophorone diamine (2855-13-2)

Listed on the Canadian DSL (Domestic Substances List)

### Benzyl alcohol (100-51-6)

Listed on the Canadian DSL (Domestic Substances List)

### Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

#### **EU-Regulations**

### 4-Nonylphenol, branched (84852-15-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine (68082-29-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### **Triethylenetetramine (112-24-3)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### Isophorone diamine (2855-13-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### Benzyl alcohol (100-51-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### National regulations

#### 4-Nonylphenol, branched (84852-15-3)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

### Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine (68082-29-1)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

### **Triethylenetetramine (112-24-3)**

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

### Isophorone diamine (2855-13-2)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

#### Benzyl alcohol (100-51-6)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

### 15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Triethylenetetramine(112-24-3)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Isophorone diamine(2855-13-2)	U.S New Jersey - Right to Know Hazardous Substance List
Benzyl alcohol(100-51-6)	U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) List

# **SECTION 16 Other information**

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Issue date : 5/20/2025

Full text of hazard classes and H-statements		
H314	Causes severe skin burns and eye damage	
H317	May cause an allergic skin reaction	
H361	Suspected of damaging fertility or the unborn child	
H372	Causes damage to organs through prolonged or repeated exposure	
H400	Very toxic to aquatic life	
H410	Very toxic to aquatic life with long lasting effects	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.