

SECTION 1: Identification

1.1. Identification

Product name : EP1285 Black A

1.2. Recommended use and restrictions on use

Recommended use : Epoxy resin
 Restrictions on use : Product for industrial use only

1.3. Supplier

ResinLab, LLC
 N109 W13300 Ellsworth Drive
 Germantown, WI 53022 - United States
 T 1-877-259-1669
msds@resinlab.com - www.resinlab.com

1.4. Emergency telephone number

Emergency number : CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Germ cell mutagenicity Category 2	H341	Suspected of causing genetic defects
Carcinogenicity Category 2	H351	Suspected of causing cancer

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction
 H319 - Causes serious eye irritation
 H341 - Suspected of causing genetic defects
 H351 - Suspected of causing cancer

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
 P264 - Wash hands, forearms and face thoroughly after handling.
 P272 - Contaminated work clothing must not be allowed out of the workplace.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 - If on skin: Wash with plenty of water.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P405 - Store locked up.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

EP1285 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
aluminum oxide	(CAS-No.) 1344-28-1	50 – 75	Not classified
Epoxy Resin	(CAS-No.) 25068-38-6	10 – 30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Butylglycidylether	(CAS-No.) 2426-08-6	1 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 Muta. 2, H341 Carc. 2, H351 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
carbon black	(CAS-No.) 1333-86-4	0.1 – 0.5	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Get medical advice/attention if you feel unwell. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Specific hazards arising from the chemical

- Hazardous decomposition products in case of fire : Toxic fumes may be released, Carbon oxides (CO, CO₂), Phenolic compounds

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

EP1285 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Contains a component(s) that is encapsulated within the product and not expected to be released during normal processing conditions or a foreseeable emergency. Do not breathe dust created by sanding, grinding or machining.

Precautions for safe handling : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Epoxy Resin (25068-38-6)		
Not applicable		
carbon black (1333-86-4)		
ACGIH	Local name	Carbon black
ACGIH	ACGIH OEL TWA	3 mg/m ³ (Inhalable fraction)
ACGIH	Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) [1]	3.5 mg/m ³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
aluminum oxide (1344-28-1)		
ACGIH	ACGIH OEL TWA	1 mg/m ³ (Respirable fraction)
OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Butylglycidylether (2426-08-6)		
ACGIH	Local name	n-Butyl glycidyl ether (BGE)
ACGIH	ACGIH OEL TWA [ppm]	3 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Reproduction; sens. Notations: Skin; DSEN
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) [1]	270 mg/m ³

EP1285 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Butylglycidylether (2426-08-6)		
OSHA	OSHA PEL (TWA) [2]	50 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses with side shields

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation, wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Black
Odor	: Mild epoxy odor
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 93 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 2.42 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

EP1285 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

VOC content

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Bases (Alkalis). Acids. Oxidizing agent. Ethylene oxide. Chlorine trifluoride.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Epoxy Resin (25068-38-6)	
LD50 oral rat	> 2000 mg/kg (OECD 420: Acute Oral toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
carbon black (1333-86-4)	
LD50 oral rat	> 10000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 28 day(s))
LD50 dermal rabbit	> 8000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust))
aluminum oxide (1344-28-1)	
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LC50 Inhalation - Rat	7.6 mg/l air (Equivalent or similar to OECD 403, 1 h, Rat, Male, Experimental value, Inhalation (aerosol))
Butylglycidylether (2426-08-6)	
LD50 dermal rabbit	778 mg/kg body weight (24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	1030 ppm (8 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE US (oral)	1530 mg/kg body weight
ATE US (dermal)	778 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Suspected of causing genetic defects.
Carcinogenicity	: Suspected of causing cancer.

EP1285 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Epoxy Resin (25068-38-6)	
NOAEL (chronic,oral,animal/male,2 years)	15 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
NOAEL (chronic,oral,animal/female,2 years)	100 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)

carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans

Butylglycidylether (2426-08-6)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

Butylglycidylether (2426-08-6)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified

Epoxy Resin (25068-38-6)	
NOAEL (oral, rat, 90 days)	50 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: other:japanese MITI guidelines for toxicity testing of chemicals

carbon black (1333-86-4)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0071 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	> 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0011 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

aluminum oxide (1344-28-1)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.015 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard	: Not classified
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Ecology - water	: Harmful to aquatic life with long lasting effects.

Epoxy Resin (25068-38-6)	
LC50 - Fish [1]	2.3 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	2 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

EP1285 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

carbon black (1333-86-4)	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
aluminum oxide (1344-28-1)	
LC50 - Fish [1]	> 100 mg/l
Butylglycidylether (2426-08-6)	
LC50 - Fish [1]	65 mg/l (96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	9.2 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	35 mg/l (96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

Epoxy Resin (25068-38-6)	
Persistence and degradability	Not readily biodegradable in water.
carbon black (1333-86-4)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
aluminum oxide (1344-28-1)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
BOD (% of ThOD)	Not applicable
Butylglycidylether (2426-08-6)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

Epoxy Resin (25068-38-6)	
BCF - Other aquatic organisms [1]	31 (Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	3 (Estimated value, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
carbon black (1333-86-4)	
Bioaccumulative potential	Not bioaccumulative.
aluminum oxide (1344-28-1)	
Bioaccumulative potential	No bioaccumulation data available.
Butylglycidylether (2426-08-6)	
Partition coefficient n-octanol/water (Log Pow)	0.63 (Literature)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Epoxy Resin (25068-38-6)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.
carbon black (1333-86-4)	
Surface tension	Not applicable (solid)
Ecology - soil	No (test)data on mobility of the substance available. Not toxic to plants. Not toxic to animals.

EP1285 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminum oxide (1344-28-1)	
Ecology - soil	No (test)data on mobility of the substance available.
Butylglycidylether (2426-08-6)	
Surface tension	No data available (test not performed)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.092 – 1.167 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin), 9, III
UN-No. (IMDG) : 3082
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Epoxy Resin
Class (IMDG) : 9 - Miscellaneous dangerous substances and articles
Packing group (IMDG) : III - substances presenting low danger
Limited quantities (IMDG) : 5 L

Air transport

Transport document description (IATA) : UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin), 9, III
UN-No. (IATA) : 3082
Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s.
Epoxy Resin
Class (IATA) : 9 - Miscellaneous Dangerous Substances and Articles
Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

aluminum oxide	CAS-No. 1344-28-1	50 – 75%
----------------	-------------------	----------

Epoxy Resin (25068-38-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

EP1285 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminum oxide (1344-28-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

Butylglycidylether (2426-08-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Epoxy Resin (25068-38-6)

Listed on the Canadian DSL (Domestic Substances List)

carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

aluminum oxide (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

Butylglycidylether (2426-08-6)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Contains no REACH candidate substance

National regulations


carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Butylglycidylether (2426-08-6)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

 **WARNING:** This product can expose you to 1-chloro-2,3-epoxypropane, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
carbon black(1333-86-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
aluminum oxide(1344-28-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Butylglycidylether(2426-08-6)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EP1285 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H302	Harmful if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H341	Suspected of causing genetic defects
H351	Suspected of causing cancer
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS US - ResinLab

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.