

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : EP1200 Black B

1.2. Recommended use and restrictions on use

Recommended use : Epoxy hardener
 Restrictions on use : Product for industrial use only

1.3. Supplier

ResinLab, LLC
 N109 W13300 Ellsworth Drive
 Germantown, WI 53022 - United States
 T 1-877-259-1669
msds@resinlab.com - www.resinlab.com

1.4. Emergency telephone number

Emergency number : CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

| | | |
|---|------|---|
| Skin corrosion/irritation Category 1B | H314 | Causes severe skin burns and eye damage |
| Skin sensitization, Category 1 | H317 | May cause an allergic skin reaction |
| Reproductive toxicity Category 2 | H361 | Suspected of damaging fertility or the unborn child |
| Specific target organ toxicity (repeated exposure) Category 2 | H373 | May cause damage to organs through prolonged or repeated exposure |

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms
 (GHS US)



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage
 H317 - May cause an allergic skin reaction
 H361 - Suspected of damaging fertility or the unborn child
 H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
 P264 - Wash hands, forearms and face thoroughly after handling.
 P272 - Contaminated work clothing must not be allowed out of the workplace.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
 P302+P352 - If on skin: Wash with plenty of water.
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P310 - Immediately call a poison center or doctor.
 P314 - Get medical advice/attention if you feel unwell.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P363 - Wash contaminated clothing before reuse.
 P391 - Collect spillage.

EP1200 Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS US classification |
|---------------------------------|----------------------|---------|---|
| 4-Nonylphenol, branched | (CAS-No.) 84852-15-3 | 10 – 30 | Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| Poly(oxypropylene)diamine | (CAS-No.) 9046-10-0 | 1 – 5 | Skin Corr. 1, H314 Aquatic Acute 3, H402 Aquatic Chronic 3, H412 |
| 1,4-Bis(aminocyclohexyl)methane | (CAS-No.) 1761-71-3 | 1 – 5 | Acute Tox. 4 (Oral), H302 Skin Corr. 1, H314 Skin Sens. 1B, H317 STOT RE 2, H373 Aquatic Acute 2, H401 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : IF exposed or concerned: Get medical advice/attention. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Rinse immediately with plenty of water for 15 minutes. Remove/Take off immediately all contaminated clothing. Get medical advice/attention. |
| First-aid measures after eye contact | : Immediately rinse with plenty of water (for at least 15 minutes). Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention. Maintain irrigation until patient received medical care. Continue to irrigate for one hour if medical attention is not available. Cover wound with sterile dressing. |
| First-aid measures after ingestion | : Rinse mouth. Do not induce vomiting. Call a physician immediately. |

4.2. Most important symptoms and effects (acute and delayed)

| | |
|-------------------------------------|---|
| Symptoms/effects after skin contact | : Burns. May cause an allergic skin reaction. |
| Symptoms/effects after eye contact | : Serious damage to eyes. |
| Symptoms/effects after ingestion | : Burns. |

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

| | |
|------------------------------|--|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. Carbon dioxide. |
|------------------------------|--|

5.2. Specific hazards arising from the chemical

5.3. Special protective equipment and precautions for fire-fighters

| | |
|--------------------------------|--|
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |
|--------------------------------|--|

EP1200 Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Contains a component that is encapsulated within the product and not expected to be released during normal processing conditions or a foreseeable emergency.

Precautions for safe handling : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| EP1200 Black B | | |
|---|-------------------------------------|--|
| OSHA | OSHA PEL (TWA) (mg/m ³) | 15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction) |
| OSHA | Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |
| 4-Nonylphenol, branched (84852-15-3) | | |
| Not applicable | | |
| 1,4-Bis(aminocyclohexyl)methane (1761-71-3) | | |
| Not applicable | | |
| Poly(oxypropylene)diamine (9046-10-0) | | |
| Not applicable | | |

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

EP1200 Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection:

Safety glasses with side shields

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation, wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--------------------------|
| Physical state | : Liquid |
| Color | : white |
| Odor | : Amine-like |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : > 200 °C |
| Flash point | : > 120 °C |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : Not applicable. |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Relative density | : No data available |
| Specific gravity / density | : 1.94 g/cm ³ |
| Solubility | : Not miscible. |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, dynamic | : No data available |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |
| VOC content | 0 % |

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

EP1200 Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

metals. Oxidizing agent. Reducing agents. Strong bases. Chlorine trifluoride. Ethylene oxide.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). Nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

4-Nonylphenol, branched (84852-15-3)

| | |
|---------------|--|
| LD50 oral rat | 1412 mg/kg body weight (Other, Rat, Male / female, Experimental value, Oral) |
| ATE US (oral) | 1412 mg/kg body weight |

1,4-Bis(aminocyclohexyl)methane (1761-71-3)

| | |
|--------------------|--|
| LD50 oral rat | 380 mg/kg (EPA OPP 81-1: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral) |
| LD50 dermal rabbit | 2110 mg/kg body weight (EPA OPP 81-2, 24 h, Rabbit, Male / female, Experimental value, Dermal) |
| ATE US (oral) | 380 mg/kg body weight |
| ATE US (dermal) | 2110 mg/kg body weight |

Poly(oxypropylene)diamine (9046-10-0)

| | |
|-----------------------|---|
| LD50 oral rat | 2627 mg/kg |
| LD50 dermal rat | 2980 mg/kg |
| LD50 dermal rabbit | 2980 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal) |
| LC50 Inhalation - Rat | > 0.74 mg/l |
| ATE US (oral) | 2627 mg/kg body weight |
| ATE US (dermal) | 2980 mg/kg body weight |

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Assumed to cause serious eye damage
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Suspected of damaging fertility or the unborn child.
STOT-single exposure : Not classified

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

4-Nonylphenol, branched (84852-15-3)

| | |
|--------------------------|--|
| LOAEL (oral,rat,90 days) | 400 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents) |
| NOAEL (oral,rat,90 days) | 100 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents) |

1,4-Bis(aminocyclohexyl)methane (1761-71-3)

| | |
|------------------------|--|
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
|------------------------|--|

Aspiration hazard : Not classified
Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Serious damage to eyes.
Symptoms/effects after ingestion : Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

EP1200 Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| 4-Nonylphenol, branched (84852-15-3) | |
|---|---|
| LC50 fish 1 | 0.08 mg/l (ASTM E729-96, 96 h, Hybopsis monacha, Static system, Fresh water, Experimental value, Nominal concentration) |
| EC50 Daphnia 1 | 0.084 mg/l (ASTM E729-88, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value) |
| NOEC chronic fish | 0.006 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '91 d' |

| 1,4-Bis(aminocyclohexyl)methane (1761-71-3) | |
|--|---|
| LC50 fish 1 | 68 mg/l (DIN 38412-15, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value, Nominal concentration) |
| EC50 Daphnia 1 | 6.84 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP) |
| LC50 fish 2 | 68 mg/l Test organisms (species): Leuciscus idus |
| EC50 Daphnia 2 | 6.84 mg/l Test organisms (species): Daphnia magna |
| ErC50 (algae) | 140 – 200 mg/l (DIN 38412-9, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration) |
| NOEC (chronic) | 4 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC chronic fish | > 1 mg/l Test organisms (species): other:freshwater fish |

| Poly(oxypropylene)diamine (9046-10-0) | |
|--|--|
| LC50 fish 1 | 772.14 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Cyprinodon variegatus, Static system, Salt water, Experimental value, GLP) |
| EC50 Daphnia 1 | 80 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP) |
| ErC50 (algae) | 15 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP) |

12.2. Persistence and degradability

| 4-Nonylphenol, branched (84852-15-3) | |
|---|--|
| Persistence and degradability | Biodegradability in soil: no data available. Readily biodegradable in water. |

| 1,4-Bis(aminocyclohexyl)methane (1761-71-3) | |
|--|-------------------------------------|
| Persistence and degradability | Not readily biodegradable in water. |

| Poly(oxypropylene)diamine (9046-10-0) | |
|--|-------------------------------------|
| Persistence and degradability | Not readily biodegradable in water. |

12.3. Bioaccumulative potential

| 4-Nonylphenol, branched (84852-15-3) | |
|---|--|
| BCF fish 1 | 1200 – 1300 (OECD 305: Bioconcentration: Flow-Through Fish Test, 16 day(s), Gasterosteus aculeatus, Flow-through system, Salt water, Experimental value, Fresh weight) |
| Partition coefficient n-octanol/water (Log Pow) | 5.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 23 °C) |
| Bioaccumulative potential | Potential for bioaccumulation (500 ≤ BCF ≤ 5000). |

| 1,4-Bis(aminocyclohexyl)methane (1761-71-3) | |
|--|---|
| BCF fish 1 | < 60 (OECD 305: Bioconcentration: Flow-Through Fish Test, 60 day(s), Cyprinus carpio, Flow-through system, Fresh water, Read-across, GLP) |
| Partition coefficient n-octanol/water (Log Pow) | 2.03 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

| Poly(oxypropylene)diamine (9046-10-0) | |
|---|--|
| Partition coefficient n-octanol/water (Log Pow) | 1.34 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C) |
| Bioaccumulative potential | Not bioaccumulative. |

12.4. Mobility in soil

| 4-Nonylphenol, branched (84852-15-3) | |
|---|---|
| Partition coefficient n-octanol/water (Log Koc) | 4.35 – 5.69 (log Koc, Other, Experimental value, GLP) |
| Ecology - soil | Adsorbs into the soil. |

EP1200 Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| 1,4-Bis(aminocyclohexyl)methane (1761-71-3) | |
|--|---|
| Partition coefficient n-octanol/water (Log Koc) | 3.25 (log Koc, Other, Calculated value) |
| Ecology - soil | Low potential for mobility in soil. |
| Poly(oxypropylene)diamine (9046-10-0) | |
| Surface tension | Data waiving |
| Ecology - soil | No (test)data on mobility of the substance available. |

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3267 Corrosive liquid, basic, organic, n.o.s. (4-Nonylphenol, branched ; Poly(oxypropylene)diamine), 8, III

UN-No.(DOT) : UN3267

Proper Shipping Name (DOT) : Corrosive liquid, basic, organic, n.o.s.
4-Nonylphenol, branched ; Poly(oxypropylene)diamine

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : III - Minor Danger

Hazard labels (DOT) : 8 - Corrosive



Dangerous for the environment : Yes

Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

EP1200 Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids

Emergency Response Guide (ERG) Number : 153

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (4-Nonylphenol, branched ; Poly(oxypropylene)diamine), 8, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS

UN-No. (IMDG) : 3267
CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
4-Nonylphenol, branched ; Poly(oxypropylene)diamine

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : III - substances presenting low danger

Limited quantities (IMDG) : 5 L

Marine pollutant : Yes



Air transport

Transport document description (IATA) : UN 3267 Corrosive liquid, basic, organic, n.o.s. (4-Nonylphenol, branched ; Poly(oxypropylene)diamine), 8, III, ENVIRONMENTALLY HAZARDOUS

UN-No. (IATA) : 3267

Proper Shipping Name (IATA) : Corrosive liquid, basic, organic, n.o.s.
4-Nonylphenol, branched ; Poly(oxypropylene)diamine

Class (IATA) : 8 - Corrosives

Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

| | | |
|--|---|----------|
| 4-Nonylphenol, branched | CAS-No. 84852-15-3 | 10 – 30% |
| 4-Nonylphenol, branched (84852-15-3) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 | | |
| EPA TSCA Regulatory Flag | SP - SP - indicates a substance that is identified in a proposed Significant New Use Rule. | |
| 1,4-Bis(aminocyclohexyl)methane (1761-71-3) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |
| Poly(oxypropylene)diamine (9046-10-0) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |
| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711). | |

15.2. International regulations

CANADA

EP1200 Black B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4-Nonylphenol, branched (84852-15-3)

Listed on the Canadian DSL (Domestic Substances List)

1,4-Bis(aminocyclohexyl)methane (1761-71-3)

Listed on the Canadian DSL (Domestic Substances List)

Poly(oxypropylene)diamine (9046-10-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Contains the following REACH ingredient(s): 4-Nonylphenol, branched and linear [substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof] (EC 284-325-5, CAS 84852-15-3)

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

| | |
|------|---|
| H302 | Harmful if swallowed |
| H314 | Causes severe skin burns and eye damage |
| H317 | May cause an allergic skin reaction |
| H361 | Suspected of damaging fertility or the unborn child |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life |
| H401 | Toxic to aquatic life |
| H402 | Harmful to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H411 | Toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects |

SDS US - ResinLab

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.