

SECTION 1: Identification**1.1. Identification**

Product form : Mixture
Product name : EP1200 Black A

1.2. Recommended use and restrictions on use

Recommended use : Epoxy resin
Restrictions on use : Product for industrial use only

1.3. Supplier

ResinLab, LLC
N109 W13300 Ellsworth Drive
Germantown, WI 53022 - United States
T 1-877-259-1669
msds@resinlab.com - www.resinlab.com

1.4. Emergency telephone number

Emergency number : CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS US classification**

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - If on skin: Wash with plenty of water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients**3.1. Substances**

Not applicable

EP1200 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Name	Product identifier	%
aluminum oxide	(CAS-No.) 1344-28-1	50 – 75
Epoxy Resin	(CAS-No.) 25068-38-6	20 - 30
1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid	(CAS-No.) 74398-71-3	10 – 30
carbon black	(CAS-No.) 1333-86-4	0.1 – 0.5

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth out with water. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
- Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Eye irritation.
- Symptoms/effects after ingestion : None under normal conditions.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Specific hazards arising from the chemical

- Fire hazard : No fire hazard.
- Explosion hazard : No direct explosion hazard.
- Hazardous decomposition products in case of fire : Toxic fumes may be released, Carbon oxides (CO, CO₂), Formaldehyde, a known skin and lung sensitizer and a regulated carcinogen, may be released when heated above 150 °C, Phenolic compounds

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

EP1200 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Contains a component(s) that is encapsulated within the product and not expected to be released during normal processing conditions or a foreseeable emergency. Do not breathe dust created by sanding, grinding or machining.

Precautions for safe handling : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Keep cool. Protect from sunlight.

Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Epoxy Resin (25068-38-6)		
Not applicable		
carbon black (1333-86-4)		
ACGIH	Local name	Carbon black
ACGIH	ACGIH OEL TWA	3 mg/m ³ (Inhalable fraction)
ACGIH	Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2024
OSHA	OSHA PEL TWA	3.5 mg/m ³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid (74398-71-3)		
Not applicable		
aluminum oxide (1344-28-1)		
ACGIH	ACGIH OEL TWA	1 mg/m ³ (Respirable fraction)
OSHA	OSHA PEL TWA	15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace.

EP1200 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses with side shields

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Black
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 93 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 2.01 g/cm ³
Solubility	: Not miscible.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
VOC content	No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

EP1200 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Chlorine trifluoride. Ethylene oxide. Strong oxidizing agents. Strong bases. Strong acids.

10.6. Hazardous decomposition products

No hazardous decomposition products if stored and handled as prescribed/ indicated. Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Epoxy Resin (25068-38-6)	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

carbon black (1333-86-4)	
LD50 oral rat	> 10000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 28 day(s))
LD50 dermal rabbit	> 8000 mg/kg Source: ECHA

aluminum oxide (1344-28-1)	
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Contains a component(s) that is encapsulated within the product and not expected to be released during normal processing conditions or a foreseeable emergency.

Epoxy Resin (25068-38-6)	
NOAEL (chronic,oral,animal/male,2 years)	15 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
NOAEL (chronic,oral,animal/female,2 years)	100 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)

carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

EP1200 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

carbon black (1333-86-4)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0071 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	> 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0011 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

aluminum oxide (1344-28-1)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.015 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life.
Ecology - water	: Toxic to aquatic life with long lasting effects.

Epoxy Resin (25068-38-6)	
LC50 - Fish [1]	1.3 mg/l (96 h, Pisces, Literature study)
EC50 - Crustacea [1]	≈ 2 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

carbon black (1333-86-4)	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)

aluminum oxide (1344-28-1)	
LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)

12.2. Persistence and degradability

Epoxy Resin (25068-38-6)	
Persistence and degradability	Not readily biodegradable in water.

carbon black (1333-86-4)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

aluminum oxide (1344-28-1)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

EP1200 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Epoxy Resin (25068-38-6)	
Partition coefficient n-octanol/water (Log Pow)	3 (Estimated value, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
carbon black (1333-86-4)	
Bioaccumulative potential	Not bioaccumulative.
aluminum oxide (1344-28-1)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

Epoxy Resin (25068-38-6)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Ecology - soil	No (test)data on mobility of the substance available.
carbon black (1333-86-4)	
Surface tension	Not applicable (solid)
Ecology - soil	No (test)data on mobility of the substance available. Not toxic to plants. Not toxic to animals.
aluminum oxide (1344-28-1)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG)	: UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin), 9, III, MARINE POLLUTANT
UN-No. (IMDG)	: 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Epoxy Resin
Class (IMDG)	: 9 - Miscellaneous dangerous substances and articles
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L

Air transport

Transport document description (IATA)	: UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin), 9, III
UN-No. (IATA)	: 3082

EP1200 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (IATA)	: Environmentally hazardous substance, liquid, n.o.s. Epoxy Resin
Class (IATA)	: 9 - Miscellaneous Dangerous Substances and Articles
Packing group (IATA)	: III - Low danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

aluminum oxide	CAS-No. 1344-28-1	50 – 75%
----------------	-------------------	----------

Epoxy Resin (25068-38-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
--------------------------	---

1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid (74398-71-3)

EPA TSCA Regulatory Flag	TP - TP - indicates a substance that is the subject of a proposed TSCA section 4 test rule. XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
--------------------------	--

aluminum oxide (1344-28-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

15.2. International regulations

CANADA

Epoxy Resin (25068-38-6)

Listed on the Canadian DSL (Domestic Substances List)

carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid (74398-71-3)

Listed on the Canadian DSL (Domestic Substances List)

aluminum oxide (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Contains no substance(s) listed on the REACH Candidate List

Epoxy Resin (25068-38-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

carbon black (1333-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

aluminum oxide (1344-28-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Epoxy Resin (25068-38-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

EP1200 Black A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid (74398-71-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

aluminum oxide (1344-28-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

15.3. US State regulations

 **WARNING:** This product can expose you to chemicals including Epichlorohydrin, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
carbon black(1333-86-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
aluminum oxide(1344-28-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 12/09/2024

Full text of hazard classes and H-statements:

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H401	Toxic to aquatic life

SDS US - ResinLab

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.