# **Safety Data Sheet**



Revision Number: 008.0 Issue date: 05/08/2025

# 1. IDENTIFICATION

Product name:BONDERITE M-CR 1132 AEROIDH number:1445846Product type/Chromating Products for MetalsItem number:1445856

Recommended use:

Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Region: United States

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: H317 - MAY CAUSE AN ALLERGIC SKIN REACTION.

H350 - MAY CAUSE CANCER.

HAZARD CLASS	HAZARD CATEGORY
SKIN SENSITIZATION	1
CARCINOGENICITY	1B

# PICTOGRAM(S)



#### **Precautionary Statements**

**Prevention:** P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing mist/vapours.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves, clothing, eye and face protection.

**Response:** P302+P352 - IF ON SKIN: Wash with plenty of water.

P308+P313 - IF exposed or concerned: Get medical attention. P333+P313 - If skin irritation or rash occurs: Get medical attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

Storage: P405 - Store locked up.

**Disposal:** P501 - Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Other hazards Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Chromium chromate	24613-89-6	0.1 - 1

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

#### First Aid Measures by likely routes of exposure

**Inhalation:** If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist. Delayed effects

possible after inhalation. Administer oxygen or artificial respiration as needed. Do not use mouth-to-mouth method if victim ingested or inhaled the

substance.

**Skin contact:** Remove contaminated clothing and footwear. Immediately wash skin

thoroughly with soap and water. If symptoms develop and persist, get medical attention. Treat contaminated skin with Ca-gluconate gel (burn jelly). Topical 10 % EDTA ointment can be used to treat chromate scabs and skin ulcers. A 10 % ascorbic acid solution may speed healing if applied promptly. Larger

exposures may need additional treatment.

Launder contaminated clothing before reuse. Discard any shoes or clothing

items that cannot be decontaminated.

Eye contact: Immediately flush affected eye with large amounts of gently flowing water or

0.9% sterile saline solution for at least 15 minutes. Hold eyelid wide open. Get immediate medical attention. Eye flushing should continue during

transportation to a doctor.

Ingestion: Get immediate medical attention. Do not induce vomiting. If individual is

conscious, wash out mouth with water. Provide a glass of water to dilute the

material in the stomach.

Most important symptoms and effects (acute

and delayed):

The most important known symptoms and effects, both acute and delayed, are

described in Section 11: Toxicological Information.

Indication of any immediate medical attention /

special treatment needed:

Treatment of hypocalcemia associated with corrosive fluoride compounds exposure may be corrected by intravenous calcium gluconate or calcium chloride. Treatment of hypomagnesemia may be corrected by intravenous

magnesium sulfate.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Use media appropriate for surrounding material. Water spray (fog), foam, dry

chemical or carbon dioxide.

Improper extinguishing agents: Not available.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses.

Hazardous combustion products:

Irritating and toxic gases or fumes may be released during a fire. Chromium

oxide.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

# 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Avoid breathing vapors or mists of this product. Use only with adequate ventilation. Launder work clothes frequently. Do not store or consume food, drink, or tobacco products in areas where they may become contaminated

with this material. Do not take internally. For industrial use only.

Storage: For safe storage, store between 40 °F (4.4 °C) and 104 °F (40°C)

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Keep from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. 0.003 mg/m3 TWA (as Cr(III)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. (SKIN) (as Cr(VI)) Inhalable fraction. 0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. (Respiratory sensitization) (Dermal	0.005 mg/m3 TWA 0.0025 mg/m3 OSHA_ACT 0.1 mg/m3 Ceiling 0.5 mg/m3 PEL (as Cr)	None	None
	0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. 0.003 mg/m3 TWA (as Cr(III)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. (SKIN) (as Cr(VI)) Inhalable fraction. 0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. (Respiratory sensitization) (Dermal	0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. 0.003 mg/m3 TWA (as Cr(III)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. (SKIN) (as Cr(VI)) Inhalable fraction. 0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. (Respiratory sensitization)	0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. 0.003 mg/m3 TWA (as Cr(III)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. (SKIN) (as Cr(VI)) Inhalable fraction. 0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. (Respiratory sensitization) (Dermal

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

**Eye/face protection:** Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Use chemical resistant, impervious gloves and clothing to prevent skin

contact. Gloves should be tested to determine suitability for prolonged contact.

Use of impervious boots is recommended.

IDH number: 1445846 Product name: BONDERITE M-CR 1132 AERO

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: Yellow-green Odor: Mild Not available. Odor threshold:

pH: 1.95 - 2.25

. Vapor pressure: 1 - 10 kPa (20 °C (68°F)) Values referring to water10 - 25 kPa (50 °C (122°F))

Values referring to water

> 100 °C (> 212°F)Aqueous solution Boiling point/range: Melting point/ range: Not applicable, Product is a liquid Density/Relative density: 1.00 - 1.01 at 60 °F (15.56 °C)

Relative vapor density: < 1 20 °C Not applicable Flash point: Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Autoignition temperature: Not available. Not applicable Flammability: Not applicable Evaporation rate: Not determined Solubility: Complete Water Solubility: Miscible Water Partition coefficient n-octanol/water Not available.

(logarithmic value):

VOC content: 0 % (calculated) Dynamic viscosity: Not available. Kinematic viscosity: 1 - 10 mm2/s

Particle characteristics: Not applicable, Product is a liquid

**Decomposition temperature:** Not available.

#### 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

Chromium oxide.

Incompatible materials: This product may react with strong reducing agents. Keep away from organic and combustible

materials. Strong bases. Metals.

Reactivity: Not available.

Conditions to avoid: Do not allow chemical to dry in the presence of organic materials.

# 11. TOXICOLOGICAL INFORMATION

Likely routes of exposure: Skin, Inhalation, Eyes, Ingestion

IDH number: 1445846 Product name: BONDERITE M-CR 1132 AERO

#### **Potential Health Effects/Symptoms**

Inhalation: Contains fluorides. Exposure to fluorides over years may cause fluorosis. May be harmful or

fatal if inhaled. Nasal itch and soreness, perforation of the nasal septum, dental erosion, and chronic asthmatic bronchitis may result from repeated exposure. May cause respiratory tract

irritation.

Skin contact: A component in this product may be harmful or fatal if absorbed through the skin, especially if

skin is damaged. Product contains chromium, which may cause an allergic skin sensitization reaction. Contact with broken skin may lead to formation of firmly marginated "chrome sores".

May cause allergic skin reaction.

**Eye contact:** May cause irritation.

Ingestion: Contains fluorides. Exposure to fluorides over years may cause fluorosis. Harmful or fatal if

swallowed. May cause burns of the mouth, throat and stomach. May also cause gastrointestinal disturbances such as nausea, vomiting, abdominal pain, and diarrhea. Not expected under normal conditions of use. May cause gastrointestinal tract irritation if

swallowed.

Hazardous Component(s)	LD50s and LC50s	
Chromium chromate	Inhalation LC50 (Rat, 4 h) = 200 mg/m3 Inhalation LC50 (Rat, 4 h) = 99 mg/m3 Inhalation LC50 (Rat, 4 h) = 217 mg/m3 Inhalation LC50 (Rat, 4 h) = 104 mg/m3	

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Chromium chromate	Irritant	Allergen	Respiratory

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Chromium chromate	Known To Be Human Carcinogen.	Group 1	Yes

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

This chemical contains phosphates. This chemical contains heavy metals.

# 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

## U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

DOT Hazardous Substance(s): Chromic acid

# International Air Transportation (ICAO/IATA)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s. (Chromium(III)-chromate)

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Chromium(III)-chromate)

Hazard class or division: 9

Identification number: UN 3082 Packing group: III

Marine pollutant: Chromium(III)-chromate

IDH number: 1445846 Product name: BONDERITE M-CR 1132 AERO

# 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: Chromium chromate (CAS# 24613-89-6).

CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: **CERCLA/SARA Section 313:** 

None above reporting de minimis. Please refer to the GHS classification in Section 2

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Chromium chromate (CAS# 24613-89-6). Chromium trioxide (CAS# 1333-82-0).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic

Substances List

# 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 05/08/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 1445846 Product name: BONDERITE M-CR 1132 AFRO