



SAFETY DATA SHEET

In accordance with OSHA 29 CFR 1910.1200

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

1. Identification

1.1. Product identifier

Product Name NEVER-SEEZ REGULAR GRADE AEROSOL

Other means of identification

Other information Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Lubricant
Restrictions on use No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1(800) 726-7845 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)

E-mail msds@bostik.com

1.4. Emergency telephone number

Emergency Telephone CHEMTREC (Chemical Transportation Emergency Center)
Chemtrec: 1-800-424-9300 (US) , 1-703-527-3887 (Outside U.S.)
Rocky Mountain Poison Center: 1-866-767-5089

2. Hazard(s) identification

2.1. Classification of the substance or mixture

| | |
|--|---------------|
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2A |
| Specific target organ toxicity (single exposure) | Category 3 |
| Aspiration hazard | Category 1 |
| Flammable aerosols | Category 1 |
| Gases Under Pressure | Liquefied gas |

Hazards not otherwise classified (HNOC)

Not applicable

2.2. Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes skin irritation
Causes serious eye irritation

SAFETY DATA SHEET

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Extremely flammable aerosol
Contains gas under pressure; may explode if heated



Appearance Aerosol

Physical state Compressed liquefied gas
Odor Petroleum

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Do not spray on an open flame or other ignition source
Pressurized container: Do not pierce or burn, even after use
Wear protective gloves/eye protection/face protection

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN: Wash with plenty of water and soap
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash it before reuse
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER or doctor if you feel unwell
IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
Protect from sunlight

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3. Other Information

In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible.

3. Composition/information on ingredients

3.1. Substances

Not applicable.

SAFETY DATA SHEET

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

Mixture

| Chemical name | CAS No. | Weight-% |
|---|------------|----------|
| Naphtha, petroleum, hydrotreated light, <0.1% Benzene | 64742-49-0 | 10 - 30 |
| Acetone | 67-64-1 | 10 - 30 |
| Propane | 74-98-6 | 7 - <13 |
| Butane | 106-97-8 | 5 - <10 |
| Graphite | 7782-42-5 | 5 - <10 |
| Copper | 7440-50-8 | 1 - <5 |
| Zinc oxide | 1314-13-2 | 1 - <5 |

**The exact percentage (concentration) of composition has been withheld as a trade secret*

4. First-aid measures

4.1. Description of first aid measures

| | |
|---|--|
| General advice | Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. |
| Inhalation | Remove to fresh air. If symptoms persist, call a physician. If breathing is difficult, (trained personnel should) give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical attention. Aspiration into lungs can produce severe lung damage. Delayed pulmonary edema may occur. |
| Eye contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists. |
| Skin contact | Wash off immediately with soap and plenty of water for at least 15 minutes. In case of contact with liquefied gas, thaw frosted parts with lukewarm water. Get medical attention if irritation develops and persists. |
| Ingestion | Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. |
| Self-protection of the first aider | Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|----------------------------|---|
| Symptoms | Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. |
| Effects of Exposure | No information available. |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|--------------------------------------|--|
| Note to physicians US - EN | Because of the danger of aspiration, emesis or gastric lavage should not be employed |
|--------------------------------------|--|

SAFETY DATA SHEET

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

unless the risk is justified by the presence of additional toxic substances.

5. Fire-Fighting Measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO₂). Water spray.
Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon oxides. Carbon monoxide. Hydrocarbons. Zinc oxide. Copper oxides. Sulfur oxides.

Explosion data

Sensitivity to mechanical impact Yes.

Sensitivity to static discharge Yes.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Contents under pressure. Use personal protective equipment as required. See section 8 for more information. Evacuate personnel to safe areas. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Avoid release to the environment. Prevent product from entering drains. Do not allow into any sewer, on the ground or into any body of water. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches

SAFETY DATA SHEET

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

and waterways.

Methods for cleaning up

Use personal protective equipment as required. Take precautionary measures against static discharges. Dam up. Take up with inert, damp, non-combustible material using clean non-sparking tools and place into loosely covered plastic containers for later disposal. Clean contaminated surface thoroughly.

Reference to other sections

See section 8 for more information. See section 13 for more information.

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use spark-proof tools and explosion-proof equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep in an area equipped with sprinklers. Contents under pressure. Do not puncture or incinerate cans. Avoid breathing vapors or mists. Handle product only in closed system or provide appropriate exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Take off contaminated clothing and wash before reuse. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep/store only in original container. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Protect from sunlight. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

7.3 References to other sections

Reference to other sections

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
See Section 12: ECOLOGICAL INFORMATION

8. Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH |
|---|-------------------------------|--|--------------------------------|
| Naphtha, petroleum, hydrotreated light, <0.1% Benzene 64742-49-0 | TWA: 100 ppm Sk* | - | - |
| Acetone 67-64-1 | TWA: 250 ppm STEL: 500 ppm | TWA: 1000 ppm TWA: 2400 mg/m ³ | IDLH: 2500 ppm TWA: 250 ppm |

SAFETY DATA SHEET

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

| | | | |
|-------------------------|--|--|--|
| | | (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm | TWA: 590 mg/m ³ |
| Propane 74-98-6 | : See Appendix F: Minimal Oxygen Content, explosion hazard Simple asphyxiant | TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ | IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ |
| Butane 106-97-8 | STEL: 1000 ppm explosion hazard | (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³ | IDLH: 1600 ppm TWA: 800 ppm TWA: 1900 mg/m ³ |
| Graphite 7782-42-5 | TWA: 2 mg/m ³ respirable particulate matter all forms except graphite fibers | TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf respirable dust natural (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural | IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ natural respirable dust |
| Copper 7440-50-8 | TWA: 0.2 mg/m ³ fume | TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist | IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume |
| Zinc oxide 1314-13-2 | TWA: 2 mg/m ³ respirable particulate matter STEL: 10 mg/m ³ respirable particulate matter | TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ fume (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) STEL: 10 mg/m ³ fume | IDLH: 500 mg/m ³ Ceiling: 15 mg/m ³ dust TWA: 5 mg/m ³ dust and fume STEL: 10 mg/m ³ fume |

| Chemical name | Argentina | Brazil | S.D. 594/1999 | Colombia |
|---|-------------------------------|--|--|-----------------------------|
| Naphtha, petroleum, hydrotreated light, <0.1% Benzene 64742-49-0 | - | TWA: 100 ppm | - | - |
| Acetone 67-64-1 | TWA: 500 ppm STEL: 750 ppm | TWA: 780 ppm TWA: 1870 mg/m ³ STEL: 500 ppm | LPP: 438 ppm LPP: 1040 mg/m ³ LPT: 750 ppm LPT: 1782 mg/m ³ | STEL: 500ppm TWA: 250ppm |
| Propane 74-98-6 | TWA: 2500 ppm | Simple asphyxiant | - | : |
| Butane | TWA: 800 ppm | TWA: 470 ppm | - | STEL: 1000ppm |

SAFETY DATA SHEET

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

| | | | | |
|-------------------------|---|---|--|--|
| 106-97-8 | | TWA: 1090 mg/m ³ STEL: 1000 ppm Butane, isomers | | |
| Graphite 7782-42-5 | TWA: 2 mg/m ³ | TWA: 2 mg/m ³ | LPP: 1.75 mg/m ³ | TWA: 2mg/m ³ |
| Copper 7440-50-8 | TWA: 0.2 mg/m ³ TWA: 1 mg/m ³ | TWA: 0.2 mg/m ³ | LPP: 0.18 mg/m ³ LPP: 0.88 mg/m ³ | TWA: 0.2mg/m ³ |
| Zinc oxide 1314-13-2 | TWA: 5 mg/m ³ TWA: 10 mg/m ³ STEL: 10 mg/m ³ | TWA: 2 mg/m ³ STEL: 10 mg/m ³ respirable particulate matter | LPP: 4.4 mg/m ³ LPT: 10 mg/m ³ | STEL: 10mg/m ³ TWA: 2mg/m ³ |

| Chemical name | Costa Rica | Peru | Uruguay | Venezuela |
|-------------------------|--|--|--|---|
| Acetone 67-64-1 | STEL: 500ppm TWA: 250ppm | STEL: 750ppm STEL: 1781mg/m ³ TWA: 500ppm TWA: 1187mg/m ³ | 500 ppm STEL 250 ppm TWA | STEL: 750 ppm TWA: 500 ppm |
| Propane 74-98-6 | : | - | See Appendix F: Minimal Oxygen Content, explosion hazard | TWA: 1000 mg/m ³ |
| Butane 106-97-8 | STEL: 1000ppm | TWA: 800ppm TWA: 1902mg/m ³ | 1000 ppm STEL (explosion hazard, listed under Butane, isomers) | TWA: 1000 ppm |
| Graphite 7782-42-5 | TWA: 2mg/m ³ | TWA: 2mg/m ³ | 2 mg/m ³ TWA (all forms except graphite fibers, respirable particulate matter) | TWA: 2 mg/m ³ |
| Copper 7440-50-8 | TWA: 0.2mg/m ³ | TWA: 0.2mg/m ³ TWA: 1mg/m ³ | 0.2 mg/m ³ TWA (fume) | TWA: 0.2 mg/m ³ TWA: 1 mg/m ³ |
| Zinc oxide 1314-13-2 | STEL: 10mg/m ³ TWA: 2mg/m ³ | STEL: 10mg/m ³ TWA: 2mg/m ³ TWA: 10mg/m ³ | 10 mg/m ³ STEL (respirable particulate matter) 2 mg/m ³ TWA (respirable particulate matter) | STEL: 10 mg/m ³ TWA: 2 mg/m ³ TWA: 10 mg/m ³ |

8.2. Exposure controls

Appropriate engineering controls

Engineering controls Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles. Avoid contact with eyes.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.
 Antistatic boots.

SAFETY DATA SHEET

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

| | |
|---------------------------------------|--|
| Respiratory protection | If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. |
| General hygiene considerations | Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. |

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------------|--------------------------|
| Physical state | Compressed liquefied gas |
| Appearance | Aerosol |
| Color | Gray |
| Odor | Petroleum |
| Odor threshold | No information available |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|--|-------------------------|-----------------------------------|
| pH | No data available | Not applicable Insoluble in water |
| pH (as aqueous solution) | No data available | None known |
| Melting point / freezing point | No data available | None known |
| Initial boiling point and boiling range | Not applicable, Aerosol | Not applicable, Aerosol |
| Flash point | Not applicable, Aerosol | Not applicable, Aerosol |
| Evaporation rate | No data available | None known |
| Flammability | No data available | None known |
| Flammability Limit in Air | | None known |
| Upper flammability or explosive limits | No data available | |
| Lower flammability or explosive limits | No data available | |
| Vapor pressure | No data available | None known |
| Relative vapor density | No data available | None known |
| Relative density | No data available | None known |
| Water solubility | Insoluble in water | None known |
| Solubility(ies) | No data available | None known |
| Partition coefficient | No data available | None known |
| Autoignition temperature | No data available | None known |
| Decomposition temperature | No data available | None known |
| Kinematic viscosity | No data available | None known |
| Dynamic viscosity | No data available | None known |

9.2. Other information

| | | |
|-----------------------------|--------------------------|--------------------------|
| Explosive properties | No information available | |
| Oxidizing properties | No information available | |
| Solvent content (%) | No information available | |
| Solid content (%) | 40.0 | |
| Softening point | No information available | |
| Molecular weight | No information available | |
| VOC content | 40 % | No information available |
| Liquid Density | 0.770 g/ml | |

SAFETY DATA SHEET

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

Bulk density No information available

10. Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat. Keep away from open flames, hot surfaces and sources of ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Incompatible materials Alkali. Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Carbon oxides Hydrocarbons

11. Toxicological information

11.1. Information on toxicological effects

Product Information

| | |
|---------------------|--|
| Inhalation | Specific test data for the substance or mixture is not available. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. |
| Eye contact | Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain. |
| Skin contact | Specific test data for the substance or mixture is not available. Repeated exposure may cause skin dryness or cracking. Causes skin irritation. (based on components). |
| Ingestion | Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis. |

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

SAFETY DATA SHEET

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

| | |
|-------------------------------|-----------------|
| ATEmix (oral) | 12,111.90 mg/kg |
| ATEmix (dermal) | 12,025.00 mg/kg |
| ATEmix (inhalation-gas) | >20000 ppm |
| ATEmix (inhalation-dust/mist) | >5 mg/l |
| ATEmix (inhalation-vapor) | >20 mg/l |

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---|--|---|--------------------------------------|
| Naphtha, petroleum, hydrotreated light, <0.1% Benzene 64742-49-0 | >5000 mg/kg (Rattus) | > 3160 mg/kg (Oryctolagus cuniculus) | =73680 ppm (Rattus) 4 h |
| Acetone 67-64-1 | =5800 mg/kg (Rattus) 3000 mg/Kg (mouse) | >15800 mg/Kg (Rattus) | =79 mg/l(Rattus) 4 h |
| Propane 74-98-6 | - | - | >800000 ppm (Rattus) 15 min |
| Butane 106-97-8 | - | - | =658 g/m ³ (Rattus) 4 h |
| Graphite 7782-42-5 | - | - | >2000 mg/m ³ (Rattus) 4 h |
| Copper 7440-50-8 | - | - | > 5.11 mg/L (Rat) 4 h |
| Zinc oxide 1314-13-2 | >5000 mg/kg (Rattus) | LD50 >2000 mg/Kg (Rattus) (OECD 402) | LC50 (4h) >5.7 mg/l |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Acetone (67-64-1)

| Method | Species | Exposure route | Effective dose | Exposure time | Results |
|---|---------|----------------|----------------|---------------|----------|
| OECD Test No. 405: Acute Eye Irritation/Corrosion | Rabbit | eye | | | irritant |

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical name | ACGIH | IARC | NTP | OSHA |
|---------------------|-------|------|-----|------|
| Naphtha, petroleum, | A3 | - | - | - |

SAFETY DATA SHEET

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

| | | | | |
|---|--|--|--|--|
| hydrotreated light, <0.1% Benzene 64742-49-0 | | | | |
|---|--|--|--|--|

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness. May cause respiratory irritation.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Target organ effects Liver, Kidney, Respiratory system, Eyes, Skin, Central nervous system, Central Vascular System (CVS).

Aspiration hazard May be fatal if swallowed and enters airways.

Other adverse effects No information available.

Interactive effects No information available.

12. Ecological information

12.1. Toxicity

Ecotoxicity

| Chemical name | Algae/aquatic plants | Fish | Toxicity to microorganisms | Crustacea |
|---|--|--|----------------------------|---|
| Naphtha, petroleum, hydrotreated light, <0.1% Benzene 64742-49-0 | - | LC50: =8.41mg/L (96h, Oncorhynchus mykiss) | - | LC50: =2.6mg/L (96h, Chaetogammarus marinus) |
| Acetone 67-64-1 | - | LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss) | EC50 = 14500 mg/L 15 min | EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static) |
| Graphite 7782-42-5 | - | LC50: >100mg/L (96h, Danio rerio) | - | - |
| Copper 7440-50-8 | EC50: 0.0426 - 0.0535mg/L (72h, Pseudokirchneriella subcapitata) EC50: 0.031 - 0.054mg/L (96h, Pseudokirchneriella subcapitata) | LC50 96 h = 0.8 mg/L (Cyprinus carpio static) | - | EC50: =0.03mg/L (48h, Daphnia magna) |
| Zinc oxide 1314-13-2 | LC 50 (72Hr) 0.136 mg/L | LC50 (96h) =0.7 mg/L (Danio rerio) | - | LC 50 (48Hr) =0.5 mg/l (Ceriodaphnia dubia) |

12.2. Persistence and degradability

Persistence and degradability No information available.

SAFETY DATA SHEET

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

| Chemical name | Partition coefficient |
|--------------------|-----------------------|
| Acetone 67-64-1 | -0.24 |
| Propane 74-98-6 | 1.09 |
| Butane 106-97-8 | 2.31 |

12.4. Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

13. Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Should not be released into the environment. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Dispose of in accordance with federal, state and local regulations.

14. Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

DOT

UN number or ID number UN1950
UN proper shipping name Aerosols
Transport hazard class(es) 2.1
Reportable quantity (lbs) Acetone: RQ (lb)= 5000.00
Reportable Quantity (RQ) (Acetone: RQ (kg)= 2270.00)
Special Provisions N82
DOT Marine Pollutant PP
Marine pollutant Naphtha, petroleum, hydrotreated light, <0.1% Benzene, Copper
Description UN1950, Aerosols, 2.1, Marine pollutant (Naphtha, petroleum, hydrotreated light, <0.1% Benzene, Copper)
Emergency Response Guide Number 126

IATA

SAFETY DATA SHEET

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

UN number or ID number UN1950
UN proper shipping name Aerosols, flammable
Transport hazard class(es) 2.1
Special Provisions A145, A167, A802
Description UN1950, Aerosols, flammable, 2.1

IMDG

UN number or ID number UN1950
UN proper shipping name Aerosols
Transport hazard class(es) 2.1
EmS-No. F-D, S-U
Special Provisions 63,190, 277, 327, 344, 381, 959
IMDG Marine Pollutant Name Naphtha, petroleum, hydrotreated light, <0.1% Benzene, Copper
Description UN1950, Aerosols, 2.1, Marine pollutant (Naphtha, petroleum, hydrotreated light, <0.1% Benzene, Copper)

15. Regulatory information

International Inventories

| | |
|-------------|----------|
| TSCA | Complies |
| DSL | Complies |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Complies - The components of this product are either listed or exempt from listing on inventory. Active

Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

| Chemical name | CAS No. | SARA 313 - Threshold Values % |
|---------------|-----------|-------------------------------|
| Copper | 7440-50-8 | 1.0 |
| Zinc oxide | 1314-13-2 | 1.0 |

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

16. Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate

LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

SAFETY DATA SHEET

NEVER-SEEZ REGULAR GRADE AEROSOL
Revision Number 4

Revision date 03-Oct-2024
Supersedes date 01-May-2020

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| | | | |
|---------|-----------------------------|------|----------------------------------|
| TWA | TWA (time-weighted average) | STEL | STEL (Short Term Exposure Limit) |
| Ceiling | Maximum limit value | Sk* | Skin designation |

Prepared By Product Stewardship and Regulatory Affairs.

Revision date 03-Oct-2024

Revision Note SDS sections updated. 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 12. 13. 14. 15.

Disclaimer

All information contained herein is believed to be accurate as of the date of publication, is provided “as-is” and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Bostik Inc. (“Company”) expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user’s application(s). **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN.** The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at <https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-management/medical-device-policy/> which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical devices to determine the suitability of all raw material, products and components, including any medical grade products, in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.

End of Safety Data Sheet