

# H.B. Fuller® FH-1272-B

Version 1.1 Revision Date 12/08/2015

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : H.B. Fuller® FH-1272-B

Product code : 10000003143

Manufacturer or supplier's details

Company : H.B. Fuller Company

Address : 1200 Willow Lake Boulevard

Vadnais Heights, MN 55110

Telephone : 1-888-423-8553

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

#### Recommended use of the chemical and restrictions on use

Recommended use : Solvent based adhesive

Restrictions on use : For industrial use only.

## **SECTION 2. HAZARDS IDENTIFICATION**

# **Emergency Overview**

Appearance	liquid	
Color	yellow	
Odor	solvent	

#### **GHS Classification**

Flammable liquids : Category 3
Acute toxicity (Inhalation) : Category 4
Skin irritation : Category 2
Eye irritation : Category 2B
Respiratory sensitization : Category 1
Skin sensitization : Category 1
Carcinogenicity : Category 2

Specific target organ systemic :

toxicity - single exposure

Category 3 (Respiratory system, Central nervous system)

# **GHS Label element**

Hazard pictograms







Signal Word : Danger

**Hazard Statements:** 



# H.B. Fuller® FH-1272-B

Version 1.1 Revision Date 12/08/2015

H226 Flammable liquid and vapor. H315 + H320 Causes skin and eye irritation. H317 May cause an allergic skin reaction. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.

#### **Precautionary Statements:**

**Prevention:** P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P285 In case of inadequate ventilation wear respiratory protection.

Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:** P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

#### **Potential Health Effects**

#### Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans

ethylbenzene 100-41-4 4-methyl-m-phenylene 584-84-9

diisocyanate

2-methyl-m-phenylene 91-08-7

diisocyanate

OSHA No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### Hazardous ingredients

Chemical Name	CAS-No.	Concentration [%]
Aromatic isocyanate	Not Assigned	70 - 90
xylene	1330-20-7	10 - 20



# H.B. Fuller® FH-1272-B

Version 1.1 Revision Date 12/08/2015

ethylbenzene	100-41-4	1 - 5
4-methyl-m-phenylene diisocyanate	584-84-9	0.1 - 1
2-methyl-m-phenylene diisocyanate	91-08-7	0.1 - 1

#### **SECTION 4. FIRST AID MEASURES**

General advice : Show this material safety data sheet to the doctor in

attendance.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.

Get medical attention if irritation develops and persists.

In case of eye contact : Flush eyes with water at least 15 minutes. Get medical

attention if eye irritation develops or persists.

If swallowed : Do NOT induce vomiting.

If victim is fully conscious, give a cupful of water.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

## **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during fire

fighting

: Cool closed containers exposed to fire with water spray.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

# **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material.

Sweep up and shovel into suitable containers for disposal.

Non-sparking tools should be used.



# H.B. Fuller® FH-1272-B

Version 1.1 Revision Date 12/08/2015

## **SECTION 7. HANDLING AND STORAGE**

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid inhalation of vapor or mist.

Do not use in areas without adequate ventilation. Keep away from fire, sparks and heated surfaces.

Keep container closed when not in use.

Take precautionary measures against static discharges.

Conditions for safe storage : Take measures to prevent the build up of electrostatic charge.

Use explosion-proof equipment.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Keep away from sources of ignition - No smoking.

Solvent vapors are heavier than air and may spread along

floors.

Materials to avoid : Strong oxidizing agents

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
xylene	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA Z-1
ethylbenzene	100-41-4	TWA	100 ppm	ACGIH
		STEL	125 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
4-methyl-m-phenylene diisocyanate	584-84-9	TWA	0.005 ppm	ACGIH
·		STEL	0.02 ppm	ACGIH
		С	0.02 ppm 0.14 mg/m3	OSHA Z-1
		STEL	0.02 ppm	OSHA P0



# H.B. Fuller® FH-1272-B

Version 1.1 Revision Date 12/08/2015

			0.15 mg/m3	
		TWA	0.005 ppm 0.04 mg/m3	OSHA P0
2-methyl-m-phenylene diisocyanate	91-08-7	TWA	0.005 ppm	ACGIH
		STEL	0.02 ppm	ACGIH

-

Engineering measures : Use local exhaust ventilation or other engineering controls to

minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapor Type

Hand protection

Material : Nitrile rubber

Eye protection : Safety glasses with side-shields

Hygiene measures : Avoid contact with skin, eyes and clothing.

Provide adequate ventilation.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid
Color : yellow
Odor : solvent

Odor Threshold : No data available

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Flash point : 82 °F

Evaporation rate : not determined

Upper explosion limit : upper flammability limit

not determined

Lower explosion limit : lower flammability limit

not determined

Density : 1.127 g/cm3

Solubility(ies)

Water solubility : not determined

Partition coefficient: n- : No data available

octanol/water

Autoignition temperature : not determined



# H.B. Fuller® FH-1272-B

Version 1.1 Revision Date 12/08/2015

Viscosity

Viscosity, kinematic : not determined

#### **SECTION 10. STABILITY AND REACTIVITY**

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Hazardous polymerization does not occur.

Conditions to avoid

: Heat, flames and sparks.

Hazardous decomposition

products

: Stable under normal conditions.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 14.06 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 3,066 mg/kg

Method: Calculation method

Ingredients:

xylene:

Acute oral toxicity : LD50 Oral rat: 4,300 mg/kg

Acute inhalation toxicity : LC50 rat: 47,635 mg/l

Exposure time: 4 h

ethylbenzene:

Acute oral toxicity : LD50 Oral rat: 3,500 mg/kg

Acute inhalation toxicity : LC50 rat: 17.2 mg/l

Exposure time: 4 h

## Skin corrosion/irritation

No data available

# Serious eye damage/eye irritation



# H.B. Fuller® FH-1272-B

Version 1.1 Revision Date 12/08/2015

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

**Aspiration toxicity** 

No data available

## **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

Ingredients:

xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.661 - 4.093

mg/l

Exposure time: 96 h Test Method: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia): 0.6 mg/l Exposure time: 48 h

Test Method: static test

ethylbenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l

Exposure time: 96 h

Test Method: semi-static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 1.8 - 2.4 mg/l

Exposure time: 48 h Test Method: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata): 1.7 - 7.6 mg/l

Exposure time: 96 h Test Type: static test



# H.B. Fuller® FH-1272-B

Version 1.1 Revision Date 12/08/2015

## Persistence and degradability

No data available

**Bioaccumulative potential** 

## Mobility in soil

No data available

#### Other adverse effects

No data available

# **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

Waste from residues : This product meets the definition of hazardous waste under

the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial

authorities for more restrictive requirements.

The hazard and precautionary statements displayed on the

label also apply to any residues left in the container.

# **SECTION 14. TRANSPORT INFORMATION**

## Special precautions for user

Not applicable

# **Domestic regulation**

**49 CFR** 

UN/ID/NA number : 1133
Proper shipping name : Adhesives

Class : 3
Packing group : III
Labels : 3
ERG Code : 128
Marine pollutant : no

# **International Regulation**

IATA-DGR

UN/ID No. : 1133
Proper shipping name : Adhesives

Class : 3
Packing group : III
Labels : 3
Packing instruction (cargo : 366



# H.B. Fuller® FH-1272-B

Version 1.1 Revision Date 12/08/2015

aircraft)

Packing instruction : 355

(passenger aircraft)

**IMDG-Code** 

UN number : 1133

Proper shipping name : ADHESIVES

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E,

EmS Code : F-E, S-D Marine pollutant : no

# Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **SECTION 15. REGULATORY INFORMATION**

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard Chronic Health Hazard

**SARA 302** : The following components are subject to reporting levels established

by SARA Title III, Section 302:

4-methyl-m-phenylene diisocyanate 584-84-9 2-methyl-m-phenylene diisocyanate 91-08-7

SARA 313 : The following components are subject to reporting levels established

by SARA Title III, Section 313:

xylene 1330-20-7 ethylbenzene 100-41-4 4-methyl-m-phenylene 584-84-9

diisocyanate

2-methyl-m-phenylene 91-08-7

diisocyanate

#### Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

xylene 1330-20-7 ethylbenzene 100-41-4

**US State Regulations** 

California Prop 65 WARNING! This product contains a chemical known in the State of



# H.B. Fuller® FH-1272-B

Version 1.1 Revision Date 12/08/2015

California to cause cancer.

ethylbenzene 100-41-4

# The ingredients of this product are reported in the following inventories:

**TSCA** On TSCA Inventory

**DSL** All components of this product are on the Canadian DSL.

**REACH** Not in compliance with the inventory

On the inventory, or in compliance with the inventory **AICS** 

**NZIoC** Not in compliance with the inventory

**ENCS** On the inventory, or in compliance with the inventory **KECI** On the inventory, or in compliance with the inventory **PICCS** On the inventory, or in compliance with the inventory **IECSC** On the inventory, or in compliance with the inventory

**TWINV** Not in compliance with the inventory


Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AICS (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

#### **SECTION 16. OTHER INFORMATION**

Prepared by: Global Regulatory Department - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

#### **Further information**

## NFPA:



Special hazard.

## HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.



# H.B. Fuller® FH-1272-B

Version 1.1 Revision Date 12/08/2015