

In accordance with OSHA 29 CFR 1910.1200

HM 6305 Revision Number 3 Revision date 17-Jun-2024 Supersedes date 16-Jan-2018

1. Identification

1.1. Product identifier

Product Name HM 6305

Other means of identification

Other information Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Hot-melt adhesives
Restrictions on use No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.

11320 W. Watertown Plank Road Wauwatosa, Wisconsin 53226 USA

Phone: +1(800) 726-7845 (Domestic Toll Free) Phone: +1 (414) 774-2250 (International)

E-mail msds@bostik.com

1.4. Emergency telephone number

Emergency Telephone CHEMTREC (Chemical Transportation Emergency Center)

Chemtrec: 1-800-424-9300 (US), 1-703-527-3887 (Outside U.S.)

Rocky Mountain Poison Center: 1-866-767-5089

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Not a dangerous substance or mixture according to OSHA 29 CFR 1910.1200.

Hazards not otherwise classified (HNOC)

Not applicable

2.2. Label elements

EMERGENCY OVERVIEW

Contact with solid material may cause irritation Contact with molten material will cause thermal burns

Not a dangerous substance or mixture according to OSHA 29 CFR 1910.1200.

 Appearance
 Glue sticks
 Physical state
 Solid
 Odor
 No information available

US - EN Page 1 / 10

HM 6305

Revision Number 3

Revision Number 3

Revision Number 3

Revision Number 3

2.3. Other Information

Contact with product at elevated temperatures can result in thermal burns.

3. Composition/information on ingredients

3.1. Substances

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%
Paraffin waxes and Hydrocarbon waxes	8002-74-2	10 - 30

Not a dangerous substance or mixture according to OSHA 29 CFR 1910.1200.

4. First-aid measures

4.1. Description of first aid measures

Inhalation Molten . Move to fresh air in case of accidental inhalation of vapors or decomposition

products. Solid: Not an expected route of exposure.

Eye contact Solid: In case of eye contact, remove contact lens and rinse immediately with plenty of

water, also under the eyelids, for at least 15 minutes. **Molten** . Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Contact with molten

materials requires immediate medical assistance.

Skin contact Solid: . Wash skin with soap and water. Molten . After contact with molten product, cool

skin area rapidly with cold water. For severe burns, immediate medical attention is required. Do not remove clothing if adhering to skin. Removal of solidified molten material from skin

requires medical assistance. Do not try to remove solidified material from the skin.

Ingestion Get immediate medical attention. Do not induce vomiting without medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Contact with molten substance may cause severe burns to skin and eyes.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians Burns caused by molten material must be treated clinically. Treat any burns as thermal

burns, after decontamination.

5. Fire-Fighting Measures

5.1. Extinguishing media

US - EN Page 2 / 10

HM 6305

Revision Number 3

Revision Number 3

Revision Number 3

Revision Number 3

Suitable Extinguishing Media

Large Fire

CO2, dry chemical, dry sand, alcohol-resistant foam. Water spray. CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not use straight streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

The melted product can cause severe burns.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2).

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Fine dust dispersed in air, in sufficient concentrations, and in the presence of an ignition

source is a potential dust explosion hazard.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear.

6. Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Avoid contact

with hot, molten product.

Other information Where possible allow molten material to solidify naturally.

6.2. Environmental precautions

Environmental precautions Keep out of drains, sewers, ditches and waterways. See Section 12 for additional Ecological

Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Molten . Cover with dry sand/earth.

Methods for cleaning up Solid: . Take up mechanically, placing in appropriate containers for disposal. Molten .

Where possible allow molten material to solidify naturally. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust. Clean contaminated surface thoroughly.

Reference to other sections See section 8 for more information. See section 13 for more information.

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Avoid contact with skin and eyes. Wash thoroughly after handling. Take precautionary

US - EN Page 3 / 10

HM 6305

Revision Number 3

Revision Number 3

Revision Number 3

Revision Number 3

measures against static discharges. Use adequate ventilation and/or engineering controls in high temperature processing to prevent exposure to vapors. Facilities for quickly drenching the body should be provided within the immediate work area for emergency use where there is a possibility of exposure.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other

chemicals.

Recommended storage temperature Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

7.3 References to other sections

Reference to other sections Section 10: STABILITY AND REACTIVITY

Section 13: DISPOSAL CONSIDERATIONS

8. Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Paraffin waxes and Hydrocarbon	TWA: 2 mg/m ³ fume	(vacated) TWA: 2 mg/m ³	TWA: 2 mg/m ³ fume
waxes			
8002-74-2			

Chemical name	Argentina	Brazil	S.D. 594/1999	Colombia
Paraffin waxes and Hydrocarbon	TWA: 2 mg/m ³	TWA: 2 mg/m ³	LPP: 1.75 mg/m ³	TWA: 2mg/m ³
waxes				
8002-74-2				

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Paraffin waxes and Hydrocarbon	TWA: 2mg/m ³	TWA: 2mg/m ³	2 mg/m ³ TWA (fume)	TWA: 2 mg/m ³
waxes 8002-74-2				

8.2. Exposure controls

Appropriate engineering controls

Engineering controls Ensure that eyewash stations and safety showers are close to the workstation location.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Wear safety glasses with side shields (or goggles).

Hand protection Heat resistant gloves are recommended when handling molten materials. **Solid:** . For

operations where prolonged or repeated skin contact may occur, impervious gloves should

be worn.

US - EN Page 4 / 10

HM 6305 Revision Number 3 Revision Mumber 3 Supersedes date 16-Jan-2018

Skin and body protectionLong sleeved clothing. Impervious clothing.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Glue sticks
Color Yellow

Odor No information available Odor threshold No information available

Property Values Remarks • Method

pH No data available Not applicable Insoluble in water

pH (as aqueous solution)No data availableNone knownMelting point / freezing pointNo data availableNone knownInitial boiling point and boiling rangeNo data availableNone known

Flash point > 204 °C / 399.2 °F

Evaporation rateNo data availableNone knownFlammabilityNo data availableNone knownFlammability Limit in AirNone known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

No data available None known Vapor pressure No data available Relative vapor density None known Relative density No data available None known Water solubility Insoluble in water None known Solubility(ies) No data available None known No data available None known **Partition coefficient** No data available None known **Autoignition temperature Decomposition temperature** No data available None known Kinematic viscosity No data available None known

Dynamic viscosity 2800 mPa s Spindle 27 @ 50 rpm @ 300 °F

9.2. Other information

Explosive properties

Oxidizing properties

No information available
No information available
No information available

Solid content (%) 100 Softening point @ 230 °F

Molecular weightNo information availableVOC contentNo information available

Density .960 g/cm³

Bulk density No information available

No information available

10. Stability and reactivity

US - EN Page 5 / 10

HM 6305

Revision Number 3

Revision Number 3

Revision Number 3

Revision Number 3

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions
None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Extremes of temperature and direct sunlight. To avoid thermal decomposition, do not

overheat. Do not add water or other volatile material to molten adhesive. Under dusty

conditions avoid all sources of ignition, including sparks and static electricity.

10.5. Incompatible materials

Incompatible materials Strong oxidizing agents, strong acids, and strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products Carbon monoxide Carbon dioxide (CO2) Hydrocarbons

11. Toxicological information

11.1. Information on toxicological effects

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >5000 mg/kg
ATEmix (dermal) 10,010.00 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/l
ATEmix (inhalation-vapor) >20 mg/l

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Paraffin waxes and Hydrocarbon	>5000 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus	-

US - EN Page 6 / 10

HM 6305

Revision Number 3

Revision Number 3

Revision Number 3

Revision Number 3

waxes	cuniculus)	
8002-74-2		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazardBased on available data, the classification criteria are not met.

Other adverse effects

No information available.

Interactive effects

No information available.

12. Ecological information

12.1. Toxicity

Ecotoxicity No information available.

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

12.4. Mobility in soil

Mobility No information available.

Other adverse effects

US - EN Page 7 / 10

HM 6305

Revision Number 3

Revision Number 3

Revision Number 3

Revision Number 3

Other adverse effects No information available.

13. Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and

disposal methods in compliance with applicable regulations.

Contaminated packaging Dispose of in accordance with federal, state and local regulations.

14. Transport information

DOTNot regulatedIATANot regulated

<u>IMDG</u> Not regulated

15. Regulatory information

International Inventories

TSCA	Complies
DSL	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Complies - The components of this product are either listed or exempt from listing on inventory. Active

Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation. This document is based on the information given to us by

US - EN Page 8 / 10

HM 6305
Revision Number 3
Revision Number 3
Revision Number 3
Revision Number 3

our own suppliers at the date of this document.

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

16. Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity ATE: Acute Toxicity Estimate

LC50: 50% Lethal Concentration LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value Sk* Skin designation

Prepared By Product Stewardship and Regulatory Affairs.

Revision date 17-Jun-2024

Revision Note SDS sections updated. 1. 4. 5. 6. 7. 8. 9. 10. 11. 15.

Disclaimer

All information contained herein is believed to be accurate as of the date of publication, is provided "as-is" and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Bostik Inc. ("Company") expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user's application(s). NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN. The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at

https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-mana gement/medical-device-policy/ which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical devices to determine the suitability of all raw material, products and components, including any medical grade products,

US - EN Page 9 / 10

HM 6305 Revision Number 3 Revision date 17-Jun-2024 Supersedes date 16-Jan-2018

in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.

End of Safety Data Sheet

US - EN Page 10 / 10