



# SAFETY DATA SHEET

LIQUID 1007M  
Revision Number 2.01

Revision date 05-Feb-2020  
Supersedes Date: 11-May-2018

## 1. Identification

### 1.1. Product Identifier

Product Name LIQUID 1007M

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives.  
Uses advised against No information available

### 1.3. Details of the supplier of the safety data sheet

#### Responsible Party

Bostik Inc.  
11320 W. Watertown Plank Road  
Wauwatosa, Wisconsin 53226 USA  
Phone: +1 (800) 843-0844 (Domestic Toll Free)  
Phone: +1 (414) 774-2250 (International)  
Fax: +1 (414) 774-8075

E-mail msds@bostik.com

### 1.4. Emergency telephone number

Telephone: 1-800-227-0332  
(Outside U.S.) 1-703-527-3887

## Section 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration hazard	Category 1
Flammable liquids	Category 2

### 2.2. Label Elements

#### EMERGENCY OVERVIEW

Danger

#### Hazard statements

Causes skin irritation  
Causes serious eye irritation  
May cause an allergic skin reaction  
Suspected of causing cancer  
Suspected of damaging fertility or the unborn child

# SAFETY DATA SHEET

**LIQUID 1007M**  
**Revision Number** 2.01

**Revision date** 05-Feb-2020  
**Supersedes Date:** 11-May-2018

May cause respiratory irritation  
May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Highly flammable liquid and vapor



**Appearance** Liquid

**Physical State** Liquid

**Odor** Solvent

## Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Contaminated work clothing should not be allowed out of the workplace  
Do not breathe dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ ventilating/ lighting/ equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool  
Wear protective gloves/protective clothing/eye protection/face protection

## Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.  
In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish.

## Precautionary Statements - Storage

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

## Precautionary Statements - Disposal

Dispose of contents/ container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

Not applicable

## Unknown acute toxicity

# SAFETY DATA SHEET

LIQUID 1007M  
Revision Number 2.01

Revision date 05-Feb-2020  
Supersedes Date: 11-May-2018

26 % of the mixture consists of ingredient(s) of unknown toxicity

## 2.3. Other Information

No information available.

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Mixture

### 3.2 Mixtures

Chemical name	CAS No.	Weight-%
Ethyl acetate	141-78-6	15 - 40
Toluene	108-88-3	10 - 30
Methyl ethyl ketone	78-93-3	7 - 13
Rosin	8050-09-7	3 - 7
Solvent naphtha, petroleum, light aliphatic	64742-89-8	1 - 5
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5
Ethylbenzene	100-41-4	0.1 - 1

*\*The exact percentage (concentration) of composition has been withheld as a trade secret.*

## Section 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
<b>Inhalation</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, give oxygen. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If symptoms persist, call a physician.
<b>Ingestion</b>	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
<b>Self-protection of the first aider</b>	Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** None known.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to physicians** May cause sensitization by inhalation and skin contact. Treat symptomatically.

### 4.4. Reference to Other Sections

# SAFETY DATA SHEET

LIQUID 1007M  
Revision Number 2.01

Revision date 05-Feb-2020  
Supersedes Date: 11-May-2018

**Reference to other sections** See Section 12: ECOLOGICAL INFORMATION  
Section 7: HANDLING AND STORAGE  
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## Section 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable extinguishing media

Use CO<sub>2</sub>, dry chemical, or foam. Move containers from fire area if you can do it without risk.

#### Unsuitable extinguishing media

Use water spray or fog; do not use straight streams.

### 5.2. Special hazards arising from the substance or mixture

#### Specific hazards arising from the chemical

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Thermal decomposition can lead to release of irritating and toxic gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.

**Hazardous combustion products** Carbon oxides.

#### Explosion Data

**Sensitivity to mechanical impact**

None.

**Sensitivity to static discharge**

May be ignited by friction, heat, sparks or flames.

### 5.3. Advice for firefighters

#### Special protective actions for fire-fighters

Move containers from fire area if you can do it without risk. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## Section 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

#### Personal precautions

Use personal protective equipment as required. Remove all sources of ignition. Ensure adequate ventilation, especially in confined areas. Do not touch or walk through spilled material. Evacuate personnel to safe areas.

#### Other information

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

#### For emergency responders

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

### 6.2. Environmental precautions

#### Environmental precautions

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

#### Methods for containment

Dike far ahead of spill; use dry sand to contain the flow of material. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

#### Methods for cleaning up

Use personal protective equipment as required. Dike far ahead of spill for later disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder,

# SAFETY DATA SHEET

LIQUID 1007M  
Revision Number 2.01

Revision date 05-Feb-2020  
Supersedes Date: 11-May-2018

sawdust). Use clean non-sparking tools to collect absorbed material. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly.

## 6.4. Reference to other sections

Reference to other sections See Section 12: ECOLOGICAL INFORMATION  
Section 7: HANDLING AND STORAGE  
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## Section 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

**Advice on safe handling** Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Use explosion-proof electrical/ventilating/ lighting/ equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes or clothing. After contact with skin, wash immediately with plenty of water and soap. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep only in the original container/package in a cool well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Strong acids and bases.

### 7.3. Specific end use(s)

**Specific Use(s)**  
Adhesives.

**Other information** No information available.

### 7.4. References to Other Sections

Reference to other sections See Section 12: ECOLOGICAL INFORMATION  
Section 7: HANDLING AND STORAGE  
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure Guidelines

Chemical name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Ethyl acetate 141-78-6	TWA: 400 ppm	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>	TWA: 400 ppm
Toluene 108-88-3	TWA: 20 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>	TWA: 200 ppm Ceiling: 300 ppm	TWA: 20 ppm
Methyl ethyl ketone 78-93-3	STEL: 300 ppm TWA: 200 ppm	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 300 ppm

# SAFETY DATA SHEET

**LIQUID 1007M**  
**Revision Number** 2.01

**Revision date** 05-Feb-2020  
**Supersedes Date:** 11-May-2018

		STEL: 300 ppm STEL: 885 mg/m <sup>3</sup>		
Rosin 8050-09-7	No data available	TWA: 0.1 mg/m <sup>3</sup> Formaldehyde	-	-
Xylenes (o-, m-, p- isomers) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	-	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm STEL: 150 ppm
Ethylbenzene 100-41-4	TWA: 20 ppm	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	TWA: 20 ppm

Chemical name	Argentina	Brazil	Chile	Venezuela
Ethyl acetate 141-78-6	TWA: 400 ppm	TWA: 310 ppm TWA: 1090 mg/m <sup>3</sup>	TWA: 350 ppm TWA: 1260 mg/m <sup>3</sup>	STEL: 15 ppm TWA: 400 ppm
Toluene 108-88-3	TWA: 50 ppm Skin	TWA: 78 ppm TWA: 290 mg/m <sup>3</sup> Skin	TWA: 87 ppm TWA: 328 mg/m <sup>3</sup> Skin	Skin TWA: 20 ppm
Methyl ethyl ketone 78-93-3	TWA: 200 ppm STEL: 300 ppm	TWA: 155 ppm TWA: 460 mg/m <sup>3</sup>	TWA: 175 ppm TWA: 516 mg/m <sup>3</sup>	STEL: 300 ppm TWA: 200 ppm
Rosin 8050-09-7	-	-	-	TWA:
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 78 ppm TWA: 340 mg/m <sup>3</sup>	TWA: 87 ppm TWA: 380 mg/m <sup>3</sup>	Skin STEL: 150 ppm TWA: 100 ppm
Ethylbenzene 100-41-4	TWA: 100 ppm STEL: 125 ppm	TWA: 78 ppm TWA: 340 mg/m <sup>3</sup>	TWA: 87 ppm TWA: 380 mg/m <sup>3</sup>	Skin STEL: 125 ppm TWA: 100 ppm

## 8.2. Exposure controls

### Engineering controls

Showers  
 Eyewash stations  
 Ventilation systems. Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment [PPE]

#### Eye/face protection

Tight sealing safety goggles. Face protection shield.

#### Skin and body protection

Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

#### Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

#### General hygiene considerations

Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid breathing (dust, vapor, mist, gas). Avoid contact with eyes, skin and clothing. Wash face, hands and any exposed skin thoroughly after handling. Take off all contaminated clothing and wash it before reuse. Regular cleaning of equipment, work area and clothing is recommended.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	Liquid
<b>Color</b>	Amber
<b>Odor</b>	Solvent
<b>Odor threshold</b>	No information available

# SAFETY DATA SHEET

LIQUID 1007M  
Revision Number 2.01

Revision date 05-Feb-2020  
Supersedes Date: 11-May-2018

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No data available	
Boiling point / boiling range	> 77 °C / 171 °F	
Flash point	-7 °C / = 19 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	Not applicable for liquids	
Flammability Limit in Air		
Upper flammability or explosive limits	No information available	
Lower flammability or explosive limits	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	No information available	
Water solubility	No information available	
Solubility in Other Solvents		
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
<b>9.2. Other information</b>		
Softening Point	No information available	
Molecular weight	No information available	
Solvent content (%)	No information available	
Solid content (%)	25.0	
Density	.930 g/ml	
VOC Content (%)		360.0 g/L

## **Section 10: STABILITY AND REACTIVITY**

### **10.1. Reactivity**

Stable under recommended storage conditions.

### **10.2. Chemical stability**

Stable under recommended storage conditions.

### **10.3. Possibility of hazardous reactions**

None under normal processing.

### **10.4. Conditions to avoid**

Keep away from heat, sparks and flames.

### **10.5. Incompatible materials**

Strong acids and bases.

### **10.6. Hazardous decomposition products**

# SAFETY DATA SHEET

LIQUID 1007M  
Revision Number 2.01

Revision date 05-Feb-2020  
Supersedes Date: 11-May-2018

Carbon oxides.

## Section 11: TOXICOLOGY INFORMATION

### 11.1. Information on toxicological effects

<b>Product Information</b>	No data available
<b>Inhalation</b>	May cause drowsiness or dizziness.
<b>Eye contact</b>	Irritating to eyes. Avoid contact with eyes.
<b>Skin contact</b>	Irritating to skin. May cause sensitization by skin contact.
<b>Ingestion</b>	Based on available data, the classification criteria are not met.

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl acetate 141-78-6	=5620 mg/kg (Rattus)	> 18000 mg/kg (Oryctolagus cuniculus) > 20 mL/kg (Oryctolagus cuniculus)	LC0 29.3 mg/l air
Toluene 108-88-3	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h
Methyl ethyl ketone 78-93-3	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
Rosin 8050-09-7	>2000 mg/Kg (Rattus)	> 2500 mg/kg (Oryctolagus cuniculus)	=1.5 mg/L (Rattus) 4 h
Solvent naphtha, petroleum, light aliphatic 64742-89-8	-	= 3000 mg/kg (Oryctolagus cuniculus)	-
Xylenes (o-, m-, p- isomers) 1330-20-7	=3500 mg/kg (Rattus)	> 1700 mg/kg (Oryctolagus cuniculus) > 4350 mg/kg (Oryctolagus cuniculus)	=>47635 mg/L (Rattus) 4 h = >5000 ppm (Rattus) 4 h
Ethylbenzene 100-41-4	=3500 mg/kg (Rattus)	= 15400 mg/kg (Oryctolagus cuniculus)	=17.4 mg/L (Rattus) 4 h

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Symptoms</b>	No information available.
<b>Skin corrosion/irritation</b>	Irritating to skin.
<b>Serious eye damage/eye irritation</b>	Irritating to eyes.
<b>Irritation</b>	No information available.
<b>Corrosivity</b>	No information available.
<b>Sensitization</b>	May cause sensitization of susceptible persons. May cause sensitization by skin contact.
<b>Germ cell mutagenicity</b>	No information available.
<b>Reproductive toxicity</b>	Product is or contains a chemical which is a known or suspected reproductive hazard.
<b>Developmental toxicity</b>	No information available.
<b>Teratogenicity</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	No information available.
<b>Chronic Toxicity</b>	Contains a known or suspected reproductive toxin. May cause adverse liver effects. Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure.
<b>Target organ effects</b>	Central nervous system, Eyes, Skin, Thyroid, Liver, kidney, and respiratory system.
<b>Aspiration hazard</b>	No information available.
<b>Carcinogenicity</b>	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Toluene 108-88-3	-	Group 3	-	-
Xylenes (o-, m-, p- isomers) 1330-20-7	-	Group 3	-	-
Ethylbenzene	A3	Group 2B	-	X



# SAFETY DATA SHEET

**LIQUID 1007M**  
**Revision Number** 2.01

**Revision date** 05-Feb-2020  
**Supersedes Date:** 11-May-2018

100-41-4			
----------	--	--	--

ACGIH (American Conference of Governmental Industrial Hygienists)  
 A3 - *Confirmed animal carcinogen with unknown relevance to humans*  
 IARC (International Agency for Research on Cancer)  
 Group 2B - *Possibly Carcinogenic to Humans*  
 Group 3 - *Not Classifiable as to Carcinogenicity in Humans*  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
 X - *Present*

## Section 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

No information available

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Ethyl acetate 141-78-6	EC50: =3300mg/L (48h, Desmodesmus subspicatus)	LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss) LC50: 220 - 250mg/L (96h, Pimephales promelas)	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50: =560mg/L (48h, Daphnia magna)
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna )
Rosin 8050-09-7	EC50: =400mg/L (72h, Desmodesmus subspicatus)	LC50 (96h) >10mg/L (Danio rerio)	EC50 = 31.5 mg/L 30 min	EC50 48 h >100 mg/L (Daphnia magna )
Solvent naphtha, petroleum, light aliphatic 64742-89-8	EC50: =4700mg/L (72h, Pseudokirchneriella subcapitata)			
Xylenes (o-, m-, p- isomers) 1330-20-7		LC50 96 h 2.6 mg/L (Oncorhynchus mykiss ) (OECD 203)	EC50 = 0.0084 mg/L 24 h	EC50 48 h = 3.4 mg/L (Daphnia magna)
Ethylbenzene 100-41-4	EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

No information available.

### 12.4. Mobility in soil

No information available.

### Other adverse effects

No information available

## Section 13: DISPOSAL CONSIDERATIONS

# SAFETY DATA SHEET

LIQUID 1007M  
Revision Number 2.01

Revision date 05-Feb-2020  
Supersedes Date: 11-May-2018

## 13.1. Waste treatment methods

**Disposal of Wastes** It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations

**Contaminated packaging** Dispose of in accordance with federal, state and local regulations

## Section 14: TRANSPORT INFORMATION

**Note:** The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition)  
The information shown here, may not always agree with the bill of lading shipping description for the material

### DOT

<b>UN/ID No</b>	UN1133
<b>Proper Shipping Name</b>	Adhesives
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>Reportable Quantity (RQ)</b>	(Toluene: RQ (kg)= 0.454, 2-Chloro-1,3-butadiene: RQ (kg)= 0.454, Xylenes (o-, m-, p-isomers): RQ (kg)= 45.40, Ethyl acetate: RQ (kg)= 2270.00, Methyl ethyl ketone: RQ (kg)= 2270.00)
<b>Special Provisions</b>	149, B52, IB2, T4, TP1, TP8
<b>Description</b>	UN1133, Adhesives, 3, II
<b>Emergency Response Guide Number</b>	128

### IATA

<b>UN number</b>	UN1133
<b>Proper Shipping Name</b>	Adhesives
<b>Transport hazard class(es)</b>	3
<b>Packing group</b>	II
<b>ERG Code</b>	3L
<b>Special Provisions</b>	A3
<b>Description</b>	UN1133, Adhesives, 3, II

### IMDG

<b>UN number</b>	UN1133
<b>UN proper shipping name</b>	Adhesives
<b>Transport hazard class(es)</b>	3
<b>Packing group</b>	II
<b>EmS-No.</b>	F-E, S-D
<b>Description</b>	UN1133, Adhesives, 3, II, (-7°C c.c.)

## Section 15: REGULATORY INFORMATION

### Global Inventories

TSCA	Listed
DSL	Listed

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

**Listed** - The components of this product are either listed or exempt from listing on inventory.

**Not Listed** - One or more components of this product are not listed on inventory.

# SAFETY DATA SHEET

LIQUID 1007M  
Revision Number 2.01

Revision date 05-Feb-2020  
Supersedes Date: 11-May-2018

## United States of America

### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.
Toluene	108-88-3
Xylenes (o-, m-, p- isomers)	1330-20-7
Ethylbenzene	100-41-4

### SARA 311/312 Hazard Categories

Classification is shown in section 2 of this SDS

## Europe

### **Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU**

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation

### **SVHC: Substances of Very High Concern for Authorization:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **Section 16: OTHER INFORMATION**

### **Key or legend to abbreviations and acronyms used in the safety data sheet**

No information available

### **Key Literature References and Sources for Data**

No information available

<b>Prepared By</b>	Product Safety & Regulatory Affairs
<b>Revision date</b>	05-Feb-2020
<b>Revision note</b>	SDS sections updated, 1, 11, 15.
<b>Training Advice</b>	Provide adequate information, instruction, and training for operator
<b>Further information</b>	No information available

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**